

日本 三菱牌 無熔線斷路器

三菱 104/07 版

型式	IEC947-2 版斷容量 KA (Icu/Ics)				尺寸(mm)			機種	極數	AF	電 流 容 量		定 價	
	110V	230V	380V	440V	W	L	H				AT (跳脫電流)			
B H 型 分 電 盤 用 品	5	-	-	-	25	95	58	BH-S M3	1	60	5,10,15,20,30		430	
	5	5	3	3	50						40,50,60		480	
					75	10,15,20,30			1,200					
	10	10	6	6	50	40,50,60			1,380					
					75	15,20,30		2,340						
	軌 道 式	IEC898 10		IEC947-2 15		17.5	86	50	FAZ-C(金鐘)	1	63	20,25,32,40,50		380
		-		IEC947-2 25		35						16,20,25,32,40,50		1,010
						52.5						3,16,25,40,50,63		1,800
-		IEC947-2 25		54	86	50	AZ-2-C(金鐘)	2	125	80,100,125		2,820		
				81						80,100,125		4,320		
				-						-		54	80,100,125	
配 電 盤 用 工 業 用 型		2.5	2.5	1.5	-	45	96	52	NF-30CS	2	30	3,5,10,15,20,30		900
		7.5		5		68						3,4,6,10,16,20,25,32		1,210
	50					售完為止		1,230						
	7.5		5		75	130	68	NF-32SW	2	32	3,4,6,10,16,20,25,32		1,620	
					75						售完為止		1,620	
	7.5		5		50	130	68	NF-63CV	2	63	3,(4),(5),6,10,(15),16,20,25		1,490	
					75						(30),32,40,50,(60),63		1,720	
	15		7.5		50	130	68	NF-63SV	2	63	3,(4),(5),6,10,(15),16,20,25		1,720	
					75						(30),32,40,50,(60),63		2,080	
	25		10		50	130	68	NF-63HV	2	63	10,(15),16,20,25,(30),32		1,920	
					75						40,50,(60),63		2,290	
	30		10		60	130	68	NF-125CV	2	125	50,(60),63,(75),80,100,125		2,130	
					90						售完為止		2,850	
	50		30		60	130	68	NF-125SV	2	125	(15),16,20,(30),32,40,50,(60)		3,170	
					90						63,(75),80,100,125		4,020	
	100		50		90	130	68	NF-125HV	2	125	(15),16,20,(30),32,40,50,(60)		4,950	
					90						63,(75),80,100,125		5,880	
	85		36		105	165	68	NF-125SGV	3	125	16~20,20~25,25~32,32~40		6,500	
105					35~50,45~63,56~80,70~100						9,560			
100		75		105	165	68	NF-125HGV	3	125	90~125 可調整		9,560		
				105						售完為止		9,560		
125		125		105	240	86	NF-125RGW(RT)	3	125	16~25,25~40,40~63,63~100 可調		27,130		
				105						售完為止		27,130		
36		25		105	165	68	NF-250CV	3	250	(100),125,150,175,200,225,250		5,840		
				105						售完為止		5,840		
85		36		105	165	68	NF-250SV	3	250	125,150,175,200,225,250		8,100		
				105						售完為止		8,100		
100		75		105	165	68	NF-250HV	3	250	125,150,175,200,225,250		8,660		
				105						售完為止		8,660		
85		36		105	165	68	NF-250SGV	3	250	125~160,140~200,175~250		12,980		
				105						可調整		13,870		
100		75		105	165	68	NF-250HGV	3	250	125~160,160~200,200~250		38,350		
				105						售完為止		38,350		
150		150		105	165	68	NF-250RGV	3	250	125~160,160~200,200~250		38,350		
				105						售完為止		38,350		
50		40		140	257	103	NF-400CW	2	400	250,300,350,400		10,270		
				140						售完為止		13,130		
85		50		140	257	103	NF-400SW	2	400	250,300,350,400		15,070		
				140						售完為止		17,570		
100		70		140	257	103	NF-400HEW	3	400	200,225,250,300,350,400		28,020		
				140						可調整		32,200		
150		125		140	257	103	NF-400REW	3	400	可調整		32,200		
				140						售完為止		32,200		
50		40		140	257	103	NF-630CW	3	630	500,600,630		23,510		
				140						售完為止		23,510		
85		50		140	257	103	NF-630SW	3	630	500,600,630		24,990		
				140						售完為止		24,990		
100		70		140	257	103	NF-630HEW	3	630	300,350,400,500,600,630		36,490		
				140						可調整		41,690		
150		125		140	257	103	NF-630REW	3	630	可調整		41,690		
				140						售完為止		41,690		
50		40		210	275	103	NF-800CEW	3	800	400,450,500,600,700,800		37,110		
				210						可調整		38,740		
85		50		210	275	103	NF-800SEW	3	800	可調整		38,740		
				210						售完為止		38,740		
100		70		210	275	103	NF-800HEW	3	800	400,450,500,600,700,800		42,800		
				210						可調整		42,800		
150		125		210	275	103	NF-800REW	3	800	可調整		49,480		
				210						售完為止		49,480		
125		85		210	406	140	NF-1000SEW	3	1000	500~1000 可調整		68,910		
				210						售完為止		68,910		
125		85		210	406	140	NF-1250SEW	3	1250	600~1250 可調整		84,120		
				210						售完為止		84,120		
125		85		210	406	140	NF-1600SEW	3	1600	800~1600 可調整		124,940		
				210						售完為止		124,940		
125		85		210	406	140	NF-2000S	3	2000	(1800),2000		期貨詢價		
				210						售完為止		期貨詢價		

日本 三菱牌 漏電斷路器

三菱 104/07 版

型式	遮斷容量(KA)			感度電流(mA)	機 種	極 數	AF	電 流 容 量		定 價
	110V	220V	440V					AT (跳 脫 電 流)		
漏 電 過 載 短 路 保 護 器	1.5	1.5	-	15,30mA(迷你型)	NV-L20	2	30	30		550
	10	10	5	30,100/200/500 切換	NV-32SV	3	30	5,10,15,20,(30),32		3,460
	7.5	7.5	-	30	NV-63CV	2	63	(5),(10),15,20,30,40,50,(60),63		3,000
	7.5	7.5	2.5	30,100/200/500 切換		3		(5),(10),15,20,30,40,50,(60),63		3,200
	15	15	7.5	(30),100/200/500 切換	NV-63SV	3	63	(5),(10),15,20,30,40,50,(60),63		3,600
	25	25	10	(30),100/200/500 切換	NV-63HV	3	63	15,20,30,40,50,(60),63		4,150
	30	30	10	(30),100/200/500 切換	NV-125CV	3	125	(60),63,(75),80,100,125		5,360
	50	50	25	(30),100/200/500 切換	NV-125SV	3	125	(15),16,20,(30),40,50,(60),63		14,190
	100	100	50	(30),100/200/500 切換	NV-125HV	3		(75),80,100,125		15,600
	35	35	15	(30),100/200/500 切換	NV-250CV	3	250	125,150,175,200,225,250		8,840
	50	50	25	(30),100/200/500 切換	NV-250SV	3	250	125,150,175,200,225,250		15,750
	100	100	50	(30),100/200/500 切換	NV-225HW	3	225	125,150,175,200,225 售完為止		17,340
	50	50	25	(30),100/200/500 切換	NV-400CW	3	400	250,300,350,400		19,890
	85	85	50	(30),100/200/500 切換	NV-400SW	3	400	250,300,350,400		27,500
	100	100	65	(30),100/200/500 切換	NV-400HEW	3	400	200~400 可調整		41,050
	50	50	35	100/200/500 切換	NV-630CW	3	600	500,600,630		47,120
	85	85	50	100/200/500 切換	NV-630SW	3	600	500,600,630		54,650
	100	100	65	100/200/500 切換	NV-630HEW	3	600	300~630 可調整		60,090
	85	85	50	100/200/500 切換	NV-800SEW	3	800	400~800 可調整		81,340
100	100	65	100/200/500 切換	NV-800HEW	3	800	400~800 可調整		90,610	
註: ()內之機型為訂製品或期貨										定價
其 他	漏電電驛	NV-ZBA	電壓:AC120-240V 切換, 感度電流:30,200/500 切換		43*70*118mm				4,680	
		NV-ZSA	電壓:AC120-240V/240-415V 切換, 感度電流:30,200/500 切換		63*83*117mm				7,500	
	零 相 比 流 器	ZT-15B	孔徑:15mm 外型尺寸:48*70*52 mm						4,170	
		ZT-30B	孔徑 30mm 外型尺寸:68*90*52 mm						4,740	
		ZT-40B	孔徑 40mm 外型尺寸:85*100*52 mm						5,550	
		ZT-60B	孔徑 60mm 外型尺寸:140*150*90 mm						9,550	
		ZT-80B	孔徑 80mm 外型尺寸:160*169*90 mm						10,680	
ZT-100B	孔徑 100mm 外型尺寸:185*190*90 mm						14,630			
補 助 開 關	型 式		適 用 機 種 及 規 格 說 明						定 價	
	AX-05SV		NF32-SV,NF63-CV/SV/HV,NV32-SV,NV63-CV/SV/HV						1,490	
	AX-05SVRS		NF32-SV,NF63-CV/SV/HV,NV32-SV,NV63-CV/SV/HV						1,860	
	AX-05SVLS		NF125-CV/SV/HV/SGV/HGV/RGV,NV125-CV/SV/HV							
	AX-05SVSLT		NF/NV-250CV/SV/SGV/HGV/RGV/SEV/HEV							
	AX-4SW		NF/NV400,630,800-CW/SW/CEW/SEW/HEW/REW						1,800	
	AX-10SWR(L)		NF1000/1250/1600-SEW						3,190	
	警 報 開 關	AL-05SV		NF/NV32/63CV/SV/HV,NF/NV125/250-CV/SV/HV/SGV/HGV/RGV						1,600
		AL-05SVRS		NF32-SV,NF63-CV/SV/HV,NV32-SV,NV63-CV/SV/HV						1,970
		AL-05SVLS		NF125-CV/SV/HV/SGV/HGV/RGV,NV125-CV/SV/HV						
AL-05SVSLT		NF/NV-250CV/SV/SGV/HGV/RGV/SEV/HEV								
AL-4SWL		NF/NV400,630,800-CW/SW/CEW/SEW/HEW/REW						2,100		
AL-10SWL		NF1000/1250/1600-SEW						4,700		
電 壓 跳 脫	SHTA-05SVR		NF/NV32/63CV/SV/HV,NF/NV125/250-CV/SV/HV/SGV/HGV/RGV						2,600	
	SHTA-05SVL									
	SHT-4SW		NF400,630,800-CW/SW/CEW/SEW/HEW/REW						4,300	
	SHT-10SWR		NF1000,1200,1600-SS						4,810	
低 電 壓 跳 脫	UVTNA-05SVR		NF/NV32/63CV/SV/HV,NF/NV125/250-CV/SV/HV/SGV/HGV/RGV						6,600	
	UVTNA-05SVL									
	UVTNA-4SW		NF400,630,800-CW/SW/CEW/SEW/HEW/REW						8,840	
UVTNA-10SWR		NF1000/1200/1600-SEW						12,860		
操 作 把 手	F05SV		NF32-SV,NF63-CV/SV/HV,NV32-SV,NV63-CV/SV/HV3P/4P						2,250	
	F1SV		NF125-CV/SV/HV,NV125-CV/SV/HV 3P/4P						2,250	
	F2SV		NF-250CV/SV/HV,NV125/NF250-SGV/HGV3/4P NV250-CV/SV/HV/SEV/HEV 3P						2,630	
	F4S		NF400/630-CW/SW/SEW/HEW/REW 3/4P						4,000	
	F8S		NF800-CEW/SEW/HEW/REW 3/4P						5,640	
	F10SW		NF1000,1200,1600-SEW 3P						6,320	

日本 三菱牌 電磁接觸器 . 熱動電驛 . 補助接點

三菱 104/07 版

AC1 (A)	補助 接點	額定電流 AC3		S 型電磁接觸器		直流用電磁接觸器		2 素子熱動電驛		欠相用 3 素子熱動電驛	
		220V	440V	機種	定價	機種	定價	機種	定價	機種	定價
20	1a 或 1b	11	7	S-T10	630	SD-N11	2,240	TH-T18	690	TH-T18KP	990
20	1a1b	13	9	S-T12	900	SD-N12	2,740				
32	1a1b	20	20	S-T20	1,190			TH-T25	710	TH-T25KP	1,050
32	2a2b	20	20	S-T21	1,230	SD-N21	3,490				
50	2a2b	26	25	S-T25	1,760			TH-N20TA	990	TH-N20TAKP	1,360
60	2a2b	35	32	S-N35	2,320	SD-N35	4,490				
80	2a2b	50	46	S-N50	2,780	SD-N50	4,980	TH-N60	1,610	TH-N60KP	2,600
100	2a2b	65	65	S-N65	3,450	SD-N65	7,720				
135	2a2b	80	80	S-N80	5,570	SD-N80	11,580	TH-N60TA	1,860	TH-N60TAKP	2,850
150	2a2b	100	93	S-N95	5,910	SD-N95	13,200				
150	2a2b	125	120	S-N125	7,940	SD-N125	19,920	TH-N120	2,730	TH-N120KP	3,600
200	2a2b	150	150	S-N150	11,470	SD-N150	22,410	TH-N120TA	3,100	TH-N120TAKP	3,720
260	2a2b	180	180	S-N180	14,040			TH-N220RH	5,210	TH-N220RHKP	6,320
260	2a2b	220	220	S-N220	17,660	SD-N220	37,980				
350	2a2b	300	300	S-N300	24,700	SD-N300	78,440	TH-N400RH	6,420	TH-N400RHKP	7,690
450	2a2b	400	400	S-N400	28,840	SD-N400	133,840				
660	2a2b	630	630	S-N600	64,800	SD-N600	173,060				
800	2a2b	800	800	S-N800	100,080	SD-N800	197,860				

額定容量 HP		補助 接點 構成	開放式電磁開關		正逆電磁開關		機械連鎖		補助接點	
220V	380V		機種	定價	機種(二素子)	定價	機種	定價	機種	定價
3	3.5	1a 或 1b	MSO-T10	1,170			UN-ML11	1,190	UT-AX2 T10-T32 用上裝式	410
3.5	5	1a1b/2b	MSO-T12	1,340	MSO-2xT12	3,970	N10-N12 用			
5	10	1a1b	MSO-T20	1,750	MSO-2xT20	5,340	UN-ML21 N18-N65 用	1,010	UT-AX4 T10-T32 用上裝式	750
5	10	2a2b	MSO-T21	1,810	MSO-2xT21	5,580				
7.5	15	2a2b	MSO-T25	2,360	MSO-2xT25	6,200			UT-AX11 T10-T32 用	660
10	20	2a2b	MSO-N35	3,060	MSO-2xN35	6,940			UN-AX4 N35-N65 用	750
15	25	2a2b	MSO-N50	3,820	MSO-2xN50	8,930				
20	35	2a2b	MSO-N65	4,260	MSO-2xN65	13,760			UN-AX80 N80-N125 用側裝式	800
25	40	2a2b	MSO-N80	6,270	MSO-2xN80	16,120				
30	60	2a2b	MSO-N95	7,500	MSO-2xN95	23,140	UN-ML80 N80-N125 用	1,560	UN-AX150 N150-N400 用側裝式	830
40	75	2a2b	MSO-N125	9,620	MSO-2xN125	32,530				
50	100	2a2b	MSO-N150	13,620	MSO-2xN150	39,970	UN-ML150 N150 用	1,560		
60	125	2a2b	MSO-N180	17,230	MSO-2xN180	54,800	UN-ML220 N180-N400 用	1,820	UN-AX150 N150-N400 用側裝式	830
75	150	2a2b	MSO-N220	23,040	MSO-2xN220	55,160				
100	180	2a2b	MSO-N300	32,220	MSO-2xN300	78,650				
150	300	2a2b	MSO-N400	38,660	MSO-2xN400	84,860				

電磁繼電器 (直流用) 16A				電磁繼電器 (交流用) 16A			
線圈電壓	接點構成	機種	定價	線圈電壓	接點構成	機種	定價
DC24V DC48V DC110V DC220V	4a,3a1b,2a2b	SRD-N4□□	2,230	AC120V AC220V AC380V AC440V AC550V	3a2b,4a1b,5a	SR-T5□□	740
	5a,4a1b,3a2b,2a3b	SRD-N5□□	2,350				
	8a,6a2b,4a4b,7a1b,5a3b	SRD-N8□□	2,600		9a,7a2b,5a4b	SR-T9□□	930
	10a,8a2b,7a3b,6a4b,5a5b	SRD-K100□□	4,710				
	4a,3a1b,2a2b	SRLD-N4□□	4,340				
5a4b,4a5b,6a3b 7a2b,8a1b,9a	SRLD-K100□□	6,820	5a4b,9a	SRL-K100□□	6,200		