

台製 士林牌 無熔線斷路器 · 漏電斷路器

士林 108/01 版

型式	啓斷容量 KA(Icu/Ics)				機 種		極數	AF	電 流 容 量		定 價
	110V	220V	380V	440V					AT (跳脫電流)		
BH系列 (分電盤用品)	5	-	-	-	BH (一般型)	BPL (插入式)	1	50	10,15,20,30,40,50	100	
	-	5	-	-				100	15,20,30,40,50	130	
	5	-	-	-			2	100	100	60,75,100 (BPL無60A以上)	195
	5	5	-	-					10,15,20,30,40,50	220	
									60,75,100	480	
	-	-	-	-			10,15,20,30,40,50	490			
	10	-	-	-	BHU (一般型)	BLU (插入式)	1	50	15,20,30,40,50	140	
	-	10	-	-				100	15,20,30,40,50	210	
	10	10	-	-			2	100	15,20,30,40,50	310	
									15,20,30,40,50	680	
									60,75,100	660	
	15	10	-	-			3	100	60,75,100	1,320	
					60,75,100	490					
	15	15	10	-	BHH (一般型)	-	1	50	15,20,30,40,50	225	
								100	15,20,30,40,50	465	
								100	60,75,100	1,030	
	15	10	-	-	2	100	15,20,30,40,50	1,100			
							60,75,100	1,690			
							60,75,100	490			
	15	15	10	-	BAH (插入式)	-	1	100	15,20,30,40,50	225	
100								15,20,30,40,50	470		
100								60,75,100	1,030		
22	-	-	-	BHS (一般型)	-	2	50	15,20,30,40,50	340		
							50	15,20,30,40,50	370		
							100	15,20,30,40,50	680		
22	22	-	-	3	100	60,75,100	1,080				
						15,20,30,40,50	1,130				
						15,20,30,40,50	1,710				
純漏電及插座	1	-	-	-	NV-CST1 一般型	2	15	15 漏電保護插座	450		
	1	-	-	-	NV-CST2 接地型	2	15	15 漏電保護插座	450		
	1	-	-	-	NV-BWT2 雙插接地型	2	15	15 漏電保護插座 15mA	1,400		
	1.5	1.5	-	-	NV-BF(迷你型)	2	30	15,20,30	300		
	2.5	2.5	迷你型	-			40	40	370		
	2.5	2.5	2.5	2.5	NV-SF	2	60	50, 60	640		
	1.5	1.5	-	-	NV-KF	2	30	15,20,30	400		
	2.5	2.5	-	-			40	40	470		
	1.5	1.5	-	-	NV-K30F	3	30	15,20,30	605		
-	-	1.5	1.5	660							
漏電過載	1.5	1.5	-	-	NV-KLF	1	30	15,20,30	500		
	-	-	-	-	2	535					
BH型 漏電斷路器	5	-	-	-	NVB-50L (一般型)	NVP-50L (插入式)	1	50	15,20,30,40,50	460	
	-	5	-	-	2	660					
	10	-	-	-	NVB-50UL (一般型)	NVP-50UL (插入式)	1	50	15,20,30,40,50	565	
	-	10	-	-	2		945				
	10	5	-	-	NVB-50HS	1	50	15,20,30,40,50	565		
	-	10	-	-					940		
	15	10	-	-	2	1,005					
	-	15	-	-			1,395				
工業型 無熔線 斷路器 (特殊訂製品)	10/5	10/5	7.5/3.8	7.5/3.8	NF50-SN(特殊訂製品)		2	50	10,15,20,30,40,50	1,010	
	25/13	25/13	15/7.5	10/5	NF50-HN(特殊訂製品)	3	1,130				
						4	1,980				
						2	1,030				
	15/7.5	15/7.5	10/5	7.5/3.8	NF100-MN(特殊訂製品)	3	50	10,15,20,30,40,50	1,180		
						2	2,060				
						4	1,040				
						2	1,210				
	50/25	50/25	30/15	25/13	NF100-HN(特殊訂製品)	4	100	10,15,20,30,40,50	2,070		
						2	1,330				
						3	60,75,100	1,570			
	30/15	30/15	22/11	15/7.5	NF225-CN(特殊訂製品)	4	100	10,15,20,30,40,50,60,75,100	2,920		
						2	2,020				
						3	2,140				
	50/25	50/25	30/15	25/13	NF225-SN(特殊訂製品)	4	225	125,150,175,200,225	3,950		
2						2,900					
3						3,400					
DC用	DC125V/5KA	DC250V/2.5KA	NF50-CB		2	50	10,15,20,30,40,50	750			
	DC125V/7.5KA	DC250V/5KA	NF50-SB					960			
	DC125V/15KA	DC250V/10KA	NF50-HS					990			

台製 士林牌 無熔線斷路器

士林 108/01 版

型式	啓斷容量 KA(Icu/Ics)				機種	極數	AF	電流容量 AT (跳脫電流)	定價
	110V/220V	380V	440V	550V					
N F 型 系 列 無 熔 線 斷 路 器 (配 電 · 配 線 用) 工 業 用 型	5/2.5	2.5/1.3	2.5/1.3	1.5/0.8	NF30-SN	2 3 4	30	3,5,10,15,20,30	540 770 1,460
	5/2.5	2.5/1.3	2.5/1.3	1.5/0.8	NF50-CN	2 3 4	50	10,15,20,30,40,50	790 830 1,740
	10/5	7.5/3.8	7.5/3.8	5/2.5	NF100-CN	2 3 4	100	10,15,20,30,40,50	940 1,040 1,830
	25/13	15/7.5	10/5	7.5/3.8	NF100-SN	2	100	10,15,20,30,40,50	1,140
						3			1,450
						4			2,630
						2			1,030
	30/15	22/11	15/7.5	7.5/3.8	NF125-SN	3	125	10,15,20,30,40,50	1,180
						4			2,060
						2			1,170
						3			1,490
	50/25	30/15	25/13	15/7.5	NF125-HN	4	125	10,15,20,30,40,50	2,860
						2			1,210
						3			1,670
						4			2,850
	85/43	50/25	42/21	25/13	NF100-H	2	100	15,20,30,40,50,60,75,100	1,310
						3			1,710
						4			3,160
						2			1,880
	100/50	65/33	50/25	30/15	NF100-HC	3	100	15,20,30,40,50,60,75,100	2,030
						4			3,550
						2			2,020
						3			2,140
	30/15	22/11	15/7.5	7.5/3.8	NF250-CN	4	250	125,150,175,200,225	3,950
						2			4,130
						3			5,360
						4			5,610
	50/25	30/15	25/13	15/7.5	NF250-SN	2	250	125,150,175,200,225	4,700
						3			4,900
						4			5,720
2						4,490			
85/43	50/25	42/21	25/13	NF225-HB	3	225	125,150,175,200,225	4,840	
					4			4,720	
					2			5,290	
					3			6,090	
100/50	65/33	50/25	30/15	NF225-HC	4	225	125,150,175,200,225	6,690	
					2			11,060	
					3			7,480	
					4			7,800	
35/18	25/13	22/11	14/7	NF400-CN	2	400	250,300,350,400	11,630	
					3			8,290	
					4			8,760	
					2			11,680	
50/25	35/18	30/15	20/10	NF400-SN	3	400	250,300,350,400	8,340	
					4			9,570	
					2			13,120	
					3			16,000	
85/43	50/25	50/25	25/13	NF630-CN	4	630	500,600,630	13,510	
					2			16,490	
					3			14,650	
					4			16,700	
100/50	65/33	50/25	30/15	NF600HC	3	600	500,600	15,320	
					4			19,540	
					2			23,430	
					3			20,060	
50/25	35/18	30/15	20/10	NF800-CN	4	800	700,800	23,810	
					2			20,420	
					3			25,870	
					4			26,410	
85/43	50/25	50/25	25/13	NF800-E	3	800	400 ~ 800 電子可調式	37,960	
					4			40,880	
					2			46,080	
					3			49,280	
130/65	100/50	85/43	65/33	NF1000-E	3	1000	500 ~ 1000 電子可調式	57,930	
					4				
					2				
					3				
125/63	85/43	85/43	50/25	NF1200-E	3	1200	600 ~ 1200 電子可調式		
					4				
					2				
					3				
130/65	100/50	85/43	65/33	NF1600-HS	3	1600	1400,1600		
					4				
					2				
					3				

台製 士林牌 工業型漏電斷路器&高啓斷&電子式

士林 108/01 版

型式	啓斷容量 KA(Icu/Ics)			機種	極數	AF	電流容量 AT (跳脫電流)	定價		
	220V	380V	440V					高速固定	高速可調	延時可調
工業型 ELCB (延時型訂貨需特別註明)	10/5	7.5/3.8	7.5/3.8	NV30-SN	3	30	15,20,30	1,900	2,060	2,140
					4			3,080	3,380	3,430
	10/5	7.5/3.8	7.5/3.8	NV50-SN	3	50	15,20,30,40,50	2,200	3,310	2,400
					4			3,510	3,810	3,870
	25/13	15/7.5	10/5	NV50-HN	3	50	15,20,30,40,50	2,560	2,830	2,900
					4			3,940	4,450	4,500
	10/5	7.5/3.8	7.5/3.8	NV100-CN	3	100	60,75,100	2,810	3,050	3,220
					4			4,700	5,050	5,130
	15/7.5	10/5	7.5/3.8	NV100-MN	3	100	15,20,30,40,50	3,130	3,270	3,350
					4		60,75,100	5,430	5,780	5,870
	25/13	15/7.5	10/5	NV100-SN	3	100	15,20,30,40,50	3,420	3,510	3,640
					4		60,75,100	5,930	6,280	6,380
	30/15	22/11	15/7.5	NV125-SN	3	125	15,20,30,40,50	3,970	4,310	4,470
					4		60,75,100	6,890	7,240	7,360
	50/25	30/15	25/13	NV225-SN	3	225	125,150,175,200,225	4,420	4,760	4,940
					4		60,75,100	7,660	8,010	8,140
	30/15	22/11	15/7.5	NV250-CN	3	250	250	4,250	4,600	4,770
					4		60,75,100	7,380	7,730	7,850
	50/25	30/15	25/13	NV250-SN	3	250	250	4,700	5,040	5,230
					4		60,75,100	8,150	8,500	8,640
	30/15	22/11	15/7.5	NV225CN	3	225	125,150,175,200,225	4,950	5,280	5,480
					4		60,75,100	8,570	8,920	9,070
	50/25	30/15	25/13	NV225-SN	3	225	125,150,175,200,225	6,220	6,460	6,560
					4		60,75,100	10,400	10,790	11,350
	30/15	22/11	15/7.5	NV250-CN	3	250	250	7,890	8,180	8,210
					4		60,75,100	18,410	19,100	19,660
	50/25	30/15	25/13	NV250-SN	3	250	250	-	6,460	6,560
					4		60,75,100	-	10,790	11,350
	35/18	25/13	22/11	NV400-CN	3	400	250,300,350,400	-	8,180	8,210
					4		60,75,100	-	19,100	19,660
	50/25	35/18	30/15	NV400-SN	3	400	250,300,350,400	-	10,830	11,150
					4		60,75,100	-	18,770	19,330
	85/43	50/25	42/21	NV400-HN	3	400	250,300,350,400	-	12,520	12,840
					4		60,75,100	-	26,280	26,850
	125/63	85/43	85/43	NV400-UN	3	400	250,300,350,400	-	23,050	23,380
					4		60,75,100	-	36,320	36,820
	125/63	85/43	85/43	NV800-RN	3	800	500,600,630	-	詢價	詢價
					4		60,75,100	-	詢價	詢價
	125/63	85/43	85/43	NV800-RN	3	800	700,800	-	詢價	詢價
					4		60,75,100	-	詢價	詢價

備註
 NV30/50SN.NV100CN/MN/SN.NV125SN/HN 高速固定型 mA 為 15,30,50,100mA 高速/延時可調型 mA 為 100/300/500mA 可調
 NV225CN.NV225SN 為 30mA 高速/延時可調型 mA 為 100/300/500mA 可調
 NV250CN/SN.NV400CN/SN/HN 高速可調型 mA 為 30/100/500mA 延時可調型 mA 為 100/300/500mA 可調

型式	240V	380V	440V	550V	機種	AF	AT (跳脫電流)	2P	3P	4P
	高啟斷 NFB	125/63	85/43	85/43				65/33	NF250-HS	250
	125/63	85/43	85/43	65/33	NF400-UN	400	250,300,350,400	詢價	詢價	詢價
								500,600,630	詢價	詢價
	125/63	85/43	85/43	65/33	NF800-RN	800	700,800	詢價	詢價	詢價
								詢價	詢價	
電子式 NFB	125/63	85/43	85/43	65/33	NF100-UE	100	100 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	詢價	詢價	詢價
	125/63	85/43	85/43	65/33	NF250-UE	250	250 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	詢價	詢價	詢價
	125/63	85/43	85/43	65/33	NF400-UE	400	400 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	詢價	詢價	詢價
	125/63	85/43	85/43	65/33	NF800-RE	800	630 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0) 800 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	詢價	詢價	詢價

附屬裝置	適用機種										
	適用 NFB (NF)	30/50 SN 50CN.HN 100C/M/SN	100HN 125SN 125HN	225CN.SN 250CN.SN	400CN 400SN 400HN	630CN.SN 630HN 800CN.SN	800~1600H S	100H 100HC	225HC 225HB	400HC	600HC
警報開關 (AL)		250	300	400	750	750	1,450	392	392	547	938
補助開關 (AUX)		250	300	400	750	750	1,450	392	392	470	782
AL+AUX		-	-	750	1,400	1,400	-	-	-	-	-
電壓跳脫 (SHT)		500	800	1,000	1,200	1,200	1,850	1,160	1,160	1,255	1,800
低電壓跳脫 UVT		1,500	1,700	2,000	2,200	2,200	3,750	-	-	2,297	2,504
外部操作把手 EH		650	680	780	1,740	2,300	-	779	779	-	-
端子隔離蓋 TC□□(S)	2P	TC 100N (S)	100 150 200	TC 125N (S)	120 180 240	TC 250N	220 220 330	690 690 950	-	1,000	1,400

(S)短型保護蓋
(N)一般型隔離蓋

台製 士林牌 低壓交流電磁接觸器

士林 108/01 版

AC1	補助接點	額定電流 AC3		S-P 型 MC 無保護蓋		S-PS 型 MC 附保護蓋		S-2xP 正逆 MC 無保護蓋		S-2xP 正逆 MC 附保護蓋	
		220V	440V	機種	定價	機種	定價	機種	定價	機種	定價
20	1a 或 1b	7.5	6	-	-	S-P06S	270	S-CR11(12A)	910	S-2XP06S	590
20	1a 或 1b	10.1	8	-	-	S-P09S	280	-	-	S-2XP09S	610
20	1a 或 1b	12	9	S-P11	300	S-P11S	310	S-2xP11	850	S-2xP11S	870
20	1a1b 或 2a	12	9	S-P12	360	S-P12S	370	S-2xP12	990	S-2xP12S	1,010
30	1a 或 1b	16	12	S-P15	380	S-P15S	390	S-2xP15	1,020	S-2xP15S	1,040
30	1a1b	16	12	S-P16	450	S-P16S	470	S-2xP16	1,270	S-2xP16S	1,310
40	1a1b	24	21	S-P21	540	S-P21S	560	S-2xP21	1,380	S-2xP21S	1,420
40	2a2b	24	21	S-P21A	570	S-P21AS	590	-	-	-	-
40	1a1b	26	23	S-P25	580	S-P25S	610	S-2xP25	1,500	S-2xP25S	1,550
50	2a2b	30	27	S-P30T	780	S-P30TS	810	S-2xP30T	1,860	S-2xP30TS	1,920
50	2a2b	35	27	S-P35T	800	S-P35TS	840	S-2xP35T	1,910	S-2xP35TS	1,970
65	2a2b	44	40	S-P40T	1,040	S-P40TS	1,070	S-2xP40T	2,290	S-2xP40TS	2,360
80	2a2b	58	52	S-P50T	1,260	S-P50TS	1,310	S-2xP50T	2,790	S-2xP50TS	2,870
100	2a2b	68	65	S-P60T	1,540	S-P60TS	1,580	S-2xP60T	3,360	S-2xP60TS	3,460
130	2a2b	100	90	S-P80T	2,050	S-P80TS	2,090	S-2xP80T	5,220	S-2xP80TS	5,310
150	2a2b	110	105	S-P100T	2,780	S-P100TS	2,820	S-2xP100T	6,660	S-2xP100TS	6,750
170	2a2b	135	130	S-P125T	3,940	S-P125TS	3,990	S-2xP125T	9,480	S-2xP125TS	9,580
200	2a2b	165	160	S-P150T	5,060	S-P150TS	5,110	S-2xP150T	11,340	S-2xP150TS	11,460
235	2a2b	200	190	S-P200T	6,650	S-P200TS	6,740	S-2xP200T	14,690	S-2xP200TS	14,870
250	2a2b	220	190	S-P220T	7,680	S-P220TS	7,770	S-2xP220T	15,950	S-2xP220TS	16,140
350	2a2b	300	300	S-P300	14,570			S-2XP300	32,670		
420	2a2b	400	400	S-P400	21,010			S-2xP400	43,490		
660	2a2b	600	600	S-C600	35,690						

台製 士林牌 過載保護器 · 電磁繼電器 · 補助接點 · 按鈕

士林 108/01 版

額定電流值(A) (可±20%調整)	TH-P 型過載保護器 (無安裝保護蓋)				TH-P□S 型過載保護器 (附安裝保護蓋)			
	機種	2 素子	3 素子(E)	欠相(PP)	機種	2 素子	3 素子(E)	欠相(PP)
0.16,0.24,0.4,0.6,1,1.6,2.4,4,6,9	TH-P09(PP)			250	-	-	-	-
25,0.4,0.6,0.9,1.2,1.7,2.1,3.3,4.4,6.5,9,11,15	TH-12(E)C TYPE	250	290	-	-	-	-	-
	TH-P12(E)(PP)	240	280	290	TH-P12(E)(PP)S	270	300	310
0.25,0.4,0.6,0.9,1.2,1.7,2.1,3.3,4.4,6.5,9,11,15,21	TH-P18(E)(PP)	310	370	380	TH-P18(E)(PP)S	340	390	400
	TH-P20(E)(PP)	310	370	380	TH-P20(E)(PP)S	340	390	400
28,33,40	TH-P20(E)TA(PP)	400	450	480	TH-P20(E)TA(PP)S	440	490	530
11,15,21,28,33,40,54	TH-P60(E)(PP)	590	630	730	TH-P60(E)(PP)S	620	650	760
68,80	TH-P60(E)TA(PP)	650	710	790	TH-P60(E)TA(PP)S	700	760	840
40,54,67,80	TH-P120(E)	1,220	1,350	1,460	TH-P120(E)(PP)S	1,240	1,370	1,490
105,130,160	TH-P120(E)TA	1,300	1,410	1,540	TH-P120(E)TA(PP)S	1,350	1,460	1,590
80,105,130,160,200	TH-P220T(E)CT(PP)	2,570	3,280	3,290	TH-P220T(E)CT(PP)S	2,600	3,310	3,320
105,130,160,200,260,350	TH-P400T(E)CT(PP)	3,390	4,160	4,170	TH-P400T(E)CT(PP)S	3,420	4,180	4,190
260,350,500	TH-P600(E)CT(PP)	8,290	11,870	11,880	TH-P600(E)CT(PP)S	8,320	11,900	11,910

AP-□□ 補助接點組 AC1 (16A)				電磁繼電器 (控制用) SR-P 型 AC1 (16A)			PB 按鈕開關		
2P 上裝式	AP20	65	AP20S	70	型號	接點構成	定價	型式	定價
	AP11	65	AP11S	70	SR-P40	4a,3a1b,2a2b	300	PB-2 ON-OFF	75
	AP02	65	AP02S	70	SR-P40S	4a,3a1b,2a2b	310	PB-3ON-REV-OFF	120
4P 上裝式	AP40	130	AP40S	140	SR-P50	5a,4a1b,3a2b,2a3b	320	機械連鎖	
	AP31	130	AP31S	140	SR-P50S	5a,4a1b,3a2b,2a3b	330	MPU-11	200
	AP22	130	AP22S	140	SR-P80	8a,7a1b,6a2b,5a3b,4a4b	440	MPU-21	200
2P 側裝	APS11	75	APS11S	80	SR-P80S	8a,7a1b,6a2b,5a3b,4a4b	450	MPU-50	220
	APL11	270	APL11S	280	SR-80L	8a,7a1b,6a2b,5a3b,4a4b	440	MPU-125	230

台製 士林牌 低壓交流電磁開關 (無安裝保護蓋) 士林 108/01 版

額定容量 HP(KW)		補助接點構成	開放式 MSO-P 型 (無安裝保護蓋)				封閉式 MS-P 型附 PB-2 (無安裝保護蓋)			
200/220V	380/440V		型 式	二素子	三素子 E	欠相(PP)	型 式	二素子	三素子(E)	欠相(PP)
4(3)	5.5(4)	1a 或 1b	MSO-P11	540	570	580	MS-P11	630	670	680
4(3)	5.5(4)	1a1b	MSO-P12	590	630	640	MS-P12	700	730	740
5(3.7)	7.5(5.5)	1a 或 1b	MSO-P15	630	660	670	MS-P15	730	770	780
5(3.7)	7.5(5.5)	1a1b	MSO-P16	730	780	790	MS-P16	760	800	810
7.5(5.5)	15(11)	1a1b	MSO-P21	820	860	880	MS-P21	910	950	960
7.5(5.5)	15(11)	2a2b	MSO-P21A	860	900	910	MS-P21A	940	980	990
8.5(6.5)	16(12)	1a1b	MSO-P25	890	930	940	MS-P25	930	970	980
10(7.5)	20(15)	2a2b	MSO-P30T	1,160	1,200	1,210	MS-P30T	1,380	1,440	1,450
12.5(9)	20(15)	2a2b	MSO-P35T	1,210	1,260	1,270	MS-P35T	1,470	1,540	1,550
15(11)	30(22)	2a2b	MSO-P40T	1,480	1,550	1,560	MS-P40T	1,700	1,750	1,780
20(15)	40(30)	2a2b	MSO-P50T	1,800	1,850	1,920	MS-P50T	2,160	2,190	2,310
25(19)	50(37)	2a2b	MSO-P60T	2,180	2,210	2,330	MS-P60T	2,490	2,530	2,640
35(25)	70(50)	2a2b	MSO-P80T	2,710	2,730	2,840	MS-P80T	3,080	3,110	3,230
40(30)	80(60)	2a2b	MSO-P100T	4,040	4,200	4,330	MS-P100T	4,410	4,550	4,680
50(37)	100(75)	2a2b	MSO-P125T	5,280	5,400	5,520	MS-P125T	6,160	6,280	6,390
60(45)	125(90)	2a2b	MSO-P150T	6,530	6,660	6,790	MS-P150T	7,650	7,760	7,880
75(55)	150(110)	2a2b	MSO-P200T	9,240	10,020	10,030	MS-P200T	9,910	10,680	10,700
85(65)	150(110)	2a2b	MSO-P220T	9,800	10,480	10,490	MS-P220T	11,100	11,880	11,890
125(90)	220(160)	2a2b	MSO-P300	18,040	18,920	18,930	MS-P300	23,940	24,790	24,800
150(110)	330(220)	2a2b	MSO-P400	23,290	24,150	24,160	MS-P400	31,920	32,750	32,760
220(160)	420(315)	2a2b	MSO-C600	43,410	46,830	46,840	MS-C600	66,790	70,390	70,400

士林牌衝擊式自動 Y-△ 起動開關 機械連鎖式 三台裝 士林 108/01 版

容量 HP		開放式 EYD-O-P 型(S)有保護蓋				封閉式 EYD-E-P 型附 PB-2				封閉式 EYD-A 型附 PB 電表						
220	440V	型 式	二素子	三素子	欠相	型 式	二素子	三素子	欠相	型 式	二素子	三素子	欠相			
15	25	EYD-O-P21		4,620	4,670	4,680	EYD-E-P21		6,030	6,080	6,090	EYD-A-P21	-	6,620	6,670	6,680
			S	4,710	4,770	4,780		S	6,120	6,180	6,190		S	6,710	6,770	6,780
25	40	EYD-O-P35		5,880	5,910	6,020	EYD-E-P35		7,260	7,310	7,420	EYD-A-P35	-	7,950	7,980	8,090
			S	6,000	6,030	6,140		S	7,380	7,430	7,540		S	8,070	8,100	8,210
30	60	EYD-O-P50		7,010	7,040	7,150	EYD-E-P50		8,700	8,730	8,840	EYD-A-P50	-	9,330	9,360	9,470
			S	7,170	7,200	7,310		S	8,860	8,900	9,010		S	9,490	9,520	9,640
40	75	EYD-O-P60		8,530	8,660	8,890	EYD-E-P60		10,120	10,240	10,480	EYD-A-P60	-	10,860	10,980	11,220
			S	8,690	8,810	9,040		S	10,280	10,400	10,650		S	11,020	11,140	11,380
50	100	EYD-O-P80		10,210	10,330	10,570	EYD-E-P80		12,440	12,560	12,800	EYD-A-P80	-	13,260	13,380	13,610
			S	10,380	10,500	10,750		S	12,610	12,740	12,980		S	13,420	13,540	13,790
60	125	EYD-O-P100		12,530	12,660	12,900	EYD-E-P100		15,170	15,300	15,530	EYD-A-P100	-	16,160	16,280	16,520
			S	12,710	12,830	13,060		S	15,330	15,470	15,710		S	16,330	16,450	16,700
75	150	EYD-O-P125		17,130	17,580	17,590	EYD-E-P125		19,960	20,410	20,420	EYD-A-P125	-	20,650	21,100	21,110
			S	17,320	17,770	17,780		S	20,140	20,590	20,600		S	20,830	21,280	21,290
100	180	EYD-O-P150		19,510	20,270	20,300	EYD-E-P150		22,550	23,320	23,330	EYD-A-P150	-	22,940	23,700	23,710
			S	19,700	20,460	20,490		S	22,730	23,490	23,500		S	23,120	23,890	23,900
150	260	EYD-O-P220		27,540	28,370	28,380	EYD-E-P220		30,540	31,380	31,390	EYD-A-P220	-	31,060	31,890	31,900
			S	27,810	28,640	28,650		S	30,780	31,610	31,620		S	31,300	32,140	32,150

士林牌低壓交流非可逆式電磁開關 (附安裝保護蓋) 士林 108/01 版

額定容量 HP(KW)		補助接點構成	開放式 MSO-P□S 型 (附安裝保護蓋)				封閉式 MS-P□S 型附 PB-2 (附安裝保護蓋)			
200/220V	380/440V		型 式	二素子	三素子(E)	欠相(PP)	型 式	二素子	三素子(E)	欠相(PP)
2(1.5)	3(2.2)	1a	MSO-P06S	-	-	520				
3(2.2)	5(3.7)	1a	MSO-P09S	-	-	530				
4(3)	5.5(4)	1a 或 1b	MSO-P11S	580	600	620	MS-P11S	660	700	710
4(3)	5.5(4)	1a1b	MSO-P12S	620	660	670	MS-P12S	740	770	780
5(3.7)	7.5(5.5)	1a 或 1b	MSO-P15S	660	680	690	MS-P15S	770	800	810
5(3.7)	7.5(5.5)	1a1b	MSO-P16S	780	830	840	MS-P16S	800	840	850
7.5(5.5)	15(11)	1a1b	MSO-P21S	870	910	920	MS-P21S	950	990	1,000
7.5(5.5)	15(11)	2a2b	MSO-P21AS	910	950	960	MS-P21AS	990	1,020	1,030
8.5(6.5)	16(12)	1a1b	MSO-P25S	930	970	990	MS-P25S	970	1,010	1,020
10(7.5)	20(15)	2a2b	MSO-P30TS	1,230	1,270	1,280	MS-P30TS	1,460	1,520	1,530
12.5(9)	20(15)	2a2b	MSO-P35TS	1,290	1,340	1,350	MS-P35TS	1,550	1,620	1,630
15(11)	30(22)	2a2b	MSO-P40TS	1,570	1,620	1,630	MS-P40TS	1,770	1,830	1,850
20(15)	40(30)	2a2b	MSO-P50TS	1,880	1,930	2,000	MS-P50TS	2,240	2,270	2,390
25(19)	50(37)	2a2b	MSO-P60TS	2,270	2,310	2,430	MS-P60TS	2,570	2,600	2,710
35(25)	70(50)	2a2b	MSO-P80TS	2,800	2,820	2,930	MS-P80TS	3,160	3,190	3,310
40(30)	80(60)	2a2b	MSO-P100TS	4,100	4,280	4,410	MS-P100TS	4,490	4,630	4,760
50(37)	100(75)	2a2b	MSO-P125TS	5,380	5,610	5,730	MS-P125TS	6,270	6,380	6,500
60(45)	125(90)	2a2b	MSO-P150TS	6,640	6,770	6,900	MS-P150TS	7,750	7,870	7,980
75(55)	150(110)	2a2b	MSO-P200TS	9,350	10,130	10,140	MS-P200TS	10,010	10,790	10,800
85(65)	150(110)	2a2b	MSO-P220TS	9,900	10,590	10,610	MS-P220TS	11,210	11,990	12,000

額定容量		補助接點	箱入式 MS-P□□PB(S)型附按鈕電磁開關						MS-P□□NPB(S)防塵型附按鈕			
220V (HP)	440V (HP)		型 式	MS-P□□PB(無安裝保護蓋)			MS-P□□PBS(附安裝保護蓋)			型式(IP65) 二素子	無保護蓋	(S)附保護蓋
				二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)			
4	5.5	1a 或 1b	MS-P11	680	710	720	710	740	750	MS-P11N	850	880
4	5.5	1a1b	MS-P12	760	790	800	790	820	840	MS-P12N	910	940
5	7.5	1a 或 1b	MS-P15	800	830	840	840	870	880	-	-	-
5	7.5	1a1b	MS-P16	810	860	870	860	910	920	MS-P16N	990	1,030
7.5	15	1a1b	MS-P21	970	1,030	1,040	1,020	1,070	1,080	MS-P21N	1,270	1,310
7.5	15	2a2b	MS-P21A	1,010	1,060	1,070	1,050	1,110	1,120	-	-	-
8.5	16	1a1b	MS-P25	1,000	1,050	1,060	1,040	1,090	1,110	MS-P25N	1,290	1,330
10	20	2a2b	MS-P30T	1,530	1,600	1,610	1,540	1,600	1,610	MS-P30TN	1,830	1,840
12.5	20	2a2b	MS-P35T	1,660	1,710	1,720	1,730	1,790	1,800	MS-P35TN	1,980	2,080
15	30	2a2b	MS-P40T	1,870	1,930	1,940	1,950	2,000	2,010	MS-P40TN	2,240	2,330
20	40	2a2b	MS-P50T	2,350	2,390	2,500	2,430	2,460	2,590	-	-	-
25	50	2a2b	MS-P60T	2,560	2,590	2,710	2,630	2,670	2,790	-	-	-
30	54	2a2b	MS-P80T	3,080	3,120	3,220	3,180	3,220	3,320	-	-	-

台製 士林牌 正逆轉式電磁開關

士林 108/01 版

額定容量		補助接點構成	型 式	開放式正逆轉電磁開關 MSO-2xP						箱入式正逆轉電磁開關 MS-2xP 型附外殼						
220V (HP)	440V (HP)			MSO-2xP□□無保護蓋			MSO-2xP□□S 附保護蓋			MS-2xP□□無保護蓋			MS-2xP□□S 附保護蓋			
				二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)	
4	4	2x2a1b	CR11	1,220	1,250	-	-	-	CR11	1,470	1,500	-	-	-		
4	5.5	2x(1a或1b)	P11	1,230	1,270	1,280	1,280	1,310	1,320	P11	1,480	1,520	1,530	1,530	1,560	1,580
4	5.5	2x1a1b	P12	1,360	1,390	1,400	1,400	1,440	1,450	P12	1,810	1,840	1,860	1,860	1,890	1,900
5	7.5	2x(1a或1b)	P15	1,410	1,450	1,460	1,450	1,490	1,500	P15	1,810	1,850	1,860	1,870	1,910	1,920
5	7.5	2x1a1b	P16	1,660	1,720	1,730	1,730	1,790	1,800	P16	1,920	1,980	1,990	2,000	2,060	2,070
7.5	15	2x1a1b	P21	1,890	1,950	1,960	1,960	2,020	2,030	P21	2,050	2,100	2,110	2,110	2,170	2,180
8.5	16	2x1a1b	P25	2,020	2,070	2,080	2,080	2,140	2,150	P25	2,160	2,210	2,230	2,230	2,280	2,290
10	20	2x2a2b	P30T	2,540	2,590	2,600	2,650	2,700	2,710	P30T	3,180	3,230	3,240	3,290	3,350	3,360
12.5	20	2x2a2b	P35T	2,800	2,860	2,870	2,920	2,970	2,990	P35T	3,440	3,500	3,510	3,570	3,640	3,650
15	30	2x2a2b	P40T	3,100	3,150	3,160	3,210	3,260	3,270	P40T	3,870	3,930	3,940	3,990	4,050	4,060
20	40	2x2a2b	P50T	3,950	3,990	4,100	4,070	4,100	4,210	P50T	4,860	4,900	5,010	4,980	5,020	5,130
25	50	2x2a2b	P60T	4,960	5,000	5,120	5,080	5,110	5,230	P60T	6,390	6,420	6,530	6,510	6,540	6,670
35	70	2x2a2b	P80T	6,860	6,890	6,990	7,000	7,030	7,140	P80T	7,940	7,980	8,090	8,080	8,130	8,230
40	80	2x2a2b	P100T	8,380	8,510	8,650	8,500	8,640	8,780	P100T	9,330	9,450	9,570	9,450	9,570	9,700
50	100	2x2a2b	P125T	11,710	11,820	11,940	11,890	12,000	12,120	P125T	12,740	12,860	12,990	12,900	13,020	13,150
60	125	2x2a2b	P150T	14,310	14,440	14,560	14,480	14,610	14,750	P150T	14,870	14,990	15,110	15,050	15,160	15,280
75	150	2x2a2b	P200T	17,190	17,980	17,990	17,410	18,200	18,210	P200T	18,430	19,220	19,230	18,630	19,420	19,430
85	150	2x2a2b	P220T	17,360	18,110	18,120	17,580	18,360	18,370	P220T	19,450	20,210	20,220	19,650	20,410	20,420
125	220	2x2a2b	P/C300	38,280	39,120	39,140	-	-	-	註：其他型式規格及零件請另行詢價						
150	300	2x2a2b	P/C400	45,300	46,160	46,190	-	-	-							