

台製 士林牌 無熔線斷路器 . 漏電斷路器

士林 104/07 版

型式	啟斷容量 KA 非對稱值/對稱值				機 種	極數	AF	電 流 容 量		定 價			
	110V	220V	380V	440V				AT (跳脫電流)					
BH系列 (分電盤用品)	5	-	-	-	BH (一般型)	BPL (插入式)	1	50	10,15,20,30,40,50	100			
	-	5	-	-					15,20,30,40,50	130			
	5	-	-	-					60,75,100 (BPL無60A以上)	195			
	5	5	-	-			2	100	10,15,20,30,40,50	220			
									60,75,100	480			
									10,15,20,30,40,50	490			
	-	-	-	-	3	100	60,75,100	1,015					
	BHU (一般型)	10	10	-	-	BHU (一般型)	BLU (插入式)	1	50	15,20,30,40,50	140		
										100	210		
								2	100	15,20,30,40,50	310		
		15,20,30,40,50	680										
		60,75,100	660										
		15	10	-	-			3	100	BLS (插入式)	60,75,100	1,320	
						60,75,100	225						
						15,20,30,40,50	465						
		15	15	10	-	BHH (一般型)	-	-	2	100	15,20,30,40,50	1,030	
											60,75,100	1,100	
	3								100	15,20,30,40,50	1,690		
		60,75,100	225										
		15,20,30,40,50	470										
15	10	-	-	BAH (插入式)	-				-	2	100	15,20,30,40,50	1,030
						60,75,100	1,100						
						3	100	15,20,30,40,50		1,690			
60,75,100	340												
15,20,30,40,50	680												
25/22	25/22	-	-			BHS (一般型)	-	-		2	100	60,75,100	1,080
				15,20,30,40,50	1,130								
				3	100				15,20,30,40,50	1,710			
60,75,100	450												
15,20,30,40,50	300												
純漏電及插座	1	-	-	-	NV-CST1 一般型 CST2 接地				2	15	15 漏電保護插座	450	
	1.5	1.5	-	-	NV-BF(迷你型)	2	30	15,20,30	370				
	2.5	2.5	迷你型	-				40	805				
	2.5	2.5	2.5	2.5	NV-SF	2	60	50,60	400				
	1.5	1.5	-	-	NV-KF	2	30	15,20,30	470				
	2.5	2.5	-	-	NV-K30F	3	30	40	605				
	1.5	1.5	-	-				15,20,30	660				
	-	-	1.5	1.5	NV-KLF	1	30	15,20,30	500				
BH 型漏電斷路器	1.5	1.5	-	-	NV-BF(迷你型)	2	30	15,20,30	535				
	5	-	-	-	NVB-50L (一般型)	1	50	15,20,30,40,50	460				
	-	5	-	-					NVP-50L (插入式)	2	660		
	10	-	-	-	NVB-50UL (一般型)	1	50	15,20,30,40,50	565				
	-	10	-	-					NVP-50UL (插入式)	2	945		
	10	5	-	-	NVB-50HS	1	50	15,20,30,40,50	565				
	-	10	-	-					NVP-50UL (插入式)	2	940		
	15	10	-	-	NVB-50HS	1	50	15,20,30,40,50	1,005				
	-	15	-	-					NVP-50UL (插入式)	2	1,395		
	5	-	-	-	NVB-50F(寬度加1P)	1	50	15,20,30,40,50	580				
	-	5	-	-					NVP-50UL (插入式)	2	650		
	10	-	-	-	NVB-50U(寬度加1P)	2	50	15,20,30,40,50	710				
	-	10	-	-					NVP-50UL (插入式)	2	790		
	10	-	-	-	NVB-50U(寬度加1P)	1	50	15,20,30,40,50	770				
	-	10	-	-					NVP-50UL (插入式)	2	810		
	10/10	10/10	7.5/7.5	7.5/7.5	NF50-SN	2	50	10,15,20,30,40,50	1,010				
	30/25	30/25	18/15	10/10					NF50-HN	3	50	10,15,20,30,40,50	1,130
													4
2					1,030								
18/15	18/15	10/10	7.5/7.5	NF100-MN	2	100	10,15,20,30,40,50	1,180					
								3	2,060				
									4	1,040			
60/50	60/50	35/30	30/25	NF100-HN	2	100	10,15,20,30,40,50,60,75,100	1,210					
								3	2,070				
									4	1,330			
35/30	35/30	25/22	18/15	NF225-CN	2	225	125,150,175,200,225	1,570					
								3	2,920				
									4	2,020			
60/50	60/50	35/30	30/25	NF225-SN	2	225	125,150,175,200,225	2,140					
								3	3,950				
									4	2,900			
DC 用	DC125V/5KA		DC250V/2.5KA		NF50-CB	2	50	10,15,20,30,40,50	750				
	DC125V/7.5KA		DC250V/5KA		NF50-SB				960				
	DC125V/15KA		DC250V/10KA		NF50-HS				990				

台製 士林牌 無熔線斷路器

士林 104/07 版

型式	啟斷容量 KA 非對稱值/對稱值				機種	極數	AF	電流容量 AT (跳脫電流)	定價				
	110V/220V	380V	440V	600V									
N F 型 系 列 無 熔 線 斷 路 器 (配 電 · 配 線 用) 工 業 用 型	5/5	2.5/2.5	2.5/2.5	1.5/1.5	NF30-SN	2	30	3,5,10,15,20,30	540				
						3			770				
						4			1,460				
	5/5	2.5/2.5	2.5/2.5	1.5/1.5	NF50-CN	2	50	10,15,20,30,40,50	790				
						3			830				
						4			1,740				
	10/10	7.5/7.5	7.5/7.5	5/5	NF100-CN	2	100	10,15,20,30,40,50	940				
						3			1,040				
						4			1,830				
					30/25	18/15	10/10	7.5/7.5	NF100-SN	2	100	10,15,20,30,40,50	1,140
										3			1,450
										4			2,630
	35/30	25/22	18/15	7.5/7.5	NF125-SN	2	125	10,15,20,30,40,50	1,030				
						3			1,180				
						4			2,060				
					60/50	35/30	30/25	18/15	NF125-HN	2	125	10,15,20,30,40,50	1,170
										3			1,490
										4			2,860
	100/85	60/50	50/42	30/25	NF100-H	2	100	15,20,30,40,50,60,75,100	1,210				
						3			1,670				
						4			2,850				
					120/100	75/65	60/50	-	NF100-HC	2	100	15,20,30,40,50,60,75,100	1,310
										3			1,710
										4			3,160
35/30	25/22	18/15	7.5/7.5	NF250-CN	2	250	125,150,175,200,225	1,880					
					3			2,030					
					4			3,550					
				60/50	35/30	30/25	18/15	NF250-SN	2	250	125,150,175,200,225	2,020	
									3			2,140	
									4			3,950	
100/85	60/50	50/42	30/25	NF225-HB	2	225	125,150,175,200,225	3,170					
					3			3,480					
					4			3,400					
				120/100	75/65	60/50	-	NF225-HC	2	225	125,150,175,200,225	3,400	
									3			3,730	
									4			2,900	
40/35	35/25	25/22	15/14	NF400-CN	2	400	250,300,350,400	3,400					
					3			5,360					
					4			3,330					
				60/50	40/35	35/30	22/20	NF400-SN	2	400	250,300,350,400	3,530	
									3			5,610	
									4			4,130	
100/85	60/50	50/42	35/25	NF400-HN	2	400	250,300,350,400	4,580					
					3			5,580					
					4			4,700					
				120/100	75/65	60/50	-	NF400-HC	2	400	250,300,350,400	4,900	
									3			5,720	
									4			4,490	
40/35	35/25	25/22	15/14	NF630-CN	2	630	500,600,630	4,840					
					3			4,720					
					4			5,290					
				60/50	40/35	35/30	22/20	NF630-SN	2	630	500,600,630	6,090	
									3			6,690	
									4			11,060	
100/85	60/50	60/50	30/25	NF630-HN	2	630	500,600,630	7,480					
					3			8,290					
					4			7,800					
				120/100	75/65	60/50	-	NF600HC	2	600	500,600	11,630	
									3			8,760	
									4			11,680	
60/50	40/35	35/30	22/20	NF800-CN	2	800	700,800	8,340					
					3			9,570					
					4			13,120					
				100/85	60/50	60/50	30/25	NF800-SN	2	800	700,800	16,000	
									3			13,510	
									4			16,490	
120/100	75/65	75/65	-	NF800-HC	2	800	700,800	14,650					
					3			16,700					
					4			20,420					
150/130	120/100	100/85	75/65	NF800-E	3	800	400~800 電子可調式	25,870					
					4			26,410					
150/130	120/100	100/85	75/65	NF800-HS	3	800	700,800	37,960					
					4			23,430					
150/125	100/85	100/85	60/50	NF1000-E	3	1000	500~1000 電子可調式	20,060					
					4			23,810					
150/130	120/100	100/85	75/65	NF1000-HS	3	1000	1000	20,420					
					4			25,870					
150/125	100/85	100/85	60/50	NF1200-E	3	1200	600~1200 電子可調式	26,410					
					4			19,540					
150/130	120/100	100/85	75/65	NF1200-HS	3	1200	1200	23,430					
					4			20,060					
150/125	100/85	100/85	60/50	NF1200-E	3	1200	600~1200 電子可調式	23,810					
					4			20,420					
150/130	120/100	100/85	75/65	NF1600-HS	3	1600	1400,1600	25,870					
					4			26,410					

台製 士林牌 工業型漏電斷路器&高啟斷&電子式

士林 104/07 版

型式	啟斷容量 KA 非對稱值/對稱值			機種	極數	AF	電流容量 AT (跳脫電流)	定價		
	220V	380V	440V					高速固定	高速可調	延時可調
工業型 ELCB (延時型訂貨需特別註明)	10/10	7.5/7.5	7.5/7.5	NV30-SN	3 4	30	15,20,30	1,900 3,080	2,060 3,380	2,140 3,430
	10/10	7.5/7.5	7.5/7.5	NV50-SN	3 4	50	15,20,30,40,50	2,200 3,510	2,310 3,810	2,400 3,870
	30/25	18/15	10/10	NV50-HN	3 4	50	15,20,30,40,50	2,560 3,940	2,830 4,450	2,900 4,500
	10/10	7.5/7.5	7.5/7.5	NV100-CN	3 4	100	60,75,100	2,810 4,700	3,050 5,050	3,220 5,130
	18/15	10/10	7.5/7.5	NV100-MN	3	100	15,20,30,40,50	3,130	3,270	3,350
					4			5,430	5,780	5,870
					3			3,420	3,510	3,640
	30/25	18/15	10/10	NV100-SN	4	100	15,20,30,40,50	5,930	6,280	6,380
					3			3,970	4,310	4,470
					4			6,890	7,240	7,360
	35/30	25/22	18/15	NV125-SN	3	125	15,20,30,40,50	4,420	4,760	4,940
					4			7,660	8,010	8,140
					3			4,250	4,600	4,770
	60/50	35/30	30/25	NV125-HN	4	125	15,20,30,40,50,60,75,100	7,380	7,730	7,850
					3			4,700	5,040	5,230
					4			8,150	8,500	8,640
	60/50	35/30	30/25	NV225-CN	3 4	225	125,150,175,200,225	4,950 8,570	5,280 8,920	5,480 9,070
	35/30	25/22	18/15	NV225-SN	3 4	225	125,150,175,200,225	6,220 10,400	6,460 10,790	6,560 11,350
	60/50	35/30	30/25	NV250-CN	3 4	250	250	7,890 18,410	8,180 19,100	8,210 19,660
	35/30	25/22	18/15	NV250-SN	3 4	250	250	-	6,460 10,790	6,560 11,350
60/50	35/30	30/25	NV400-CN	3 4	400	250,300,350,400	-	8,180 19,100	8,210 19,660	
40/35	35/25	25/22	NV400-SN	3 4	400	250,300,350,400	-	10,830 18,770	11,150 19,330	
60/50	40/35	35/30	NV400-HN	3 4	400	250,300,350,400	-	12,520 26,280	12,840 28,850	
100/85	60/50	50/42	NV400-UN	3 4	400	250,300,350,400	-	23,050 36,320	23,380 36,820	
150/125	100/85	100/85	NV800-RN	3 4	800	500,600,630	-	26,040 37,740	27,690 37,740	
150/125	100/85	100/85	NV800-RN	3 4	800	700,800	-	27,530 39,750	28,490 40,290	
備註										
NV30/50SN.NV100CN/MN/SN.NV125SN/HN 高速固定型 mA 為 15,30,50,100mA 高速/延時可調型 mA 為 100/300/500mA 可調										
NV225CN.NV225SN 為 30mA 高速/延時可調型 mA 為 100/300/500mA 可調										
NV250CN/SN.NV400CN/SN/HN 高速可調型 mA 為 30/100/500mA 延時可調型 mA 為 100/300/500mA 可調										
高啟斷 NFB	240V	380V	440V	550V	機種	AF	AT (跳脫電流)	2P	3P	4P
	150/125	100/85	100/85	75/65	NF250-HS	250	40,50,60,75,100	4,780	5,500	6,950
	150/125	100/85	100/85	75/65	NF400-UN	400	125,150,175,200,225,250	6,370	6,950	8,130
	150/125	100/85	100/85	75/65	NF800-RN	800	500,600,630	-	16,100	18,110
							700,800	-	21,970	25,970
電子式 NFB	150/125	100/85	100/85	75/65	NF250-UE	250	100 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	-	9,520	11,020
	150/125	100/85	100/85	75/65	NF400-UE	400	250 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	-	11,280	12,380
	150/125	100/85	100/85	75/65	NF800-RE	800	400 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	-	16,780	18,370
							630 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	-	23,170	28,640
						800 (0.4-0.45-0.5-0.6-0.7-0.8-0.9-0.95-1.0)	-	26,970	32,680	

附屬裝置	適用機種											
	適用 NFB(NF)	30/50 SN 50CN.HN 100CN/M/SN	100HN 125SN 125HN	225CN.SN 250CN.SN	400CN 400SN 400HN	630CN.SN 630HN 800CN.SN	800~1600 HS	100H 100HC	225HC 225HB	400HC	600HC	
警報開關 (AL)		250	300	400	750	750	1,450	392	392	547	938	
補助開關 (AUX)		250	300	400	750	750	1,450	392	392	470	782	
AL+AUX		-	-	750	1,400	1,400	-	-	-	-	-	
電壓跳脫(SHT)		500	800	1,000	1,200	1,200	1,850	1,160	1,160	1,255	1,800	
低電壓跳脫 UVT		1,500	1,700	2,000	2,200	2,200	3,750	-	-	2,297	2,504	
外部操作把手 EH		650	680	780	1,740	2,300	-	779	779	-	-	
端子隔離蓋 TC□□N(S)	2P	TC 100N (S)	100 150 200	TC 125N (S)	120 180 240	TC 250N	220 220 330	690 690 950	-	1,000	1,400	

台製 士林牌 低壓交流電磁接觸器

士林 104/07 版

AC1	補助接點	額定電流 AC3		S-P 型 MC 無保護蓋		S-PS 型 MC 附保護蓋		S-2xP 正逆 MC 無保護蓋		S-2xP 正逆 MC 附保護蓋	
		220V	440V	機種	定價	機種	定價	機種	定價	機種	定價
20	1a 或 1b	7.5	6	-	-	S-P06S	270	S-CR11(12A)	910	S-2XP06S	590
20	1a 或 1b	10.1	8	-	-	S-P09S	280	-	-	S-2XP09S	610
20	1a 或 1b	12	9	S-P11	300	S-P11S	310	S-2xP11	850	S-2xP11S	870
20	1a1b 或 2a	12	9	S-P12	360	S-P12S	370	S-2xP12	990	S-2xP12S	1,010
30	1a 或 1b	16	12	S-P15	380	S-P15S	390	S-2xP15	1,020	S-2xP15S	1,040
30	1a1b	16	12	S-P16	450	S-P16S	470	S-2xP16	1,270	S-2xP16S	1,310
40	1a1b	24	21	S-P21	540	S-P21S	560	S-2xP21	1,380	S-2xP21S	1,420
40	2a2b	24	21	S-P21A	570	S-P21AS	590	-	-	-	-
40	1a1b	26	23	S-P25	580	S-P25S	610	S-2xP25	1,500	S-2xP25S	1,550
50	2a2b	30	27	S-P30T	780	S-P30TS	810	S-2xP30T	1,860	S-2xP30TS	1,920
50	2a2b	35	27	S-P35T	800	S-P35TS	840	S-2xP35T	1,910	S-2xP35TS	1,970
65	2a2b	44	40	S-P40T	1,040	S-P40TS	1,070	S-2xP40T	2,290	S-2xP40TS	2,360
80	2a2b	58	52	S-P50T	1,260	S-P50TS	1,310	S-2xP50T	2,790	S-2xP50TS	2,870
100	2a2b	68	65	S-P60T	1,540	S-P60TS	1,580	S-2xP60T	3,360	S-2xP60TS	3,460
130	2a2b	100	90	S-P80T	2,050	S-P80TS	2,090	S-2xP80T	5,220	S-2xP80TS	5,310
150	2a2b	110	105	S-P100T	2,780	S-P100TS	2,820	S-2xP100T	6,660	S-2xP100TS	6,750
170	2a2b	135	130	S-P125T	3,940	S-P125TS	3,990	S-2xP125T	9,480	S-2xP125TS	9,580
200	2a2b	165	160	S-P150T	5,060	S-P150TS	5,110	S-2xP150T	11,340	S-2xP150TS	11,460
235	2a2b	200	190	S-P200T	6,650	S-P200TS	6,740	S-2xP200T	14,690	S-2xP200TS	14,870
250	2a2b	220	190	S-P220T	7,680	S-P220TS	7,770	S-2xP220T	15,950	S-2xP220TS	16,140
350	2a2b	300	300	SP300/SC300	14,570			S-2XP300/P300	32,670		
420	2a2b	400	400	SP400/SC401	21,010			S-2xC401/P400	43,490		
660	2a2b	600	600	S-C600	35,690						

台製 士林牌 過載保護器 . 電磁繼電器 . 補助接點 . 按鈕

士林 104/07 版

額定電流值(A) (可±20%調整)	TH-P 型過載保護器 (無安裝保護蓋)				TH-P□S 型過載保護器 (附安裝保護蓋)			
	機種	2 素子	3 素子(E)	欠相(PP)	機種	2 素子	3 素子(E)	欠相(PP)
0.16,0.24,0.4,0.6,1, 1.6,2.4,4,6,9	TH-P09(PP)			250	-	-	-	-
25,0.4,0.6,0.9,1.2,1.7, 2.1,3.3,4.4,6.5,9,11,15	TH-12(E)C TYPE	250	290	-	-	-	-	-
	TH-P12(E)(PP)	240	280	290	TH-P12(E)(PP)S	270	300	310
0.25,0.4,0.6,0.9,1.2,1.7, 2.1,3.3,4.4,6.5,9,11,15,21	TH-P18(E)(PP)	310	370	380	TH-P18(E)(PP)S	340	390	400
	TH-P20(E)(PP)	310	370	380	TH-P20(E)(PP)S	340	390	400
28,33,40	TH-P20(E)TA(PP)	400	450	480	TH-P20(E)TA(PP)S	440	490	530
11,15,21,28,33,40,54	TH-P60(E)(PP)	590	630	730	TH-P60(E)(PP)S	620	650	760
68,80	TH-P60(E)TA(PP)	650	710	790	TH-P60(E)TA(PP)S	700	760	840
40,54,67,80	TH-P120(E)	1,220	1,350	1,460	TH-P120(E)(PP)S	1,240	1,370	1,490
105,130,160	TH-P120(E)TA	1,300	1,410	1,540	TH-P120(E)TA(PP)S	1,350	1,460	1,590
80,105,130,160,200	TH-P220T(E)CT(PP)	2,570	3,280	3,290	TH-P220T(E)CT(PP)S	2,600	3,310	3,320
105,130,160,200,260,350	TH-P400T(E)CT(PP)	3,390	4,160	4,170	TH-P400T(E)CT(PP)S	3,420	4,180	4,190
260,350,500	TH-P600(E)CT(PP)	8,290	11,870	11,880	TH-P600(E)CT(PP)S	8,320	11,900	11,910

AP-□□補助接點組 AC1(16A)				電磁繼電器 (控制用) SR-P 型 AC1(16A)			PB 按鈕開關		
2P 上裝式	AP20	65	AP20S	70	型號	接點構成	定價	型式	定價
		AP11	65	AP11S	70	SR-P40	4a,3a1b,2a2b	300	PB-2 ON-OFF
	AP02	65	AP02S	70	SR-P40S	4a,3a1b,2a2b	310	PB-3ON-REV-OFF	120
4P 上裝式	AP40	130	AP40S	140	SR-P50	5a,4a1b,3a2b,2a3b	320	機械連鎖	
	AP31	130	AP31S	140	SR-P50S	5a,4a1b,3a2b,2a3b	330	MPU-11	200
	AP22	130	AP22S	140	SR-P80	8a,7a1b,6a2b,5a3b,4a4b	440	MPU-21	200
2P 側裝	APS11	75	APS11S	80	SR-P80S	8a,7a1b,6a2b,5a3b,4a4b	450	MPU-50	220
	APL11	270	APL11S	280	SR-80L	8a,7a1b,6a2b,5a3b,4a4b	440	MPU-125	230

台製 士林牌 低壓交流電磁開關 (無安裝保護蓋) 士林 104/07 版

額定容量 HP(KW)		補助接點構成	開放式 MSO-P 型 (無安裝保護蓋)				封閉式 MS-P 型附 PB-2 (無安裝保護蓋)			
200/220V	380/440V		型 式	二素子	三素子 E	欠相(PP)	型 式	二素子	三素子(E)	欠相(PP)
4(3)	5.5(4)	1a 或 1b	MSO-P11	540	570	580	MS-P11	630	670	680
4(3)	5.5(4)	1a1b	MSO-P12	590	630	640	MS-P12	700	730	740
5(3.7)	7.5(5.5)	1a 或 1b	MSO-P15	630	660	670	MS-P15	730	770	780
5(3.7)	7.5(5.5)	1a1b	MSO-P16	730	780	790	MS-P16	760	800	810
7.5(5.5)	15(11)	1a1b	MSO-P21	820	860	880	MS-P21	910	950	960
7.5(5.5)	15(11)	2a2b	MSO-P21A	860	900	910	MS-P21A	940	980	990
8.5(6.5)	16(12)	1a1b	MSO-P25	890	930	940	MS-P25	930	970	980
10(7.5)	20(15)	2a2b	MSO-P30T	1,160	1,200	1,210	MS-P30T	1,380	1,440	1,450
12.5(9)	20(15)	2a2b	MSO-P35T	1,210	1,260	1,270	MS-P35T	1,470	1,540	1,550
15(11)	30(22)	2a2b	MSO-P40T	1,480	1,550	1,560	MS-P40T	1,700	1,750	1,780
20(15)	40(30)	2a2b	MSO-P50T	1,800	1,850	1,920	MS-P50T	2,160	2,190	2,310
25(19)	50(37)	2a2b	MSO-P60T	2,180	2,210	2,330	MS-P60T	2,490	2,530	2,640
35(25)	70(50)	2a2b	MSO-P80T	2,710	2,730	2,840	MS-P80T	3,080	3,110	3,230
40(30)	80(60)	2a2b	MSO-P100T	4,040	4,200	4,330	MS-P100T	4,410	4,550	4,680
50(37)	100(75)	2a2b	MSO-P125T	5,280	5,400	5,520	MS-P125T	6,160	6,280	6,390
60(45)	125(90)	2a2b	MSO-P150T	6,530	6,660	6,790	MS-P150T	7,650	7,760	7,880
75(55)	150(110)	2a2b	MSO-P200T	9,240	10,020	10,030	MS-P200T	9,910	10,680	10,700
85(65)	150(110)	2a2b	MSO-P220T	9,800	10,480	10,490	MS-P220T	11,100	11,880	11,890
125(90)	220(160)	2a2b	MSO-C300/P300	18,040	18,920	18,930	MS-C300/P300	23,940	24,790	24,800
150(110)	330(220)	2a2b	MSO-C401/P400	23,290	24,150	24,160	MS-C401/P400	31,920	32,750	32,760
220(160)	420(315)	2a2b	MSO-C600	43,410	46,830	46,840	MS-C600	66,790	70,390	70,400

士林牌衝擊式自動 Y-△ 起動開關 機械連鎖式 三台裝 士林 104/07 版

容量 HP		開放式 EYD-O-P 型(S)有保護蓋				封閉式 EYD-E-P 型附 PB-2				封閉式 EYD-A 型附 PB 電表						
220V	440V	型 式	二素子	三素子 (E)	欠相 TH(PP)	型 式	二素子	三素子 (E)	欠相 TH(PP)	型 式	二素子	三素子 (E)	欠相 TH(PP)			
15	25	EYD-O-P21	-	4,620	4,670	4,680	EYD-E-P21	-	6,030	6,080	6,090	EYD-A-P21	-	6,620	6,670	6,680
			S	4,710	4,770	4,780		S	6,120	6,180	6,190		S	6,710	6,770	6,780
25	40	EYD-O-P35	-	5,880	5,910	6,020	EYD-E-P35	-	7,260	7,310	7,420	EYD-A-P35	-	7,950	7,980	8,090
			S	6,000	6,030	6,140		S	7,380	7,430	7,540		S	8,070	8,100	8,210
30	60	EYD-O-P50	-	7,010	7,040	7,150	EYD-E-P50	-	8,700	8,730	8,840	EYD-A-P50	-	9,330	9,360	9,470
			S	7,170	7,200	7,310		S	8,860	8,900	9,010		S	9,490	9,520	9,640
40	75	EYD-O-P60	-	8,530	8,660	8,890	EYD-E-P60	-	10,120	10,240	10,480	EYD-A-P60	-	10,860	10,980	11,220
			S	8,690	8,810	9,040		S	10,280	10,400	10,650		S	11,020	11,140	11,380
50	100	EYD-O-P80	-	10,210	10,330	10,570	EYD-E-P80	-	12,440	12,560	12,800	EYD-A-P80	-	13,260	13,380	13,610
			S	10,380	10,500	10,750		S	12,610	12,740	12,980		S	13,420	13,540	13,790
60	125	EYD-O-P100	-	12,530	12,660	12,900	EYD-E-P100	-	15,170	15,300	15,530	EYD-A-P100	-	16,160	16,280	16,520
			S	12,710	12,830	13,060		S	15,330	15,470	15,710		S	16,330	16,450	16,700
75	150	EYD-O-P125	-	17,130	17,580	17,590	EYD-E-P125	-	19,960	20,410	20,420	EYD-A-P125	-	20,650	21,100	21,110
			S	17,320	17,770	17,780		S	20,140	20,590	20,600		S	20,830	21,280	21,290
100	180	EYD-O-P150	-	19,510	20,270	20,300	EYD-E-P150	-	22,550	23,320	23,330	EYD-A-P150	-	22,940	23,700	23,710
			S	19,700	20,460	20,490		S	22,730	23,490	23,500		S	23,120	23,890	23,900
150	260	EYD-O-P220	-	27,540	28,370	28,380	EYD-E-P220	-	30,540	31,380	31,390	EYD-A-P220	-	31,060	31,890	31,900
			S	27,810	28,640	28,650		S	30,780	31,610	31,620		S	31,300	32,140	32,150

士林牌低壓交流非可逆式電磁開關 (附安裝保護蓋) 士林 104/07 版

額定容量 HP(KW)		補助接點構成	開放式 MSO-P□S 型 (附安裝保護蓋)				封閉式 MS-P□S 型附 PB-2 (附安裝保護蓋)			
200/220V	380/440V		型 式	二素子	三素子(E)	欠相(PP)	型 式	二素子	三素子(E)	欠相(PP)
2(1.5)	3(2.2)	1a	MSO-P06S	-	-	520				
3(2.2)	5(3.7)	1a	MSO-P09S	-	-	530				
4(3)	5.5(4)	1a 或 1b	MSO-P11S	580	600	620	MS-P11S	660	700	710
4(3)	5.5(4)	1a1b	MSO-P12S	620	660	670	MS-P12S	740	770	780
5(3.7)	7.5(5.5)	1a 或 1b	MSO-P15S	660	680	690	MS-P15S	770	800	810
5(3.7)	7.5(5.5)	1a1b	MSO-P16S	780	830	840	MS-P16S	800	840	850
7.5(5.5)	15(11)	1a1b	MSO-P21S	870	910	920	MS-P21S	950	990	1,000
7.5(5.5)	15(11)	2a2b	MSO-P21AS	910	950	960	MS-P21AS	990	1,020	1,030
8.5(6.5)	16(12)	1a1b	MSO-P25S	930	970	990	MS-P25S	970	1,010	1,020
10(7.5)	20(15)	2a2b	MSO-P30TS	1,230	1,270	1,280	MS-P30TS	1,460	1,520	1,530
12.5(9)	20(15)	2a2b	MSO-P35TS	1,290	1,340	1,350	MS-P35TS	1,550	1,620	1,630
15(11)	30(22)	2a2b	MSO-P40TS	1,570	1,620	1,630	MS-P40TS	1,770	1,830	1,850
20(15)	40(30)	2a2b	MSO-P50TS	1,880	1,930	2,000	MS-P50TS	2,240	2,270	2,390
25(19)	50(37)	2a2b	MSO-P60TS	2,270	2,310	2,430	MS-P60TS	2,570	2,600	2,710
35(25)	70(50)	2a2b	MSO-P80TS	2,800	2,820	2,930	MS-P80TS	3,160	3,190	3,310
40(30)	80(60)	2a2b	MSO-P100TS	4,100	4,280	4,410	MS-P100TS	4,490	4,630	4,760
50(37)	100(75)	2a2b	MSO-P125TS	5,380	5,610	5,730	MS-P125TS	6,270	6,380	6,500
60(45)	125(90)	2a2b	MSO-P150TS	6,640	6,770	6,900	MS-P150TS	7,750	7,870	7,980
75(55)	150(110)	2a2b	MSO-P200TS	9,350	10,130	10,140	MS-P200TS	10,010	10,790	10,800
85(65)	150(110)	2a2b	MSO-P220TS	9,900	10,590	10,610	MS-P220TS	11,210	11,990	12,000

額定容量		補助接點	箱入式 MS-P□PB(S)型附按鈕電磁開關							MS-P□NPB(S)防塵型附按鈕		
220V (HP)	440V (HP)		型 式	MS-P□PB(無安裝保護蓋)			MS-P□PBS(附安裝保護蓋)			型式(IP65) 二素子	無保護蓋	(S)附保護蓋
				二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)			
4	5.5	1a 或 1b	MS-P11	680	710	720	710	740	750	MS-P11N	850	880
4	5.5	1a1b	MS-P12	760	790	800	790	820	840	MS-P12N	910	940
5	7.5	1a 或 1b	MS-P15	800	830	840	840	870	880	-	-	-
5	7.5	1a1b	MS-P16	810	860	870	860	910	920	MS-P16N	990	1,030
7.5	15	1a1b	MS-P21	970	1,030	1,040	1,020	1,070	1,080	MS-P21N	1,270	1,310
7.5	15	2a2b	MS-P21A	1,010	1,060	1,070	1,050	1,110	1,120	-	-	-
8.5	16	1a1b	MS-P25	1,000	1,050	1,060	1,040	1,090	1,110	MS-P25N	1,290	1,330
10	20	2a2b	MS-P30T	1,530	1,600	1,610	1,540	1,600	1,610	MS-P30TN	1,830	1,840
12.5	20	2a2b	MS-P35T	1,660	1,710	1,720	1,730	1,790	1,800	MS-P35TN	1,980	2,080
15	30	2a2b	MS-P40T	1,870	1,930	1,940	1,950	2,000	2,010	MS-P40TN	2,240	2,330
20	40	2a2b	MS-P50T	2,350	2,390	2,500	2,430	2,460	2,590	-	-	-
25	50	2a2b	MS-P60T	2,560	2,590	2,710	2,630	2,670	2,790	-	-	-
30	54	2a2b	MS-P80T	3,080	3,120	3,220	3,180	3,220	3,320	-	-	-

台製 士林牌 正逆轉式電磁開關

士林 104/07 版

額定容量		補助接點構成	開放式正逆轉電磁開關 MSO-2xP							箱入式正逆轉電磁開關 MS-2xP 型附外殼						
220V (HP)	440V (HP)		型 式	MSO-2xP□□無保護蓋			MSO-2xP□□S 附保護蓋			型 式	MS-2xP□□無保護蓋			MS-2xP□□S 附保護蓋		
				二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)		二素子	三素子(E)	欠相(PP)	二素子	三素子(E)	欠相(PP)
4	4	2x2a1b	CR11	1,220	1,250	-	-	-	-	CR11	1,470	1,500	-	-	-	-
4	5.5	2x(1a或1b)	P11	1,230	1,270	1,280	1,280	1,310	1,320	P11	1,480	1,520	1,530	1,530	1,560	1,580
4	5.5	2x1a1b	P12	1,360	1,390	1,400	1,400	1,440	1,450	P12	1,810	1,840	1,860	1,860	1,890	1,900
5	7.5	2x(1a或1b)	P15	1,410	1,450	1,460	1,450	1,490	1,500	P15	1,810	1,850	1,860	1,870	1,910	1,920
5	7.5	2x1a1b	P16	1,660	1,720	1,730	1,730	1,790	1,800	P16	1,920	1,980	1,990	2,000	2,060	2,070
7.5	15	2x1a1b	P21	1,890	1,950	1,960	1,960	2,020	2,030	P21	2,050	2,100	2,110	2,110	2,170	2,180
8.5	16	2x1a1b	P25	2,020	2,070	2,080	2,080	2,140	2,150	P25	2,160	2,210	2,230	2,230	2,280	2,290
10	20	2x2a2b	P30T	2,540	2,590	2,600	2,650	2,700	2,710	P30T	3,180	3,230	3,240	3,290	3,350	3,360
12.5	20	2x2a2b	P35T	2,800	2,860	2,870	2,920	2,970	2,990	P35T	3,440	3,500	3,510	3,570	3,640	3,650
15	30	2x2a2b	P40T	3,100	3,150	3,160	3,210	3,260	3,270	P40T	3,870	3,930	3,940	3,990	4,050	4,060
20	40	2x2a2b	P50T	3,950	3,990	4,100	4,070	4,100	4,210	P50T	4,860	4,900	5,010	4,980	5,020	5,130
25	50	2x2a2b	P60T	4,960	5,000	5,120	5,080	5,110	5,230	P60T	6,390	6,420	6,530	6,510	6,540	6,670
35	70	2x2a2b	P80T	6,860	6,890	6,990	7,000	7,030	7,140	P80T	7,940	7,980	8,090	8,080	8,130	8,230
40	80	2x2a2b	P100T	8,380	8,510	8,650	8,500	8,640	8,780	P100T	9,330	9,450	9,570	9,450	9,570	9,700
50	100	2x2a2b	P125T	11,710	11,820	11,940	11,890	12,000	12,120	P125T	12,740	12,860	12,990	12,900	13,020	13,150
60	125	2x2a2b	P150T	14,310	14,440	14,560	14,480	14,610	14,750	P150T	14,870	14,990	15,110	15,050	15,160	15,280
75	150	2x2a2b	P200T	17,190	17,980	17,990	17,410	18,200	18,210	P200T	18,430	19,220	19,230	18,630	19,420	19,430
85	150	2x2a2b	P220T	17,360	18,110	18,120	17,580	18,360	18,370	P220T	19,450	20,210	20,220	19,650	20,410	20,420
125	220	2x2a2b	P/C300	38,280	39,120	39,140	-	-	-	註：其他型式規格及零件請另行詢價						
150	300	2x2a2b	P/C400	45,300	46,160	46,190	-	-	-							