

台製 伍菱牌 無熔線斷路器.漏電斷路器

伍菱 104/01 版

型式	啟斷容量 KA 非對稱值 / 對稱值				機 種	P	AF	電流容量		定 價	
	110/220V	220V	380/440V	感度電流 mA				AT (跳脫電流)	卡式	插入式	
卡式 . 插入式分電箱用品	5	-	-	-	BH	1	50	15,20,30,40,50	125	145	
	-	5	-	-		2	100	15,20,30,40,50	260	270	
	-	5	-	-		3		60,75,100	460	475	
	10	5*	-	-	BHS	1	50	15,20,30,40,50	150	170	
	-	10	-	-		2	100	15,20,30,40,50	330	600	
	-	10	5*	-		3		60,75,100	600	870	
	15	10	-	-	BHH	1	50	15,20,30,40,50	250	-	
	-	15	-	-		2	100	15,20,30,40,50	495	-	
	-	15	10*	-		3		60,75,100	1,000	-	
	25/22	-	-	-	BHK	1	50	15,20,30,40,50	260	-	
	-	25/22	-	-		2	100	15,20,30,40,50	520	-	
	-	25/22	-	-		3		60,75,100	1,200	-	
純漏電	啟斷容量 KA 非對稱值 / 對稱值				機 種	P	AF	電流容量		定 價	
	110/220V	220V	380/440V	感度電流 mA				AT (跳脫電流)	30mA	其它 mA	
	2.5	2.5	-	30,100,200,300,500	EL250-R	2	50	15,20,30,40,50	470	540	
	2.5	2.5	-	30,100,200,300,500	EL350-R	3	50	15,20,30	740	970	
-	-	1.5		3		50	40,50	925	970		
漏電兼過載保護器	1.5	1.5	-	30mA	NV-LB	2	30	15,20,30	430	-	
	5	5	-	30mA	NV50-WE (1P1P 型)	1	50	15,20,30,40,50	670	-	
	5	5	-	30,100,200,300,500		2	50	15,20,30,40,50	920	1,000	
	5	5	-	30,100,200,300,500		3	50	15,20,30,40,50	1,320	1,450	
	10	10	-	30mA	NV50-WS (1P1P 型)	1	50	15,20,30,40,50	790	-	
	10	10	-	30,100,200,300,500		2	50	15,20,30,40,50	1,200	1,350	
	10	10	-	30,100,200,300,500		3	50	15,20,30,40,50	1,650	1,800	
	15	-	-	30mA	NV50-WH (1P1P 型)	1	50	15,20,30,40,50	1,100	-	
	15	15	-	30,100,200,300,500		2	50	15,20,30,40,50	1,500	1,600	
	15	15	-	30,100,200,300,500		3	50	15,20,30,40,50	1,800	1,900	
-	-	5	30,100,200,300,500		4	50	15,20,30,40,50	2,700	2,800		
工業型漏電兼過載保護器	16/15	16/15	10	30mA	NV100-WE	3	100	15,20,30,40,50,60,75,100	2,800	2,800	
				30/100/300mA 可調		4			4,200	4,200	
	30/25	30/25	16/15	30mA	NV100-WS	3	100	15,20,30,40,50,60,75,100	3,500	3,500	
				30/100/300mA 可調		4			5,200	5,200	
	60/50	60/50	35/30	30mA	NV100-WH	3	100	15,20,30,40,50,60,75,100	4,000	4,000	
				30/100/300mA 可調		4			6,500	6,500	
	30/25	30/25	16/15	30mA	NV100-CB	3	100	15,20,30,40,50,60,75,100	3,700	3,700	
				30/100/300mA 可調		4			4,950	4,950	
	60/50	60/50	30/25	100/300/500mA 可調	NV100-HB	3	100	15,20,30,40,50,60,75,100	8,590	8,590	
				30/100/300mA 可調		4			12,600	12,600	
60/50	60/50	35/30	100/300/500mA 可調	NV225-HB	3	225	125,150,175,200,225	8,300	8,300		
			100/300/500mA 可調		4			12,600	12,600		
60/50	60/50	35/30	100/300/500 可調	NV400-HB	3	400	250,300,350,400	-	13,400		
			100/300/500 可調		4			-	23,000		
60/50	60/50	35/30	100/300/500 可調	NV800-HB	3	800	500,600	-	38,700		
			100/300/500 可調		4			-	53,600		
60/50	60/50	35/30	100/300/500 可調	NV800-HB	3	800	700,800	-	71,900		
			100/300/500 可調		4			-	81,000		

台製 伍菱牌 無熔線斷路器

伍菱 104/01 版

AC	非對稱/對稱	220V	380V	440V	600V	機 種	極數	AF	電流容量 AT (跳脫電流)	定價
一 般 配 電 用 S 系 列	熱動電磁式	16/15	10	7.5	5	NF50-WE	2 3	50	15,20,30,40,50	1,050 1,200
	熱動電磁式	30/25	-	-	-	NF100-WE	1	100	15,20,30,40,50	950
		30/25	20/18	16/15	10		2		15,20,30,40,50,60,75,100	1,050
							3		15,20,30,40,50,60,75,100	1,250
	熱動電磁式	40/35	30/25	20/18	16/15	NF125-WE	2	125	15,20,30,40,50	1,400
							3		60,75,100,125	1,600
							3		15,20,30,40,50	1,600
	熱動電磁式	60/50	35/30	30/25	22/20	NF125-WS	2	125	15,20,30,40,50,60,75,100	1,800
							3			1,800
							4			3,550
							2			1,850
							3			2,000
							4			3,900
	熱動電磁式	40/35	30/25	20/18	16/15	NF250-WE	2	250	125,150,175,200,225	2,500
							3			2,700
							2			3,000
	熱動電磁式	60/50	35/30	30/25	22/20	NF250-WS	3	250	125,150,175,200,225	3,500
							2			3,400
							3			3,500
							4			5,800
2							4,000			
3							4,500			
熱動電磁式	40/35	30/25	20/18	16/15	NF400-WE	2	400	250,300,350,400	5,900	
						3			6,300	
熱動電磁式	60/50	35/30	30/25	22/20	NF400-WS	2	400	250,300,350,400	6,000	
						3			6,400	
						4			10,000	
熱動可調 電磁式	60/50	35/30	30/25	22/20	NF630-WS	3	630	500,600	15,000	
						4			22,000	
熱動可調 電磁式	60/50	35/30	30/25	22/20	NF800-HS	3	800	700,800	20,000	
						4			24,000	
高 啓 斷 容 量 H 系 列	熱動電磁式	100/85	60/50	60/50	35/30	NF100-H	2	100	15,20,30,40,50,60,75,100	2,200
							3			2,500
							4			4,300
	熱動電磁式	100/85	60/50	60/50	35/30	NF225-H	2	225	125,150,175,200,225	4,600
							3			5,000
							4			8,000
	熱動電磁式	100/85	60/50	60/50	35/30	NF400-H	2	400	250,300,350,400	8,600
							3			9,000
							4			12,000
							4			17,200
	熱動可調 電磁式	100/85	60/50	60/50	35/30	NF800-H	3	800	500,600	23,600
							4			21,000
							3			28,800
							4			42,000
	熱動可調 電磁式	100/85	60/50	60/50	35/30	NF1200-H	3	1200	1000	66,000
							4			48,000
							3			78,000
							4			76,000
	熱動可調 電磁式	125/100	75/65	60/50	40/35	NF1600-H	3	1600	1400,1600	132,000
							4			132,000
熱動可調 電磁式	120/100	75/65	60/50	40/35	NF125-WR	3	125	15,20,30,40,50,60,75,100,125	3,800	
						4			5,200	
熱動可調 電磁式	120/100	75/65	60/50	40/35	NF250-WR	3	250	125,150,175,200,225,250	6,800	
						4			9,800	
熱動可調 電磁式	120/100	75/65	60/50	40/35	NF400-WR	3	400	250,300,350,400	11,000	
						4			13,000	
熱動可調 電磁式	120/100	75/65	60/50	40/35	NF800-WR	3	800	500,600	22,000	
						4			29,000	
						3			28,000	
						4			35,000	
						3			50,000	
						4			80,000	
熱動可調 電磁式	120/100	75/65	60/50	40/35	NF1200-WR	3	1200	1000,1200	50,000	
						4			80,000	
DC	DC 直流用	DC125V	10KA	DC250V	5KA	NF100-WED	2		10,15,20,30,40,50	1,150
									60,75,100	1,250

AC1 (A)	補助 接點	AC3 (HP),A		C 型接觸器		C 型正逆接觸器		MSO-C-電磁開關			MSO-C2 正逆電磁開關			熱動過載保護電驛		
		220V	440V	機種	定價	機種	定價	機種	2 素子	欠相	機種	2 素子	欠相	機種	2 素子	欠相
20	1a/1b	(3)9	(5)8	C-09D	320	C2-09D	850	09D	580	635	09D	1,300	1,380	NTH-0.5~11	260	310
25	1a/1b	(4)12	(7.5)11	C-11D	325	C2-11D	860	11D	585	640	11D	1,330	1,390	NTH-14~21	280	380
25	1a/1b	(5.5)16	(10)15	C-12D	400	C2-12D	1,000	12D	670	740	12D	1,530	1,580	NTH-25~28	320	400
32	1a/1b	(7.5)22	(15)21	C-18D	480	C2-18D	1,170	18D	790	860	18D	2,040	2,120	NTH-32	380	450
40	1a/1b	(10)32	(20)30	C-25D	720	C2-25D	1,650	25D	1,160	1,300	25D	2,700	2,800	NTH-38~44	480	600
50	1a/1b	(15)42	(25)36	C-35D	960	C2-35D	2,160	35D	1,480	1,710	35D	3,270	3,340	NTH-50~65	680	790
60	1a/1b	(20)55	(40)52	C-45D	1,320	C2-45D	2,900	45D	1,900	1,990	45D	4,180	4,320	NTH-80~96	800	900
80	1a/1b	(25)65	(45)57	C-55D	1,570	C2-55D	3,380	55D	2,250	2,420	55D	5,250	5,430	NTH-126	1,000	1,360
90	1a/1b	(30)80	(50)64	C-65D	2,000	C2-65D	4,200	65D	2,830	2,980	65D	7,140	7,450	NTH-04 分離座		70
125	1a/1b	(35)105	(75)95	C-80D	2,410	C2-80D	5,070	80D	3,320	3,570	80D	7,840	8,070	機械電氣連鎖(C 型)		145
130	1a/1b	(40)110	(75)95	C-100D	2,910	C2-100D	6,070	100D	3,870	4,180	100D	8,380	8,690	CA9-D02 2b		

AC1 (A)	補助 接點	AC3 額定容量 KW(HP)/A		S 型電磁接觸器			S 型電磁開關				輔助接點	定價	
		220V	440V	機種	無 保護蓋	保護蓋 (S)	機種	無保護蓋		加保護蓋(S)			
								2 素子	欠相	2 素子	欠相	SMC-D11 S 型側裝式 1a1b	85
20	1a/1b	2.2(3),9	3.7(5),8	SMC-09	350	370	MSO-S-09	610	660	630	680	CA1 2P	85
25	1a/1b	3(4),12	5.5(7.5),11	SMC-12	370	390	MSO-S-12	640	680	660	700	C 型頂裝式 1a1b	
32	1a/1b	3.7(5),15	7.5(10),14	SMC-18	470	490	MSO-S-18	760	840	780	860	CA1 4P	140
40	1a/1b	5.5(7.5),22	11(15),21	SMC-22	550	570	MSO-S-22	860	930	880	950	C 型頂裝式 2a2b	
50	1a/1b	7.5(10),32	15(20),30	SMC-32	800	830	MSO-S-32	1,270	1,460	1,300	1,490	CA8 2P	85
60	1a/1b	11(15),42	19(25),36	SMC-40	950	980	MSO-S-40	1,360	1,670	1,390	1,700	C 型側裝式 1a1b	