

台製 順山牌 無熔線斷路器.漏電開關

順山 104/07 版

型式	啟斷容量(KA)			感度電流 mA	機 種	極數	AF	電 流 容 量		定 價	
	110V	220V	380V					AT (跳脫電流)	插入式	卡式	
BH 型無熔線斷路器	5	5	-	-	BH 卡式 BHP 插入式	1	50	15,20,30,40,50	訂製品	124	
	5	5	-	-		2	100	15,20,30,40,50 60,75,100	訂製品	248	
	-	5	-	-		3	100	15,20,30,40,50 60,75,100	訂製品	450	
	10	-	-	-	BHK 卡式 BHPK 插入式	1	50	15,20,30,40,50	訂製品	160	
	10	10	-	-		2	100	15,20,30,40,50 60,75,100	訂製品	350	
	-	10	-	-		3	100	15,20,30,40,50 60,75,100	訂製品	650	
	15	10	-	-	BHH 卡式	1	50	15,20,30,40,50	-	280	
	15	15	-	-		2	100	15,20,30,40,50 60,75,100	-	560	
	-	15	10	-		3	100	15,20,30,40,50 60,75,100	-	1,300	
	22	-	-	-	BHS 卡式	1	50	15,20,30,40,50	-	500	
歐規軌道式無熔線斷路器	20	10	-	-	C63S	1	63	6 10,16,20,25,32 40,50,63	-	410	
	-	20	10	-		2	63	6 10,16,20,25,32 40,50,63	-	855	
	-	20	10	-		3	63	6 10,16,20,25,32 40,50,63	-	750	
	-	20	10	-		4	63	6 10,16,20,25,32 40,50,63	-	800	
	-	20	10	-		1	63	6 10,16,20,25,32 40,50,63	-	1,440	
	-	20	10	-		2	63	6 10,16,20,25,32 40,50,63	-	1,275	
	-	20	10	-		3	63	6 10,16,20,25,32 40,50,63	-	1,350	
	-	20	10	-		4	63	6 10,16,20,25,32 40,50,63	-	2,060	
純漏電斷路器	1.5	1.5	-	30mA 100,200,300mA	KEL-230S	2	30	15,20,30	訂製品	430	
	1.5	1.5	-	30mA	KEL-230	2	30	15,20,30	訂製品	435	
	2.5	2.5	-	30mA 100,200,300mA	KEL-250	2	50	15,20,30,40,50 15,20,30,40,50	訂製品	440	
	2.5	2.5	-	30mA 100,200,300mA	KEL-260	2	60	15,20,30 40,50,60 15,20,30,40,50,60	訂製品	660	
	2.5	2.5	-	30mA 100,200,300mA	KEL-360	3	60	15,20,30 40,50,60 15,20,30,40,50,60	訂製品	740	
	-	-	1.5	30mA 100,200,300mA		3	60	15,20,30 40,50,60 15,20,30,40,50,60	訂製品	790	
	-	-	1.5	30mA 100,200,300mA		3	60	15,20,30 40,50,60 15,20,30,40,50,60	訂製品	740	
	5	-	-	30mA 100,200,300mA	KSB	1	50	15,20,30,40,50	訂製品	925	
	5	5	-	30mA 100,200,300mA		2	50	15,20,30,40,50	訂製品	800	
	-	5	2.5	30mA 100,200,300mA		3	50	15,20,30,40,50	訂製品	960	
10	-	-	30mA 100,200,300mA	KCB	1	50	15,20,30,40,50	訂製品	1,050		
10	10	-	30mA 100,200,300mA		2	50	15,20,30,40,50	訂製品	790		
-	10	5	30mA 100,200,300mA		3	50	15,20,30,40,50	訂製品	1,200		
15	10	-	30mA	KHB	1	50	15,20,30,40,50	訂製品	1,320		
-	15	-	30mA		2	50	15,20,30,40,50	訂製品	1,650		
NFB 附屬裝置	適用機種(NF/KBL)	50 型	100 型	125 型	225/250 型	400 型	800 型				
	電壓跳脫(SHT)	\$920	\$920	\$920	\$1,070	\$1,530	\$1,530				
	低電壓跳脫(UVT)	詢價	詢價	詢價	詢價	詢價	詢價				
	輔助開關(AUX)	\$630	\$630	\$690	\$760	\$1,230	\$1,230				
	警報開關(AL)	\$760	\$760	\$840	\$920	\$1,370	\$1,370				
	外部操作把手(EH)	F050SP \$1,200	F100SP \$1,250	F125SP \$1,300	F225SP \$1,400	F400SP \$4,200	F800SP \$7,500				
	端子隔離蓋(TC)3P	\$250	\$300	\$330	\$400	-	-				
	操作把手防塵環 PF	\$85	\$85	\$85	\$85	\$100	\$100				
	漏電開關專用防水型接線盒 IP66/IP67 防水等級		KSB250/KCB250 專用 KEL260/KEL-230S 專用				型號 WPB01-66	\$500			
	軌道安裝片		SA230/KEL230S 專用				型號 93108	\$45			

台製 順山牌 無熔線斷路器.漏電開關

順山 104/07 版

型式	啟斷容量 Icu/Ics(KA)			感度電流 mA	機種	極數	AF	電流容量		定價	
	220V	380V	440V					AT (跳脫電流)			
工業型 MCCB 無熔線斷路器	25/13	18/10	10/5	-	NF50HS	2 3	50	15,20,30,40,50		1,050	
	25/13	18/10	15/8	-	NF100-HS	2 3	100	15,20,30,40,50,60,75,100		1,200	
	50/25	30/15	25/13	-	NF125-SW	2	125	16,20,32,40,50,63,75,100		1,600	
						3			1,800		
						2			1,800		
	85/43	50/25	50/25	-	NF100-SS	3	100	16,20,32,40,50,63,75,100		2,000	
						4			2,500		
	100/50	65/35	50/25	**無大電力證明	NF100-HW	3	100	16,20,32,40,50,63,75,100		2,500	
						4			3,800		
	50/25	30/15	25/13	-	NF250-KS	2	250	125,150,175,200,225		2,700	
						3			3,500		
						3			4,500		
25/13	18/10	15/8	-	NF250-HS	3	250	125,150,175,200,225		2,700		
					250			3,500			
85/43	50/25	50/25	-	NF225-SS	3	225	125,150,175,200,225		5,000		
					4			8,000			
100/50	65/35	50/25	**無大電力證明	NF225-HW	3	225	125,150,175,200,225		6,800		
					4			9,800			
50/25	30/15	30/15	-	NF400-HS	2	400	250,300,350,400		6,000		
					3			6,400			
85/43	50/25	50/25	-	NF400-KS	3	400	250,300,350,400		9,000		
					4			12,000			
100/50	65/35	50/25	**無大電力證明	NF400-HW	3	400	250,300,350,400		11,000		
					4			13,000			
50/25	30/15	30/15	-	NF800-CP	2	800	500,600		14,000		
					3			15,000			
					2			19,000			
100/50	65/35	50/25	-	NF800-SS	3	800	500,600		17,200		
					4			22,000			
					3			21,000			
100/50	65/35	50/25	-	NF1600-SS	3	1600	1000		43,000		
					4			62,000			
					3			49,000			
100/50	65/35	50/25	-	NF1600-SS	4	1600	1200		78,000		
					3			76,000			
					4			132,000			
工業型漏電兼過載保護器	220V	380V	440V	感度電流 mA	機種	P	AF	AT (跳脫電流)	30mA	其它 mA	
	25	18	10	30,100,300mA	KBL100-HS	3	100	15,20,30,40,50,60,75,100	3,700	4,100	
	85	50	50	30,100,300mA	KBL100-SS	3	100	15,20,30,40,50,60,75,100	5,600	5,600	
						4			6,600	6,600	
	85	50	50	30,100,300mA	KBL225-SS	3	225	125,150,175,200,225	8,300	8,300	
						4			12,400	12,400	
	85	50	50	100,300,500mA	KBL400-KS	3	400	250,300,350,400	-	14,500	
						4			-	24,400	
	100	65	50	100,300,500mA	KBL800-SS	3	800	500,600	-	38,700	
						4			-	71,900	
						3			-	53,400	
	100	65	50	100,300,500mA	KBL800-SS	4	800	700,800	-	81,000	
3						-					
4						-					
歐規軌道漏電過載保護器	110V	220V	-	30,100,200,300	KBL63S	1	63	6	913	990	
	20KA	10KA	-	30,100,200,300				10,16,20,25,32	875	963	
								40,50,63	891	979	
								6	1,848	2,058	
	20	-	-	30,100,200,300				10,16,20,25,32	1,736	1,960	
								40,50,63	1,792	2,000	
								6	3,800	4,200	
	20	-	-	30,100,200,300				10,16,20,25,32	3,700	4,100	
								40,50,63	3,800	4,200	
								6	6,800	6,900	
	20	-	-	30,100,200,300				10,16,20,25,32	6,600	6,700	
								40,50,63	6,800	6,900	
6											
1.5	-	-	安全開關 2P2E	SA-230	2	30	3,4,6,10		158		
							15,20,30		138		

台製 順山牌 電磁接觸器.電磁開關

順山 104/07 版

AC1 連續電流	AC3 額定容量 KW(HP) A			補助 接點	電磁接觸器 SMC-□□			電磁開關 MSO-SMC-□□		
	220V	380V	440V		型式	無保護蓋	+保護蓋(S)	型式	無保護蓋	+保護蓋(S)
20A	2.2(3),9	3.7(5),8.5	3.7(5),8	1a1b	SMC-09	600	620	MSO-SMC-09	1,030	1,090
25A	3(4),12	5.5(7.5),11.5	5.5(7.5),11.5	1a1b	SMC-12	690	710	MSO-SMC-12	1,130	1,190
32A	3.7(5),15	7.5(10),15	7.5(10),14	1a1b	SMC-18	920	960	MSO-SMC-18	1,395	1,490
40A	5.5(7.5),22	11(15),22	11(15),21	1a1b	SMC-22	1,030	1,070	MSO-SMC-22	1,565	1,660
50A	7.5(10),32	15(20),31	15(20),30	1a1b	SMC-32	1,490	1,550	MSO-SMC-32	2,215	2,350
60A	11(15),42	19(25),38	19(25),36	1a1b	SMC-40	1,980	2,040	MSO-SMC-40	2,825	3,000
80A	15(20),55	30(40),55	30(40),52	2a2b	SMC-50	2,410	2,490	MSO-SMC-50	3,435	3,590
100A	19(25),65	33(45),65	33(45),57	2a2b	SMC-65	2,940	3,020	MSO-SMC-65	4,160	4,330
110A	22(30),80	37(50),80	37(50),64	2a2b	SMC-75	3,910	3,990	MSO-SMC-75	5,170	5,340
135A	25(35),105	45(60),105	55(75),80	2a2b	SMC-85	5,300	5,380	MSO-SMC-85	7,700	7,870
165A	37(50),135	75(100),135	75(100),130	2a2b	S-C125	7,500	-	CA1-D20 側裝輔助接點 1a1b	\$150	
200A	45(60),165	90(125),165	90(125),160	2a2b	S-C150	9,700	-	MSP21(A)塑膠殼 09~22 用\$320/附 PB\$400		
250A	65(85),220	110(150),210	110(150),190	2a2b	S-C220	14,700	-	MSP35(A)塑膠殼 32~40 用\$720/附 PB\$800		

台製 順山牌 DS 表前開關.ATS.RCSW

順山 104/07 版

NFB 型表前格離開關	額定電流 In(A)		型式 NFB 型 DS	定 價	
	AF	AT		2P	3P
	100AF	100AT	DS-100A	1,200	1,300
	200AF	200AT	DS-200A	2,300	2,600
	300AF	300AT	DS-300A	4,800	5,200
	400AF	400AT	DS-400A	5,800	6,200
	500AF	500AT	DS-500A	7,500	8,000
	600AF	600AT	DS-600A	-	14,000
	800AF	800AT	DS-800A	-	19,000
	1600AF	1000AT	DS-1600A	-	42,000
	1600AF	1200AT	DS-1600A	-	48,000
	1600AF	1600AT	DS-1600A	-	74,000

ATS 電源自動切換開關 / RCSW 遠端控制切換開關	啓斷容量(KA)Icu/Ics				極數	額定電流 AT	ATS 型 式	定 價		RCSW 型 式	定 價
	110V	220V	380V	440V				不含箱	含箱		
	25/13	25/13	18/10	15/8	3	15,20,30,40,50,60,75,100	ATS 100A	15,800	18,200	RC 100A	40,000
	25/13	25/13	18/10	15/8		125,150,175,200,225,250	ATS 250A	18,800	21,200	RC 250A	48,000
	50/25	50/25	30/15	25/13		250,300,350,400	ATS 400A	26,400	30,300	RC 400A	60,000
	50/25	50/25	30/15	25/13		500,600	ATS 600A	51,400	60,500	RC 600A	70,000
	50/25	50/25	35/18	30/15		700,800	ATS 800A	57,500	66,600	RC 800A	85,000
	100/50	100/50	65/33	50/25		1000	ATS1000A	133,100	151,300	RC 1000A	100,000
	100/50	100/50	65/33	50/25		1200	ATS1200A	142,200	160,400	RC 1200A	105,000
	100/50	100/50	65/33	50/25		1400,1600	ATS1600A	181,600	212,000	RC 1600A	170,000
	85/43	85/43	50/25	50/25		15,20,30,40,50,60,75,100	ATS 100A	23,300	25,800	RC 100A	43,500
	85/43	85/43	50/25	50/25	125,150,175,200,225,250	ATS 250A	27,300	29,600	RC 250A	50,000	
	85/43	85/43	50/25	50/25	250,300,350,400	ATS 400A	48,400	54,500	RC 400A	65,000	
	100/50	100/50	65/33	50/25	500,600	ATS 600A	74,100	84,700	RC 600A	75,000	
	100/50	100/50	65/33	50/25	700,800	ATS 800A	86,300	96,900	RC 800A	95,000	
	100/50	100/50	65/33	50/25	1000	ATS1000A	178,500	196,700	RC 1000A	110,000	
	100/50	100/50	65/33	50/25	1200	ATS1200A	190,600	208,800	RC 1200A	140,000	
	100/50	100/50	65/33	50/25	1400,1600	ATS1600A	214,900	239,000	RC 1600A	250,000	
	√	-	-	-	2	15,20 (110V)家用型	ATS-H01	-	2,500	以上適用電壓 220/380V	
	-	√	-	-		15,20 (220V)家用型		-	3,000		

外接 接線 銅牌	適用斷路器機種(適用各廠牌 NFB)		極數(P)	型 式	定 價
	NF100HS / NF125SW / NF100SS / NF100HW / KBL100HS / KBL100SS				
	NF250HS / NF250KS / NF225SS / NF225HW / KBL225SS		3/4P	B250	270
	NF400HS / NF400KS / NF400HW / KBL400KS		3/4P	B400	380
NF800CP / NF800SS / KBL800SS		3/4P	B800	1,250	