

台製 亞迪牌 無熔線斷路器

亞迪 104/07 版

型式	啟斷容量 KA 非對稱值/對稱值				機種	AF	電 流 容 量				定 價			
	220V	380V	440V	600V			AT (跳脫電流)				1P	2P	3P	4P
BH 系列分電盤用品	5	-	-	-	BH 一般型 BHP 插入式	100	15,20,30,40,50 60,75,100				110	230	420	
	10	-	-	-	HBH 一般型 HBHP 插入式	100	15,20,30,40,50 60,75,100				140	285	560	
	15	-	-	-	SBH 一般型 SBHP 插入式	100	15,20,30,40,50 60,75,100				265	560	1,060	
	-	10	-	-		100	15,20,30,40,50 60,75,100						1,200	1,600
	25/22	-	-	-	RBH 一般型	100	15,20,30,40,50 60,75,100				350	750	1,250	1,800
歐規軌道	6	6	-	-	AM-63 軌道式 (外銷用)	63	6,10,16,20,25,32 40,50,63				140	300	550	685
	10	10	-	-			6,10,16,20,25,32 40,50,63				155	320	595	750
配電及配線工業型	18/15	12/10	10/8	5/4	100EB	100	15,20,30,40,50 60,75,100				1,100	1,225	1,390	
	30/25	20/18	12/10	5/4	100SB	100	15,20,30,40,50 60,75,100				1,200	1,335	1,500	
	40/35	30/25	20/18	16/15	125EK	125	15,20,30,40,50 60,75,100,125				1,280	1,440	1,780	
	60/50	35/30	30/25	22/20	125SK	125	15,20,30,40,50 60,75,100,125				1,620	1,820	1,990	3,300
	100/85	60/50	60/50	35/30	125HK	125	15,20,30,40,50 60,75,100,125				2,800	3,000	3,500	
	40/35	30/25	20/18	16/15	250EK	250	125,150,175,200,225 250				2,480	2,680	3,200	
	60/50	35/30	30/25	22/20	250SK	250	125,150,175,200,225 250				3,280	3,780	4,500	5,800
	100/85	60/50	60/50	35/30	250HK	250	125,150,175,200,225 250				4,800	5,000	5,200	
	40/35	30/25	20/18	16/15	400EK	400	250,300,350,400				6,100	6,400		
	60/50	35/30	30/25	22/20	400SK	400	250,300,350,400				6,300	6,600	9,800	
	100/85	60/50	60/50	35/30	400HK	400	250,300,350,400				8,600	9,000	12,000	
	60/50	35/30	25/22	15	800SB	800	500,600				13,200	14,200	21,000	
	100/85	60/50	60/50	35/30	800HK	800	500,600						17,000	23,500
	60/50	35/30	25/22	15	800SB	800	700,800				18,200	19,200	23,000	
	100/85	60/50	60/50	35/30	800HK	800	700,800						21,300	28,000
電源保護器	1.5/1.5	額定電壓: AC220V/DC80V			ACP	100	10,15,20,25,30,40,50 60,75,100				380	800	1,160	1,540
	1.5/1.5	額定電壓:AC220V/DC80V (附補助接點)			ACP-W	100	10,15,20,25,30,40,50 60,75,100				430	860	1,210	1,595
漏電保護電源組	使用電壓:100~120V 感度電流:15/30mA, 0.1sec 啟斷容量:1KA/AC110V 功率:1500W 線徑 2mm 平方				ASP-1502S	15A	15mA 線徑 2mm 平方*2C,附插座				650			
					ASP-3002S		30mA 線徑 2mm 平方*2C,附插座				650			
					ASP-1502W		15mA 線徑 2mm 平方*2c 附線 1.8M				800			
					ASP-3002W		30mA 線徑 2mm 平方*2c 附線 1.8M				800			
					ASP-1503S		15mA 線徑 2mm 平方*3C,附插座						700	
					ASP-3003S		30mA 線徑 2mm 平方*3C,附插座						700	
					ASP-1503W		15mA 線徑 2mm 平方*3C 附線 1.8M						850	
					ASP-3003W		30mA 線徑 2mm 平方*3C 附線 1.8M						850	
定時器 24H TIMMER	型式	外型	停電補償	輸出控制	電壓	定價								
	KI03P1W1/2	03:無外殼	P:無停電補償	1W:2 進 2 出(1a 接點) 3W: 2 進 3 出(1c 接點)	1:110V 2:220V	950								
	KI03P3W1/2		B:附停電補償			1,000								
	KI03B1W1/2					1,000								
	KI03B3W1/2					1,050								
	KI04P1W1/2	04:附鐵殼	P:無停電補償	1W:2 進 2 出(1a 接點) 3W: 2 進 3 出(1c 接點)	1:110V 2:220V	1,100								
	KI04P3W1/2		B:附停電補償			1,150								
KI04B1W1/2			1,150											
KI04B3W1/2			1,200											

台製 亞迪牌.詮安牌 漏電斷路器

亞迪 104/07 版

型式	啟斷容量 KA				特殊訂製 mA	機 種	極數	電 流 容 量		定 價		
	110V	220V	380V	440V				AT (跳脫電流)	30mA	訂製mA	可調 mA	
純漏電保護	1.5	1.5	-	-	-	SEG-30(迷你型)	2	15,20,30	400	500		
					100,300,500	SEG-30(防水型)	2	15,20,30	700	700		
	1.5	1.5	-	-	-	SEG-50(迷你型)	2	15,20,30,40,50	450			
					100,200,300	EG-30	2	15,20,30	400	500		
	1.5	1.5	-	-	-	EG-3P	3	15,20,30	600			
					40,50			700				
	15,20,30	700										
	40,50	800										
-	-	1.5	-	-								
-	-	2.5	-	-								
漏電過載	5	5	-	-	100,200,300	AE (寬度加 1P 型)	1	15,20,30	600	700		
					100,200,300		2	15,20,30,40,50	820	920		
					100,200,300		3	15,20,30,40,50	1,135	1,235		
					100,200,300		3	15,20,30,40,50	1,570	1,570		
					100,200,300		4	15,20,30,40,50	1,890	1,950		
					100,200,300		4	15,20,30,40,50	2,000	2,000		
	10	10	-	-	100,200,300	AEH (寬度加 1P 型)	1	15,20,30	700	800		
					100,200,300		2	15,20,30,40,50	1,000	1,100		
					100,200,300		3	15,20,30,40,50	1,300	1,400		
					100,200,300		3	15,20,30,40,50	1,790	1,790		
					100,200,300		4	15,20,30,40,50	2,100	2,200		
					100,200,300		4	15,20,30,40,50	2,300	2,300		
	5	5	-	-	-	AES(標準型)	1	15,20,30,40,50	600			
					30/100/200/300 可調	AEB(加長型)	2	15,20,30,40,50	820	920	970	
					100,300,500	AEP(插入式)	3	15,20,30,40,50	1,135	1,245		
					3 段可調 mA	AEP(防水型)	2	15,20,30,40,50			1,150	
					30/100/200/300 可調	AES(防水型)	2	15,20,30,40,50	1,100		1,200	
					30/100/200/300 可調	AESH(防水型)	2	15,20,30,40,50	1,150		1,250	
10	10	-	-	-	AESH(標準型)	1	15,20,30,40,50	700				
				30/100/200/300 可調	AEBH(加長型)	2	15,20,30,40,50	1,000	1,100	1,150		
				100,300,500	AEPH(插入式)	3	15,20,30,40,50	1,300	1,400			
				-	AESS(標準型)	1	15,20,30,40,50	1,100				
				100,300,500		2	15,20,30,40,50	1,500	1,600			
				100,300,500		3	15,20,30,40,50	1,800	1,900			
15	15	-	-	-	AE1033	2	15,20,30,40,50	2,070				
				60,75,100		2,530						
				-	AE1033HN	2	15,20,30,40,50	2,300				
				60,75,100		2,750						
				-	AE1033S	2	15,20,30,40,50	3,000				
				60,75,100		3,200						
-	AE1033A	2	15,20,30,40,50			3,100						
60,75,100		3,300										
15	15	-	-	-	AE1033	3	15,20,30,40,50	2,190				
				60,75,100		2,640						
				-	AE1033HN	3	15,20,30,40,50	2,420				
				60,75,100		2,860						
				-	AE1033S	3	15,20,30,40,50	3,110				
				60,75,100		3,500						
-	AE1033A	3	15,20,30,40,50			3,300						
60,75,100		3,500										
25	25	15	15	100/200/500 可調	AE1034A	4	15,20,30,40,50			5,000		
				60,75,100			5,500					
				-	AE2032	2	125,150,175,200,225			6,380		
				100/200/500 可調		AE2033	3	125,150,175,200,225			6,600	
				-	AE2034	4	125,150,175,200,225			11,000		
				100/200/500 可調		AE2033S	3	125,150,175,200,225			8,000	
50	50	30	25	30/100/300 可調	AE2034S	4	125,150,175,200,225			12,500		

台製 詮安牌 防水型 漏電斷路器 (IP67)

防水型	啟斷容量 KA				特殊訂製 mA	機 種	極數	電 流 容 量		定 價		
	110V	220V	380V	440V				AT (跳脫電流)	30mA	訂製mA	可調 mA	
	10	10	-	-	100/300/500 可調	LS-50BPUS	2	15,20,30				1,052