

台製 理研牌 無熔線斷路器

理研 104/07 版

型式	啟斷容量 KA 非對稱值/對稱值				機種	數極	AF	電 流 容 量		定 價
	220V	380V	440V	600V				AT (跳脫電流)		
BH系列分電盤用品	5	-	-	-	BH (一般型) BP (插入式)	1	50	15,20,30,40,50		82
						2	100	15,20,30,40,50		164
						3		60,75,100		310
								15,20,30,40,50		340
							60,75,100		575	
	10	-	-	-	BHU (一般型) BPU (插入式)	1	50	15,20,30,40,50 (插入式\$115)		110
						2	100	15,20,30,40,50 (插入式\$258)		230
						3		60,75,100		455
								15,20,30,40,50		455
							60,75,100		845	
	15	-	-	-	BHH (一般型)	1	50	15,20,30,40,50		220
						2	100	15,20,30,40,50		400
						3		60,75,100		805
						15,20,30,40,50		805		
						60,75,100		930		
配電及配線工業型	18/15	10	7.5	5	RK-100EB	2	100	15,20,30,40,50		910
						3		60,75,100		990
								15,20,30,40,50		990
		60,75,100		1,150						
	30/25	20/18	10	5	RK-100SB	2	100	15,20,30,40,50		980
						3		60,75,100		1,100
								15,20,30,40,50		1,100
		60,75,100		1,250						
	30/25	20/18	10	7.5	RK-125EB	3	125	15,20,30,40,50		1,150
								60,75,100,125		1,350
	60/50	35/30	25/22	18/15	RK-125SB	2	125	15,20,30,40,50,60,75,100,125		1,450
						3				1,650
	30/25	20/18	10	7.5	RK-250EB	2	250	125,150,175,200,225(250A\$2,260)		2,175
						3		125,150,175,200,225(250A\$2,595)		2,380
	60/50	40/35	35/25	25/22	RK-250SB	2	250	125,150,175,200,225(250A\$3,580)		3,200
3						125,150,175,200,225(250A\$4,100)		3,820		
40/35	25/22	20/18	15/14	RK-400EB	2	400	250,300,350,400		5,020	
					3				5,300	
					4				7,100	
60/50	40/35	35/30	25/22	RK-400SB	2	400	250,300,350,400		5,300	
					3				5,800	
60/50	40/35	35/30	25/22	RK-800SB	3	800	500,600		11,000	
							700,800		16,000	
					4		500,600		16,000	
							700,800		21,000	
漏電斷路器	2.5	-	30mA	SRG-30	2	30	15,20,30		330	
				SRG-50	2	50	15,20,30,40,50		380	
	2.5	-	30mA	RG-30	2	30	15,20,30 (300mA\$430)		330	
				RG-50	2	50	40,50 (300mA\$460)		360	
	-	1.5	30/100/200/300	RG-3P	3	30	15,20,30 (40/50A\$550)		460	
					3	50	15,20,30,40,50		650	
E型漏電兼過載斷路	5	-	30mA	ES(1P 標準型)	1	50	15,20,30,40,50 (EH\$460)		500	
				EC(1P 加長型)	2		15,20,30,40,50 (EH\$650)		750	
				EP(插入式)	3		15,20,30,40,50 (EH\$1,000)		960	
				EH(寬度加1P)	3		15,20,30,40,50		1,200	
	5	2.5			4	15,20,30,40,50		1,880		
	10	-	30mA	ESU(1P 標準型)	1	50	15,20,30,40,50 (EHU\$600)		600	
				ECU(1P 加長型)	2		15,20,30,40,50 (EHU\$820)		870	
				EPU(插入式)	3		15,20,30,40,50 (EHU\$1,470)		1,300	
				EHU(寬度加1P)	3		15,20,30,40,50		1,580	
	10	5			4	15,20,30,40,50		2,300		
	15	-	30mA	ESH(1P 標準型)	1	50	15,20,30,40,50		1,300	
					2		15,20,30,40,50		1,800	
				3	15,20,30,40,50		2,700			
工業型漏電器	15	-	30mA	RF103H	3	100	15,20,30,40,50		2,320	
					3		60,75,100		2,650	
	25	-	30mA	RF103J	3	100	15,20,30,40,50		2,830	
					3		60,75,100		3,010	
25	15	30/100/200 可調	RF104J	3	100	15,20,30,40,50,60,75,100		2,750		
30/25	20/18	200mA	RF203J	3	225	125,150,175,200,225		6,430		
				4				7,080		

台製 理研牌 低壓交流電磁接觸器(C1)

理研 104/07 版

AC1	補助接點	額定電流 AC3		電磁接觸器(C1)		正逆接觸器(C1)		接觸器(C1)加保護蓋		正逆接觸器(C1)加保護蓋					
		220V	380V	機種	定價	機種	定價	機種	定價	機種	定價				
25	1a或1b	9	9	RAB-A09	285										
25	1a或1b	12	12	RAB-A12	308	RRAB-A12	836	RAB-A12F	320	RRAB-A12F	860				
25	1a1b	15	15	RAB-A15	378	RRAB-A15	986	RAB-A15F	395	RRAB-A15F	1,020				
32	1a1b	18	18	RAB-A18	428	RRAB-A18	1,106	RAB-A18F	445	RRAB-A18F	1,140				
35	1a1b	24	24	RAB-A24	498	RRAB-A24	1,266	RAB-A24F	515	RRAB-A24F	1,300				
40	1a1b	30	30	RAB-A30	598	RRAB-A30	1,486	RAB-A30F	620	RRAB-A30F	1,530				
50	1a1b	35	35	RAB-A35	728	RRAB-A35	1,766	RAB-A35F	750	RRAB-A35F	1,810				
65	1a1b	36	36	RAB-A36	768	RRAB-A36	1,846	RAB-A36F	790	RRAB-A36F	1,890				
80	1a1b	50	50	RAB-50T	1,080	RRAB-50T	2,480	N型接觸器(C1)		(MS)S1/E1 開放 S2/E2 附加殼					
90	1a1b	65	65	RAB-65T	1,250	RRAB-65T	2,870	AC3(HP) 機種 定價		2 素子(S) 欠相(E)					
100	1a1b	75	75	RAB-72T	1,680	RRAB-72T	3,780	220V	RAB-□ (C1)	(S1)	(S2)	(E1)	(E2)		
110	1a1b	80	80	RAB-78T	1,980	RRAB-78T	4,690	1HP 以下	-12N	285	640	810	-	-	
125	1a1b	95	95	RAB-95T	2,200	RRAB-95T	5,130	12(1~3)	-12N	285	510	610	-	-	
140	2a2b	100	100	RAB-88T	2,450	RRAB-88T	5,300	25(7.5)	-25N	1,100	1,650	1,945	1,850	2,220	
150	2a2b	115	115	RAB-110T	3,100	RRAB-110T	7,060	35(10)	-35N	1,225	1,775	2,095	1,980	2,350	
165	2a2b	125	125	RAB-125T	3,800	RRAB-125T	8,950	50(15)	-50N	1,560	2,380	2,695	2,535	2,870	
170	2a2b	135	135	RAB-135T	4,100	RRAB-135T	9,100	65(20)	-65N	1,785	2,595	2,950	2,770	3,115	
200	2a2b	165	165	RAB-155T	5,500	RRAB-155T	12,350	80(25)	-80N	2,395	3,410	4,150	3,620	4,370	
200	2a2b	165	165	RAB-150T	6,500	RRAB-150T	14,350	100(35)	-100N	3,040	4,135	4,995	4,400	5,025	
240	2a2b	200	200	RAB-180T	7,000	RRAB-180T	15,350	125(40)	-125N	4,720	6,320	7,050	6,405	7,130	
260	2a2b	225	225	RAB-225T	8,000	T型機械連鎖裝置		150(50)	-150N	6,160	7,835	8,580	8,050	8,905	
330	2a2b	260	260	RAB-260T	12,000	RK-T35(機械)	100	180(60)	-180N	7,920	10,420	11,990	10,950	12,885	
400	2a2b	300	300	RAB-300T	14,500	RL-T70(電氣)	170	225(75)	-225N	9,020	11,575	13,140	12,100	14,075	
425	2a2b	400	400	RAB-450T	18,800	RL-800(電氣)	210	260(100)	-260	11,700	14,385	16,025	14,910	16,970	
過載 2H/欠相 2E 保護繼電器								N型電磁開關附加殼/PB				N型正逆轉電磁開關 RRAB-			
額定電流 (中間值±20%)		適用接觸器		機種 BTH-□	過載 (2H)	欠相 (2E)	HP	機種	2素子	欠相	2素子	欠相	2素子	欠相	
							220V	RAB-	(S3)	(E3)	(S1)	(E1)	(S2)	(E2)	
0.35,0.7,1.2, 2.3,3.6,5.6, 6.7,7.5,9		A09		-7	220	-	7.5	25N	2,295	2,505	3,290	3,660	3,870	4,250	
0.4,0.63,1.1,1.4, 1.8,2.4,3.1,4.5, 6.5,7.5,8.5,11		A12~A24		-A25	260	358	10	35N	2,425	2,635	3,620	4,040	4,200	4,640	
14,19,25		A15~A24					320	398	15	50N	3,065	3,280	5,210	5,500	6,080
0.4,0.63,1.1,1.4, 1.8,2.4,3.1,4.5, 6.5,7.5,8.5,11,14		09T~18T/A09~A36		-32K	280	300	20	65N	3,300	3,510	5,640	5,910	6,530	6,810	
19,25		24T~30T/A24~A36					35	100N					7,410	7,520	8,380
35		35T/36T/A35/A36					40	125N			9,390	9,580	10,460	10,670	
15,18,22,24		30T~36T/A30~A36		-35T	350	550	50	150N			14,140	14,740	按鈕開關		
28,30		30T~36T/A30~A36					60	180N					18,360	19,560	機種 定價
42,52,63		50T/65T		-80K	580	700	75	225N			23,380	25,500	PB-2	90	
80,100		72T/78T/85T					100	260					45,840	48,800	PB-3
18,22,30,34,41, 48,56,67,80		50N/65N/50T/65T		-()80	650	850	專用型單接點 接觸器(C1)								
41,56,67,80		80N/100N/88T/110T					額定電流		220V	380V	主接點	輔助接點	機種		定價
90		100N/88T~135T		-()125	900	1,150	100	100	1A	1a1b	RAB-341		1,250		
107		125N/88T~135T					150	150	1A	1a1b	RAB-3415		1,440		
120,130		135T/150N		-()125	1,300	1,500	200	200	1A	1a1b	RAB-342		1,600		
144,180,252		180N~260/150~225T					300	300	1A	2a2b	RAB-343(開放式)		3,550		
288,324		300/260T		-CT350	2,000	2,500	300	300	1A	2a2b	RAB-343(封閉式)		4,250		
360		450/300T/450T		-CT450	2,200	2,700	特殊用途控制繼電器								
0.35,0.7		A09~A24		▼-18T 售完為止	380	358	AC1		絕緣		接點購成		機種 定價		
1.2~11		A15~A24					10	600V	300V DC30		1C/2C/2A/1X/1Y		RPR-30		650
15,18		A15~A24		▼()26 售完為止	350	600	AC1 AC3		1C/2C/2A/1X/1Y		RPR-40		710		
0.35,0.7,1.2,1.8,2.3 2.8,3.6,5.6,6.7,7.5, 9,11,15,18		12T/15T/18T/24T					AC1		絕緣		1C/2C/2A/1X/1Y		RPR-50		780
11,15,18,22,24, 28,30,34,41		25N/35N		▼()50 售完為止	550	750	A型控制繼電器								
							10		4a		RCR-A10-40		300		
				10		3a1b		RCR-A10-31		300					
				10		2a2b		RCR-A10-22		300					
				A/T型大電流專用控制繼電器											
				25		12		4a 或 2a2b		RAR-A12		380			
				40		15		4a		RAR-25T		750			
				O.L 單體固定座											
								適用機種		機種		定價			
								BTH-A25		BTH-A25MP		100			

台製 理研牌 電磁開關

理研 104/07 版

補助接點構成	容量 HP		機種	(S1)			(S2)IP42 不附 PB			(S3)IP42 附 PB 整套			正逆轉 RRAB-			三台裝 Y-Δ RAS3-□□			
	220V	440V		2 素子 RAB-	開放式	P 型 膠殼	T 型 膠殼	封閉式 鐵殼	P 型 膠殼	T 型 膠殼	封閉式 鐵殼	2 素子 RRAB	開放式 (S1)	封閉 (S2)	HP □□	開放欠相(E1)	封閉式 (E3)	附表 (E3A)	
1a/1b	3	5	A09	510	600	658	610	660	660	660									
1a/1b	4	7.5	A12	568	658	696	658	726	856	726	A12	1,204	1,534	加電壓錶牌價加 500元					
			A12F	580	670	708	670	738	868	738	A12F	1,228	1,558						
1a1b	4	7.5	A15	638	758	776	758	816	936	816	A15	1,404	1,734						
			A15F	655	775	793	775	828	953	828	A15F	1,438	1,768						
1a1b	6	11	A18	748	830	830	830	846	998	846	A18	1,524	1,854						
			A18F	765	843	843	843	863	1,015	863	A18F	1,558	1,888						
1a1b	7.5	15	A24	818	916	916	916	1,020	1,078	1,020	A24	1,648	2,014	-7.5	3,860	4,880	5,600		
			A24F	835	933	933	933	1,037	1,095	1,037	A24F	1,718	2,048						
1a1b	8.5	16	A30	958		1,168	1,189		1,300	1,295	A30	2,146	2,646						
			A30F	980		1,190	1,211		1,322	1,317	A30F	2,190	2,690						
1a1b	10	20	A35	1,128		1,298	1,319		1,520	1,377	A35	2,426	2,926	-10	4,350	5,370	6,090		
			A35F	1,150		1,320	1,341		1,542	1,399	A35F	2,470	2,970						
1a1b	12.5	20	A36	1,168		1,338	1,359		1,560	1,417	A36	2,506	3,006						
			A36F	1,190		1,360	1,381		1,582	1,439	A36F	2,550	3,050						
1a1b	15	30	50T	1,660			1,860		1,969	50T	3,480		-15	4,760	5,780	6,500			
1a1b	20	40	65T	1,830			2,030		2,203	65T	3,870		-20	5,350	6,370	7,080			
1a1b	25	50	72T	2,360			2,609			72T	4,880		-25	5,550	6,670	7,390			
1a1b	30	60	78T	2,660			2,866			78T	5,710		-30	6,330	7,460	8,210			
1a1b	35	60	95T	3,080			3,280			88T	6,150								
2a2b	35	70	88T	3,350			3,560			88T	6,550								
2a2b	40	80	110T	4,200			4,580			110T	9,560		-40	7,970	9,190	9,900			
2a2b	45	85	125T	5,100			5,549			125T	11,450								
2a2b	50	100	135T	5,450			6,467			135T	13,900		-50	9,480	10,710	11,420			
2a2b	60	125	155T	7,500			7,870			155T	17,850		-60	11,320	12,850	13,210			
2a2b	60	125	150T	8,500						150T	19,850								
2a2b	75	150	180T	9,000						180T	20,850		-75	13,360	14,890	15,250			
2a2b	85	170	225T	10,000															
2a2b	100	200	260T	14,200									-100	18,970	21,010	21,370			
2a2b	125	220	300T	16,900									-125	23,460	25,500	25,860			
2a2b	150	300	450T	21,200									-150	27,540	32,640	33,000			
2a2b	175	300											-175	42,840	47,940	48,300			
2a2b	200	350											-200	49,470	57,630	58,000			
2a2b	250	450											-250	62,730	71,400	71,800			

補助接點	容量 HP		欠相	(E1)	(E2)IP42 不附 PB			(E3)IP42 附 PB			正逆轉 欠相	(E1)	(E2)	直卡式輔助接點				
	220V	440V			RAB-	開放式	P 型殼	T 型殼	鐵殼	P 型殼				T 型殼	鐵殼	開放式	封閉	AC1
1a/1b	3	5	A09(T)		755	798	755	880	978	880				AC1	接點	機種	定價	
1a/1b	4	7.5	A12	666	798	836	798	880	978	880	A12	1,344	1,674	10A	2a	RA1-T20	90	
			A12F	678	810	848	810	892	990	892	A12F	1,368	1,698		1a1b	RA1-T11	90	
1a1b	4	7.5	A15	736	880	906	888	1,067	1,108	1,067	A15	1,534	1,864		2b	RA1-T02	90	
			A15F	753	905	923	905	1,084	1,125	1,084	A15F	1,568	1,898		4a	RA1-T40	150	
1a1b	6	11	A18	826	948	988	948	1,102	1,158	1,102	A18	1,654	1,984		3a1b	RA1-T31	150	
			A18F	843	965	1,005	965	1,119	1,175	1,119	A18F	1,688	2,018		2a2b	RA1-T22	150	
1a1b	7.5	15	A24	896	1,028	1,046	1,028	1,173	1,228	1,173	A24	1,814	2,144		1a3b	RA1-T13	150	
			A24F	913	1,045	1,063	1,045	1,190	1,245	1,190	A24F	1,848	2,178		4b	RA1-T04	150	
1a1b	8.5	16	A30	1,158		1,368	1,389		1,570	1,581	A30	2,346	2,846		側卡式輔助接點			
			A30F	1,180		1,390	1,411		1,592	1,603	A30F	2,390	2,890		AC1	接點	機種	定價
1a1b	10	20	A35	1,328		1,510	1,530		1,720	1,734	A35	2,626	3,126	10A	1a1b	RB-110	90	
			A35F	1,350		1,532	1,552		1,742	1,756	A35F	2,670	3,170			RC-110	100	
1a1b	12.5	20	A36	1,368		1,550	1,592		1,760	1,774	A36	2,706	3,206	T 型卡式限時繼電器				
			A36F	1,390		1,572	1,614		1,782	1,796	A36F	2,750	3,250	規格	機種	定價		
1a1b	15	30	50T	1,780			1,979		2,234	50T	3,880		1~30Sec 普通	LTR-12	750			
1a1b	20	40	65T	1,950			2,152		2,407	65T	4,270		1~30Min 普通	LTR-15	750			
1a1b	25	50	72T	2,430			2,741			72T	5,030		1~30SecY-Δ	LTR-422	750			
1a1b	30	60	78T	2,730			2,999			78T	6,110		1~30MinY-Δ	LTR-43	750			
1a1b	35	60	95T	3,280			3,658			95T	6,550		1~30SecY-Δ 氣壓式	RA2-D22	750			
2a2b	35	70	88T	3,600			3,815			88T	6,800		1~30SecY-Δ 電子式	TR-222	450			
2a2b	40	80	110T	4,480			4,682			110T	9,660		24 小時 定時器					
2a2b	45	85	125T	5,300			5,651			125T	11,550		開放式	TR-24PO(S1)	700			
2a2b	50	100	135T	5,650			6,671			135T	14,100			TR-241C(S1)	725			
2a2b	60	125	155T	8,000			8,080			155T	18,350		附鐵殼	TR-24PO(S2)	750			
2a2b	60	125	150T	9,000						150T	20,350			TR-241C(S2)	825			
2a2b	75	150	180T	9,500						180T	21,350							