

台製 慶同牌 無熔線斷路器

慶同 108/01 版

型式	啓斷容量 KA (Icu/Ics)					機種	極數	AF	電 流 容 量 AT (跳脫電流)	定 價
	110V	220V	380V	440V	600V					
配 電 盤 用 型	25/13	25/13	20/10	10/5	-	SB-100	2	100	15,20,30,40,50,60,75,100	850
							3			950
	50/25	50/25	30/15	25/13	-	SK-125	2	125	15,20,30,40,50,60,75,100,125	1,200
							3			1,300
	85/35	85/35	50/20	50/20	-	HK-125	3	125	15,20,30,40,50,60,75,100,125	2,500
	50/25	50/25	30/15	25/13	-	SK-250	2	250	125,150,175,200,225,250	1,700
							3			2,800
	85/35	85/35	50/20	50/20	-	HK-250	3	250	125,150,175,200,225,250	3,500
	50/25	50/25	30/15	25/13	-	SK-400	2	400	250,300,350,400	4,300
							3			4,600
	85/35	85/35	50/20	50/20	-	HK-400	3	400	250,300,350,400	6,000
	50/25	50/25	30/15	25/13	-	SB-800	3	800	500,600	11,000
					3		800	700,800	14,000	
100/50	100/50	65/35	50/25	-	HK-800	3	800	500,600	11,500	
						3	800	700,800	15,000	
125/100	125/100	75/65	60/50	-	NF1600-SS	3	1000	1000	34,000	
						3	1200	1200	39,000	
						3	1600	1400,1600	56,500	
分 電 盤 BH 型	5/2.5	-	-	-	-	BH	1	50	15,20,30,40,50	90
	5/2.5	5/2.5	-	-	-		2	100	15,20,30,40,50	180
							3		60,75,100	305
	5/2.5	5/2.5	-	-	-		3	15,20,30,40,50	305	
							3	60,75,100	460	
	10/5	-	-	-	-	BHK	1	50	15,20,30,40,50	110
	10/5	10/5	-	-	-		2	100	15,20,30,40,50	220
							3		60,75,100	360
	10/5	10/5	-	-	-		3	15,20,30,40,50	360	
							3	60,75,100	560	
	15/5	10/5	-	-	-	BHH	1	50	15,20,30,40,50	170
	15/7.5	15/7.5	-	-	-		2	100	15,20,30,40,50	425
					3		60,75,100		765	
15/7.5	15/7.5	10/5	-	-		3	15,20,30,40,50	765		
						3	60,75,100	895		
漏 電 斷 路 器	1.5	1.5	-	30mA		KEL-230S	2	30	30 迷你型	300
	2.5	2.5	-	30mA		KEL-250	2	50	15,20,30,40,50	355
	-	2.5	2.5	30mA		KEL-350	3	50	15,20,30,40,50	620
	5	5	-	30mA		KCB-150L	1	50	15,20,30,40,50	465
						KCB-250L	2		15,20,30,40,50	660
						KCB-350L	3		15,20,30,40,50	910
	10	10	-	30mA		KCB-150	1	50	15,20,30,40,50	530
						KCB-250	2		15,20,30,40,50	800
						KCB-350	3		15,20,30,40,50	1,050
	15	15	-	30mA		KCB-150H	1	50	15,20,30,40,50	935
						KCB-250H	2		15,20,30,40,50	1,170
						KCB-350H	3		15,20,30,40,50	1,490
	25	25	-	30mA		KBL100-HS	3	100	15,20,30,40,50	1,880
									60,75,100	2,230
25	25	15	30mA		KBL-100-HH	3	100	15,20,30,40,50,60,75,100	2,750	
						4			詢價	
25	25	15	100/200/500mA		KBL-100-HHA	3	100	15,20,30,40,50,60,75,100	2,750	
						4			詢價	
50	50	30	30/100/300mA		KBL-225HH	3	225	125,150,175,200,225	5,140	
						4			詢價	

AC1 (A)	補助接點 構 成	額定電流 AC3		C 型電磁接觸器		NTH 型熱動過載保護電驛				
		220V	380V	機 種	定價	機 種	O.L 電流範圍(A) □□表最大值	適用 MC	2 素子	欠相
20	1a 或 1b	9A	8A	C-09D	345	NTH-□□	0.35~0.5/0.5~0.75/0.75~1.05A	C-09D~35D	290	350
25	1a 或 1b	12A	11A	C-11D	345		1.05~1.45/1.4~1.9/1.8~2.5/2.4~3A			
25	1a 或 1b	16A	15A	C-12D	370		2.9~4/3.8~5/4.5~6.5/6~8/8~11A			
32	1a 或 1b	22A	21A	C-18D	520		10~15 / 11~14 / 14~17A	C-12D~35D	290	350
40	1a 或 1b	32A	30A	C-25D	780		17~21A	C-18D~35D	320	375
50	1a 或 1b	42A	36A	C-35D	950		21~25A	C-18D~35D	320	375
60	1a1b	55A	52A	C-45D	1,250		24~28 / 28~32A	C-25D~35D	375	410
80	1a1b	65A	57A	C-55D	1,500		30~38 / 36~44A	C-25D~35D	410	440
90	1a1b	80A	64A	C-65D	1,700		33~50A	C-45D~100D	580	620
125	1a1b	105A	95A	C-80D	2,200		43~65 / 54~80A	C-55D~100D	-	635
130	1a1b	110A	95A	C-100D	2,600		64~96A	C-80D~100D	-	635
							85~126A	C-100D	-	1,050

額定容量三相 HP			補助接點 構 成	MSO 型電磁開關			MSL 開放型正逆電磁開關			MSL1 密閉型正逆電磁開關		
220V	380V	440V		型 式	2 素子	欠相	型 式	2 素子	欠相	型 式	2 素子	欠相
3	5	5	1a 或 1b	MSO-09D	630	680	MSL-09D	1,350	1,400	MSL1-09D	1,750	1,800
4	7.5	7.5	1a 或 1b	MSO-11D	640	690	MSL-11D	1,350	1,400	MSL1-11D	1,750	1,800
5.5	10	10	1a 或 1b	MSO-12D	690	750	MSL-12D	1,450	1,500	MSL1-12D	1,850	1,900
7.5	15	15	1a 或 1b	MSO-18D	835	900	MSL-18D	1,700	1,800	MSL1-18D	2,100	2,200
10	20	20	1a 或 1b	MSO-25D	1,200	1,250	MSL-25D	2,300	2,350	MSL1-25D	2,950	2,950
15	25	25	1a 或 1b	MSO-35D	1,400	1,450	MSL-35D	2,700	2,750	MSL1-35D	3,300	3,350
20	40	40	1a1b	MSO-45D	-	1,850	MSL-45D	-	3,500	MSL1-45D	-	4,800
25	45	45	1a1b	MSO-55D	-	2,150	MSL-55D	-	3,850	MSL1-55D	-	5,150
30	50	50	1a1b	MSO-65D	-	2,300	MSL-65D	-	4,050	MSL1-65D	-	5,300
35	60	75	1a1b	MSO-80D	-	2,800	MSL-80D	-	5,500	MSL1-80D	-	7,050
40	75	75	1a1b	MSO-100D	-	3,600	MSL-100D	-	6,900	MSL1-100D	-	8,450

類 別	品 名	接點構成	定 價	適 用 機 種	
側裝式輔助接點	CA8-D20	2a	88	C-09D~C-100D	
	CA8-D11	1a1b	88		
	CA8-D02	2b	88		
頂裝式輔助接點	CA1-D20	2a	88		
	CA1-D11	1a1b	88		
	CA1-D02	2b	88		
	CA1-D40	4a	150		
	CA1-D31	3a1b	150		
	CA1-D22	2a2b	150		
	CA1-D13	1a3b	150		
機械連鎖附 2b 接點	CA9-D02	2b	120		
過載電驛獨立座	NTH-04	-	60		NTH-0.5~NTH-32