

日本 日新牌 漏電斷路器

日新 104/07 版

| | 啟斷容量 KA | | | | 感應電流 (mA) | 機 種 | P | AF | 電流容量 | | 定 價 |
|---|--|------|------|------|-----------------------|-------------------------|-------------------------|-------|--------------------------------|---------------|--------|
| | 110V | 220V | 380V | 440V | | | | | AT(跳脫電流) | | |
| 漏電保護專用 | 1.5 | 1.5 | - | - | 30 | N-32S | 2 | 30 | 15,20,30 | | 385 |
| | 2.5 | 2.5 | - | - | 15,30,50,100,200,300 | N-42 | 2 | 40 | 15,20,30,40 | | 400 |
| | 2.5 | 2.5 | - | - | 15,30,50,100,200,300 | NR-42 | 2 | 40 | 15,20,30,40 | | 692 |
| | 2.5 | 2.5 | - | - | 30,50,100,200,300,500 | NR-62 | 2 | 60 | 50,60 | | 1,577 |
| | 2.5 | 2.5 | - | - | 30,50,100,200,300,500 | NR-102 | 2 | 100 | 75,100 | | 2,462 |
| | - | 2.5 | 2.5 | 2.5 | 15,30,50,100,200,300 | N-33-HV | 3 | 30 | 15,20,30 | | 670 |
| | - | 2.5 | 2.5 | 2.5 | 15,30,50,100,200,300 | NR-33 | 3 | 30 | 15,20,30 | | 1,554 |
| | - | 2.5 | 2.5 | 2.5 | 30,50,100,200,300,500 | NR-63 | 3 | 60 | 40,50,60 | | 1,739 |
| | - | 2.5 | 2.5 | 2.5 | 30,50,100,200,300,500 | NR-103 | 3 | 100 | 75,100 | | 2,647 |
| 漏電兼過載短路保護型 | 1.5 | 1 | - | - | 15,30,50,100,200,300 | N-32E | 2 | 30 | 15,20,30 | | 640 |
| | 2.5 | 2.5 | - | - | 15,30,50,100,200,300 | NR-32E | 2 | 30 | 5,10,15,20,30 | | 1,916 |
| | 10 | 5 | - | - | 30,50,100,200,300,500 | NR-62E | 2 | 60 | 15,20,30,40,50,60 | | 2,262 |
| | 10 | 10 | - | - | 30,50,100,200,300,500 | NR-102E | 2 | 100 | 50 | | 3,231 |
| | - | 2.5 | 1.5 | 1.5 | 15,30,50,100,200,300 | NR-33E | 3 | 30 | 5,10,15,20,30 | | 2,139 |
| | - | 5 | 2.5 | 2.5 | 30,50,100,200,300,500 | NR-63E | 3 | 60 | 15,20,30,40,50,60 | | 2,524 |
| | - | 10 | 5 | 5 | 30,50,100,200,300,500 | NR-103E | 3 | 100 | 15,20,30,40,50,60,75,100 | | 3,524 |
| | - | 35 | 18 | 18 | 30,100/200/300 可調 | N-104NB | 4 | 100 | 15,20,30,40,50(售完為止) | | 10,200 |
| | - | 35 | 18 | 18 | 30,100/200/300 可調 | N-104NB | 4 | 100 | 60,75,100(售完為止) | | 11,016 |
| | - | 60 | 30 | 25 | 200/500 可調 | N-104EGA | 4 | 100 | 15,20,30,40,50,60,75,100(售完為止) | | 21,170 |
| | - | 60 | 35 | 30 | 100/200/500 可調 | N-224EGA | 4 | 225 | 125,150,175,200,225(售完為止) | | 35,770 |
| | - | 85 | 42 | 42 | 100/200/500 可調 | N-404EBA | 4 | 400 | 300,400(售完為止) | | 48,185 |
| | 分電盤用斷路器 (安全開關) 110V 6~10A1KA, 15~30A1.5KA | | | | | | TK-211E (舊型號 ND-21E) | 2 | 1E | 6,10,15,20,30 | |
| 分電盤用斷路器 (安全開關) 110V/220V 6~10A1KA, 15~30A1.5KA | | | | | | TK-222E (舊型號 ND-22E) | 2 | 2E | 6,10,15,20,30 | | 271 |
| 配線用暗插座(附漏電保護功能) 110V/1KA, 15mA | | | | | | N-11 | | 2P | 15 | | 865 |
| 配線用暗插座(附漏電保護功能) 附接地 110V/1KA, 15mA | | | | | | N-12 | | 2P+E | 15 | | 865 |
| 分接插座 110V/1KA, 15mA | | | | | | NK-2115 | | 2P+1E | 15 | | 停售 |
| 分接插座(附漏電保護功能) 110V/1KA, 15mA | | | | | | NK-2215 | | 2P | 15 | | 631 |