

台製 伍菱牌 電磁接觸器 . 電磁開關

伍菱 2005 年版

AC1 (A)	AC3(A)		補助接點 構成	電磁接觸器 S-C 型		額定容量 HP		開放式電磁開關		封閉式電磁開關		精美型 MS 附鈕按	
	220V	380V		機種	定價	220V	440V	機種	定價	機種	定價	機種	定價
20	12	9	1a 或 1b	S-C11	350	4	5	MSO-C11	610	MS-C11	720	MS-C11PB	780
20	12	9	1a1b/2a	S-C12	420	4	5	MSO-C12	660	MS-C12	770	MS-C12PB	830
30	16	12	1a1b	S-C16	620	5.5	10	MSO-C16	935	MS-C16	1,040	MS-C16PB	1,100
36	24	21	2a2b	S-C21	740	7.5	15	MSO-C21	1,045	MS-C21	1,210	MS-C21PB	1,270
45	35	27	2a2b	S-C35	1,100	12.5	20	MSO-C35	1,430	MS-C35	1,820	MS-C35PB	1,880
65	50	44	2a2b	S-C50	1,480	17.5	30	MSO-C50	2,150	MS-C50	2,550	MS-C50PB	2,610
80	58	56	2a2b	S-C60	1,650	20	40	MSO-C60	2,200	MS-C60	2,580	MS-C60PB	2,640
100	67	63	2a2b	S-C65	2,080	25	50	MSO-C65	2,640	MS-C65	3,300	MS-C65PB	3,420
125	85	80	2a2b	S-C80	2,580	30	60	MSO-C80	3,140	MS-C80	3,730	MS-C80PB	3,850
145	110	90	2a2b	S-C100	3,520	40	80	MSO-C100	4,680	MS-C100	5,500	MS-C100PB	5,620
165	135	130	2a2b	S-C125	4,400	50	100	MSO-C125	5,500	MS-C125	6,720	MS-C125PB	6,840
200	165	160	2a2b	S-C150	5,860	60	125						
250	220	190	2a2b	S-C220	8,800	85	150						

Y-△ 起動開關 (三台裝)						TH 型 過載保護電驛			
斷容量 HP		開放型 (O)		封閉式 (D)		機種	適用接觸器	標準電流值負載 (A)	定價
220V	380V	機種	定價	機種	定價				
10	15	EYD-O-21	6,200	EYD-D-21	7,600	TH-12	S-C11~16	0.8, 1.2, 2.1, 3.5, 5, 6.5, 9, 11, 15	250
20	30	EYD-O-35	7,600	EYD-D-35	9,000	TH-20	S-C16~21	2.1, 3.5, 5, 6.5, 9, 11, 15, 22, 30	300
30	50	EYD-O-50	9,800	EYD-D-50	11,000				
40	60	EYD-O-65	11,200	EYD-D-65	13,500	TH-20T	S-C21~35	2.1, 3.5, 5, 6.5, 9, 11, 15, 22, 30	340
50	75	EYD-O-80	13,200	EYD-D-80	15,200	TH-60	S-C50~80	41, 54, 67, 80	600
60	100	EYD-O-100	17,200	EYD-D-100	20,000				
75	125	EYD-O-125	19,300	EYD-D-125	22,500	TH-60T	S-C50~80	41, 54, 67, 80	650
100	150	EYD-O-150	27,500	EYD-D-150	30,000	TH-120	S-C100~125	80, 105, 130	1,200
125	200	EYD-O-220	42,000	EYD-D-220	46,000				

台製 大菱牌 電磁接觸器 . 電磁開關

大菱 2006.05.25 版

AC1 (A)	AC3(A)		補助接點 構成	電磁接觸器 S-C□□		額定容量 HP			非可逆式電磁開關			正逆轉 MS		額定容量 HP		2 台裝 Y-△		3 台裝 Y-△		
	220V	380V		機種	定價	220V	380V	MSO-C□□	MS-C□□	MS-C□□PB	開放式	封閉式	附按鈕	開放式	封閉式	220V	440V	開放式	封閉式	開放式
20	12	9	1a/1b	C11	250	3	5.5	410	520	560	-	-	-	-	-	-	-	-	-	-
20	12	9	1a1b	C12	290	3	5.5	450	580	620	1,200	1,660	-	-	-	-	-	-	-	-
25	18	12	1a1b	C16	380	5	7.5	610	800	840	1,530	2,000	10	15	3,400	4,800	4,100	5,500		
32	22	20	2a2b	C21	560	7.5	15	780	920	960	1,800	2,300	15	20	3,900	5,300	4,600	6,000		
50	35	32	2a2b	C35	820	12	20	1,160	1,560	1,600	2,700	3,340	25	40	4,800	6,200	5,800	7,400		
70	50	46	2a2b	C50	1,100	15	30	1,600	2,300	2,400	3,420	4,400	30	50	5,400	7,000	6,800	8,600		
80	60	56	2a2b	C60	1,240	20	30	1,720	2,420	2,520	-	-	40	60	5,700	7,300	7,200	9,000		
100	65	62	2a2b	C65	1,600	20	40	2,100	2,720	2,820	-	-	40	60	6,400	8,200	8,400	10,400		
120	80	75	2a2b	C80	2,100	25	50	2,600	3,200	3,300	-	-	50	75	6,800	8,600	9,300	11,300		
150	100	80	2a2b	C100	3,000	35	70	3,800	4,500	4,700	-	-	60	100	8,900	10,900	12,200	14,400		
180	125	100	2a2b	C125	3,400	40	75	4,200	4,900	5,100	-	-	75	125	9,800	11,800	13,600	15,800		
200	150	140	2a2b	C150	5,200	60	100	6,200	7,500	-	-	-	100	150	13,400	15,600	18,600	22,000		
E 型電磁接觸器 S-E□□				E□□		MSO-	MS-	MS-P B	熱動電驛(A 為中間值)				E 型輔助接點							
20	13	12	1a	E-11	270	4	7.5	460	570	620	TH 型	TH-12	0.6/0.9/1.2/1.7/2.1 2.8/3.5/5/6.5/7.5/9/11.		160	ER-7	\$40			
20	13	12	1a	E-12	240	4	7.5	430	-	570		TH-20	0.6/0.9/1.2/1.7/2.1/2.8/3.5 5/6.5/7.5/9/11/15/18/22		220					
25	18	16	1a	E-16	320	5	10	510	610	660		TH-20T	22/30/35		280	ER-8	\$84			
40	28	25	1a	E-25	620	7.5	15	870	1,120	1,200		TH-60	30/35/40/56/67		440					
55	38	35	1a	E-35	860	10	20	1,120	1,260	1,600		TH-120	67/80/107/130		720					
70	55	50	2a2b	E-50	1,200	20	30	1,700	2,400	2,600	E 型	TRE-16	0.6/0.9/1.2/1.7/2.1/2.8 /3.5/5/6.5/7.5/9/11/15		190	4a/4b				
80	67	60	2a2b	E-60	1,320	25	40	1,820	2,520	2,720		TRE-35	15/22/30/35		250	3a1b				

台製 伍菱牌 無熔線斷路器

伍菱 2005 年版

型式	啟斷容量 KA 非對稱值 / 對稱值					機種	極數	AF	電 流 容 量 AT (跳脫電流)	定 價	
	跳脫方式	220V	380V	440V	600V						
一 般 配 電 用 S 系 列	完全電磁式	16/15	10/10	7.5/7.5	5/5	NF50-AS	2	50	15,20,30,40,50	880	
							3			980	
	完全電磁式	30/25	20/18	16/15	10/10	NF50-CS	2	50	15,20,30,40,50	1,080	
							3			1,200	
	完全電磁式	16/15	10/10	7.5/7.5	5/5	NF100-AS	2	100	15,20,30,40,50	1,080	
							3		60,75,100	1,150	
									15,20,30,40,50	1,180	
									60,75,100	1,250	
	完全電磁式	30/25	20/18	16/15	10/10	NF100-CS	2	100	15,20,30,40,50	1,100	
							3		60,75,100	1,280	
									15,20,30,40,50	1,200	
									60,75,100	1,420	
	完全電磁式	60/50	35/30	30/25	22/20	NF100-HS	2	100	15,20,30,40,50,60,75,100	1,600	
							3			1,850	
							4			3,800	
	熱動電磁式	30/25	20/18	16/15	10/10	NF225-AS	2	225	125,150,175,200,225	2,250	
3							2,600				
熱動電磁式	60/50	35/30	30/25	22/20	NF225-HS	2	225	125,150,175,200,225	3,400		
						3			3,500		
						4			5,400		
熱動電磁式	40/35	30/25	20/18	16/15	NF400-AS	2	400	250,300,350,400	6,000		
						3			6,400		
熱動電磁式	60/50	35/30	30/25	22/20	NF400-HS	2	400	250,300,350,400	6,400		
						3			6,700		
						4			10,000		
熱動可調 電磁式	60/50	35/30	30/25	22/20	NF800-HS	3	800	500,600	15,000		
						4			22,000		
熱動可調 電磁式	60/50	35/30	30/25	22/20	NF800-HS	3	800	700,800	20,000		
						4			26,000		
高 啓 斷 容 量 H 系 列	完全電磁式	100/85	60/50	60/50	35/30	NF100-H	2	100	15,20,30,40,50,60,75,100	2,200	
							3			2,400	
							4			4,300	
	熱動電磁式	100/85	60/50	60/50	35/30	NF225-H	2	225	125,150,175,200,225	4,600	
							3			5,000	
							4			8,000	
	完全電磁式	100/85	60/50	60/50	35/30	NF250-H	3	250	250	5,200	
	完全電磁式	100/85	60/50	60/50	35/30	NF400-H	2	400	250,300,350,400	8,600	
							3			9,000	
	熱動可調 電磁式	100/85	60/50	60/50	35/30	NF800-H	3	800	500,600	17,200	
							4		23,600		
							3		700,800	21,000	
							4		28,800		
	熱動可調 電磁式	100/85	60/50	60/50	35/30	NF1200-H	3	1200	1000	42,000	
							4		66,000		
							3		1200	48,000	
熱動可調 電磁式	125/100	75/65	60/50	40/35	NF1600-H	3	1600	1000,1200,1400,1600	76,000		
						4			132,000		
附 屬 配 件	適用機種		外部操作把手			電壓跳脫裝置(SHT)		補助開關裝置(AUX)		警報接點裝置(ALT)	
	NF50-AS/CS		WB050-HA	1,200		-	-	-	-	WB050-AL	370
	NF100-AS/CS/HS/H		WB100-HA	1,250		WB100-ST	1,170	WB100-AX	370	WB100-AL	370
	NF225-AS/HS/H		WB225-HA	1,300		WB225-ST	1,270	WB225-AX	460	WB225-AL	500
	NF400-AS/HS/H		WB400-HA	4,200		WB400-ST	2,220	WB400-AX	520	WB400-AL	620
	NF600-HS,NF800-HS/H		WB800-HA	7,500		WB800-ST	2,500	WB800-AX	1,760	WB800-AL	1,960
	NF1200-H, NF1600-H		WB1600-HA	9,500		WB1600-ST	4,200	WB1600-AX	2,000	WB1600-AL	2,600

型式	啟斷容量 KA 非對稱值 / 對稱值				機種	極數	AF	電流容量		定價
	110/220V	220V	380V	440V				AT (跳脫電流)		
一般型 插入式	5	-	-	-	BH	1	50	15,20,30,40,50	103	
	-	5	-	-		2	100	15,20,30,40,50	206	
	-	5	-	-		3		60,75,100	400	
	-	5	-	-	BHS	1	50	15,20,30,40,50	380	
	10	10	-	-		2	100	15,20,30,40,50	780	
	-	10	5	5		3		60,75,100	132	
	-	10	5	5	BHH	1	50	15,20,30,40,50	308	
	15	10	-	-		2	100	15,20,30,40,50	562	
	-	15	10	10		3		60,75,100	552	
	分電箱用品	-	10	5	5	BHK	1	50	15,20,30,40,50	982
		25/22	10	-	-		2	100	15,20,30,40,50	250
		-	25/22	10	10		3		60,75,100	495
-		15	10	10	BHK	1	50	15,20,30,40,50	1,000	
25/22		10	-	-		2	100	15,20,30,40,50	1,000	
-		25/22	10	10		3		60,75,100	1,152	
-		15	10	10	BHK	1	50	15,20,30,40,50	260	
25/22		10	-	-		2	100	15,20,30,40,50	520	
-		25/22	10	10		3		60,75,100	1,200	
-	15	10	10	BHK	1	50	15,20,30,40,50	1,180		
25/22	10	-	-		2	100	15,20,30,40,50	1,420		
-	25/22	10	10		3		60,75,100			

型式	啟斷容量 KA 非對稱值 / 對稱值			感度電流 (mA) (其他 : mA 可訂製)	機種	極數	AF	電流容量		定價
	110/220V	220V	380/440V					AT (跳脫電流)		
純漏電器	2.5	2.5	-	30mA	EL250-R	2	50	15,20,30	500	
	1.5	1.5	-	30mA	EL330-R	3	30	40,50	580	
	-	-	1.5	15,20,30				700		
	2.5	2.5	-	30mA	EL350-R	3	50	15,20,30,40,50	950	
BH型漏電過載保護	2.5	2.5	-	30mA	NV50-SB (1P1P 型)	3	50	15,20,30,40,50	780	
	5	5	-	30mA				1	15,20,30,40,50	720
	5	5	-	30mA				2	15,20,30,40,50	1,000
	10	10	-	30mA	NV50-MB (1P1P 型)	3	50	15,20,30,40,50	1,360	
	10	10	-	30mA				1	15,20,30,40,50	920
	10	10	-	30mA				2	15,20,30,40,50	1,200
	10	10	-	30mA				3	15,20,30,40,50	2,000
-	-	5	30mA	3	15,20,30,40,50	2,200				
工業型漏電兼過載保護器	16/15	16/15	10	30mA 30/50/100mA 可調	NV100-AB	3	100	15,20,30,40,50	3,000	
	30/25	30/25	16/15	30mA 30/50/100mA 可調	NV100-CB	3	100	60,75,100	3,300	
	60/50	60/50	30/25	30mA 30/50/100mA 可調				15,20,30,40,50	3,600	
	30/25	30/25	16/15	30mA 30/50/100mA 可調	NV100-HB	3	100	60,75,100	4,600	
	60/50	60/50	30/25	30mA 30/50/100mA 可調				15,20,30,40,50	5,200	
	30/25	30/25	16/15	30mA 30/50/100mA 可調	NV225-CB	3	225	60,75,100	7,800	
	60/50	60/50	35/30	30mA 30/50/100mA 可調				15,20,30,40,50	8,600	
	60/50	60/50	35/30	100/300/500 可調	NV225-HB	3	225	125,150,175,200,225	11,000	
	60/50	60/50	35/30	100/300/500 可調				125,150,175,200,225	12,000	
工業型漏電兼過載保護器	60/50	60/50	35/30	100/300/500 可調	NV400-HB	3	400	250,300,350,400	24,000	
	60/50	60/50	35/30	100/300/500 可調				250,300,350,400	28,000	
	60/50	60/50	35/30	100/300/500 可調	NV800-HB	3	800	500,600	45,000	
	60/50	60/50	35/30	100/300/500 可調				700,800	62,000	
60/50	60/50	35/30	100/300/500 可調	NV800-HB	4	800	500,600	88,000		
60/50	60/50	35/30	100/300/500 可調				700,800	98,000		