

日本 三菱牌 無熔線斷路器

三菱 2010 年 2 月版

型式	IEC947-2 啟斷容量 KA (Icu/Ics)				尺寸(mm)			機種	極數	AF	電 流 容 量 AT (跳 脫 電 流)	定 價
	110V	230V	380V	440V	W	L	H					
B H 型 分 電 盤 用 品	5	-	-	-	25	95	58	BH-T	1	50	15,20,30,40,50	280
	5	5	-	-	50				670			
					75				1,520			
	5	5	3	3	50	95	58	BH-T	2	100	60,75,100	1,840
					75				3,560			
	10	-	-	-	25	95	58	BH-TH	1	50	15,20,30,40,50	360
					50				840			
					75				1,940			
	10	10	-	-	50	95	58	BH-AT	2	100	60,75,100	2,200
75					3,750							
軌 道 式	IEC898 10		IEC947-2 15		17.5	86	50	FAZ-C (金鐘)	1	63	16,20,25,32,40,50,63	380
					35				1,010			
					52.5				1,800			
			IEC947-2 25		54	86	50	AZ-2-C (金鐘)	2	125	80,100,125	2,820
					81				4,320			
配 電 盤 用 工 業 用 型	2.5	2.5	1.5	-	45	96	52	NF-30CS	2	30	3,5,10,15,20,30	900
					68				1,210			
	7.5	7.5	5	2.5	50	130	68	NF-32SW	2	30	3,4,6,10,16,20,25,32	1,230
					75				1,620			
	7.5	7.5	5	2.5	50	130	68	NF-63CW	2	63	3,4,6,10,16,20,25,32 40,50,63	1,490
					75				1,720			
	15	15	7.5	7.5	50	130	68	NF-63SW	2	63	3,4,6,10,16,20,25,32 40,50,63	1,720
					75				2,080			
	25	25	10	10	50	130	68	NF-63HW	2	50	10,16,20,25,32,40,50,63	1,920
					75				2,290			
	30	30	10	10	60	130	68	NF-125CW	2	125	50,63,80,100,125	2,130
					90				2,850			
	50	50	30	25	60	130	68	NF-125SW	2	125	16,20,32,40,50,63 80,100,125	3,170
					90				4,020			
	100	100	50	50	90	130	68	NF-125HW	2	125	16,20,32,40,50,63,80,100	4,950
					3				5,880			
	85	85	36	36	105	165	86	NF-125SGW(RT)	3	125	16~25,25~40,40~63	6,500
	100	100	75	65	105	165	86	NF-125HGW(RT)	3	125	63~100,80~125 可調整	9,560
	125	125	100	65	105	165	86	NF-125HGWT(RT)	3	125	40~63,63~100 80~125 可調整	22,320
	125	125	125	125	105	240	86	NF-125RGW(RT)	3	125	16~25,25~40,40~63 63~100 可調整	27,130
	35	35	18	15	105	165	68	NF-250CW	2	250	125,150,175,200,225,250	4,990
					3				5,840			
	50	50	30	25	105	165	68	NF-250SW	2	250	125,150,175,200,225,250	7,300
					3				8,100			
	100	100	50	50	105	165	68	NF-250HW	2	250	125,150,175,200,225,250	8,170
					3				8,660			
	85	85	36	36	105	165	86	NF-250SGW(RT)	3	250	125~160,160~250 可調整	13,870
	100	100	75	65	105	165	86	NF-250HGW(RT)	3	250	125~160,160~250 可調整	13,850
	125	125	100	65	105	165	86	NF-250HGWT(RT)	3	250	125~160,160~250 可調整	33,650
	125	125	125	125	105	240	86	NF-250RGW(RT)	3	250	125~160,160~250 可調整	38,350
	50	50	40	25	140	257	103	NF-400CW	2	400	250,300,350,400	10,270
					3				13,130			
	85	85	50	42	140	257	103	NF-400SP	2	400	250,300,350,400	15,070
3					17,570							
100	100	70	65	140	257	103	NF-400HEP	3	400	200~400 可調整	28,020	
150	150	125	125	140	257	103	NF-400REP	3	400	200~400 可調整	32,200	
50	50	40	36	210	275	103	NF-630CW	3	630	500,600,630	23,510	
85	85	50	50	210	275	103	NF-630SP	3	630	500,600,630	24,990	
100	100	70	65	210	275	103	NF-630HEP	3	630	300~630 可調整	36,490	
150	150	125	125	210	275	103	NF-630REP	3	600	300~630 可調整	41,690	
50	50	40	36	210	275	103	NF-800CEW	3	800	400~800 可調整	37,110	
85	85	50	42	210	275	103	NF-800SEP	3	800	400~800 可調整	38,740	
100	100	70	65	210	275	103	NF-800HEP	3	800	400~800 可調整	42,800	
150	150	125	125	210	275	103	NF-800REP	3	800	400~800 可調整	49,480	
125	125	85	85	210	406	140	NF-1000SS	3	1000	500~1000 可調整	68,910	
125	125	85	85	210	406	140	NF-1200SS	3	1200	600~1200 可調整	84,120	
125	125	85	85	210	406	140	NF-1600SS	3	1600	800~1600 可調整	124,940	
125	125	85	85	210	406	140	NF-2000S	3	2000	(1800),2000	期貨詢價	

訂購請洽普萊格 Tel:(02)2226-8250 分機#

Fax:(02)2226-8245

普萊格企業(有)公司 編製

日本 三菱牌 漏電斷路器

三菱 2010 年 2 月版

型式	遮斷容量(KA)			感度電流(mA)	機 種	極 數	AF	電 流 容 量		定 價	
	110V	220V	440V					AT (跳脫電流)			
漏 電 過 載 短 路 保 護 器	1.5	1.5	-	15,30mA(迷你型)	NV-L20	2	30	30		550	
	10	10	5	30,100/200/500 切換	NV-30SW	3	30	(5),(10),15,20,30		3,460	
	7.5	7.5	-	30	NV-50CW	2	50	(5),(10),15,20,30,40,50		2,750	
	7.5	7.5	7.5	30,100/200/500 切換		3		(5),(10),15,20,30,40,50		3,060	
	15	15	-	30	NV-50SW	2	50	(5),(10),15,20,30,40,50		3,400	
	15	15	7.5	(30),100/200/500 切換		3		(5),(10),15,20,30,40,50		3,600	
	25	25	10	(30),100/200/500 切換	NV-50HW	3	50	15,20,30,40,50		4,150	
	30	30	10	(30),100/200/500 切換	NV-100CW	3	100	60,75,100		5,360	
	50	50	25	(30),100/200/500 切換	NV-100SW	3	100	15,20,30,(40),50,60,75,100		14,190	
	100	100	50	(30),100/200/500 切換	NV-100HW	3	100	(15),(20),(30),(40),50,60,75,100		15,600	
	35	35	15	(30),100/200/500 切換	NV-225CW	3	225	125,150,175,200,225		8,840	
	50	50	25	(30),100/200/500 切換	NV-225SW	3	225	125,150,175,200,225		15,750	
	100	100	50	(30),100/200/500 切換	NV-225HW	3	225	125,150,175,200,225		17,340	
	50	50	25	(30),100/200/500 切換	NV-400CW	3	400	250,300,350,400		19,890	
	85	85	50	(30),100/200/500 切換	NV-400SP	3	400	250,300,350,400		27,500	
	100	100	65	(30),100/200/500 切換	NV-400HEP	3	400	200~400 可調整		41,050	
	50	50	35	100/200/500 切換	NV-600CW	3	600	500,600		47,120	
	85	85	50	100/200/500 切換	NV-600SP	3	600	500,600		54,650	
	100	100	65	100/200/500 切換	NV-600HEP	3	600	300~600 可調整		60,090	
85	85	50	100/200/500 切換	NV-800SEP	3	800	400~800 可調整		81,340		
100	100	65	100/200/500 切換	NV-800HEP	3	800	400~800 可調整		90,610		
註: () 內之機型為訂製品或期貨											
其 他	漏電電驛	NV-ZBA	電壓:AC120-240V 切換,	感度電流:30,200/500 切換	43*70*118mm					4,680	
		NV-ZSA	電壓:AC120-240V/240-415V 切換,	感度電流:30,200/500 切換	63*83*117mm					7,500	
	零相比流器	ZT-15B	孔徑:15mm	外型尺寸:48*70*52 mm							4,170
		ZT-30B	孔徑 30mm	外型尺寸:68*90*52 mm							4,740
		ZT-40B	孔徑 40mm	外型尺寸:85*100*52 mm							5,550
		ZT-60B	孔徑 60mm	外型尺寸:140*150*90 mm							9,550
		ZT-80B	孔徑 80mm	外型尺寸:160*169*90 mm							10,680
ZT-100B	孔徑 100mm	外型尺寸:185*190*90 mm							14,630		
型 式 適用 機 種 及 規 格 說 明 定 價											
補 助 開 關	AX-05SWR(L)	NF32-SW,NF63-CW/SW/HW,NV30-SW,NV50-CW/SW/HW								1,330	
	AX-1SW	NF125-CW/SW/HW,NV100-CW/SW/HW								1,330	
	AX-2SWR(L)	NF250-CW/SW/HW,NV225-CW/SW/RW/SEW/HEW								1,490	
	AX-2GSWR	NF125-SGW/HGW/RGW,NF250-SGW/HGW/RGW								1,650	
	AX-4SW	NF400,630,800-CW/SW/CEW/SEW/HEW/REW								1,800	
	AX-10SWL	NF1000,1200,1600-SS								3,190	
警 報 開 關	AL-05SWR(L)	NF32-SW,NF63-CW/SW/HW								1,460	
	AL-1SW	NF125-CW/SW/HW,NV100-CW/SW/HW/RW								1,460	
	AL-2SWR(L)	NF250-CW/SW/HW,NV225-CW/SW/RW/SEW/HEW								1,760	
	AL-2GSWR	NF125-SGW/HGW/RGW,NF250-SGW/HGW/RGW								1,930	
	AL-4SWL	NF400,630-CW/SW/CEW/SEW/HEW/REW								2,100	
	AL-10SWL	NF1000,1200,1600-SS								4,270	
電 壓 跳 脫	SHTA-05SWR	NF32-SW,NF63-CW/SW/HW								2,430	
	SHTA-1SWR	NF125-CW/SW/HW								2,690	
	SHTA-2SWR	NF250-CW/SW/HW								3,500	
	SHTA-2GSWR	NF125,250-SGW/HGW/RGW/UGW								3,860	
	SHT-4SW	NF400,630,800-CW/SW/CEW/SEW/HEW/REW								4,040	
	SHT-10SWR	NF1000,1200,1600-SS								4,810	
低 電 壓 跳 脫	UVTNA-05SWR(L)	NF32-SW,NF63-CW/SW/HW,NV30-SW,NV50-CW/SW/HW								6,600	
	UVTNA-1SWR(L)	NF125-CW/SW/HW/RGW								6,600	
	UVTNA-2SWR(L)	NF250-CW/SW/HW/RGW								7,260	
	UVTNA-2GSWR	NF125-SGW/HGW/RGW,NF250-SGW/HGW/RGW								8,450	
	UVTNA-4SW	NF400,630,800-CW/SW/CEW/SEW/HEW/REW								8,840	
	UVTNA-10SWR	NF1000,1200,1600-SS								12,860	
操 作 把 手	F05S	NF32-SW,NF63-CW/SW/HW,NV30-SW,NV63-CW/SW/HW								2,250	
	F1S	NF125-CW/SW/HW,NV100-CW/SW/HW								2,250	
	F2S	NF-250CW/SW/HW,NV225-CW/SW/HW/HEW								2,630	
	F2GUL	NF125-SGW/HGW,NF250-SGW/HGW								2,900	
	F4S	NF400-CW/SP/SEP/HEP/REP,NF630CW								4,000	
	F8S	NF630-SP/SEP/HEP/REP,NF800-CEW/SEP/HEP/REP								5,640	
F10SW	NF1000,1200,1600-SS								6,320		

訂購請洽普萊格 Tel:(02)2226-8250 分機#

Fax:(02)2226-8245

普萊格企業(有)公司 編製

日本 三菱牌 電磁接觸器 . 熱動電驛 . 補助接點

三菱 2010 年 2 月版

AC1 (A)	補助 接點	額定電流 AC3		S 型電磁接觸器		直流用電磁接觸器		2 素子熱動電驛		欠相用 3 素子熱動電驛	
		220V	440V	機 種	機 種	機 種	定 價	機 種	定 價	機 種	定 價
20	1a 或 1b	11	7	S-N10	630						
20	1a 或 1b	13	9	S-N11	700	SD-N11	2,240	TH-N12	680	TH-N12KP	950
20	1a1b	13	9	S-N12	900	SD-N12	2,740				
25	-	18	13	S-N18AX	1,120			TH-N18	690	TH-N18KP	990
32	1a1b	20	20	S-N20	1,190			TH-N20	710	TH-N20KP	1,050
32	2a2b	20	20	S-N21	1,230	SD-N21	3,490				
50	2a2b	26	25	S-N25	1,760			TH-N20TA	990	TH-N20TAKP	1,360
60	2a2b	35	32	S-N35	2,320	SD-N35	4,490				
80	2a2b	50	46	S-N50	2,780	SD-N50	4,980	TH-N60	1,610	TH-N60KP	2,600
100	2a2b	65	65	S-N65	3,450	SD-N65	7,720				
135	2a2b	80	80	S-N80	5,570	SD-N80	11,580	TH-N60TA	1,860	TH-N60TAKP	2,850
150	2a2b	100	93	S-N95	5,910	SD-N95	13,200				
150	2a2b	125	120	S-N125	7,940	SD-N125	19,920	TH-N120	2,730	TH-N120KP	3,600
200	2a2b	150	150	S-N150	11,470	SD-N150	22,410	TH-N120TA	3,100	TH-N120TAKP	3,720
260	2a2b	180	180	S-N180	14,040			TH-N220RH	5,210	TH-N220RHKP	6,320
260	2a2b	220	220	S-N220	17,660	SD-N220	37,980				
350	2a2b	300	300	S-N300	24,700	SD-N300	78,440	TH-N400RH	6,420	TH-N400RHKP	7,690
450	2a2b	400	400	S-N400	28,840	SD-N400	133,840				
660	2a2b	630	630	S-N600	64,800	SD-N600	173,060				
800	2a2b	800	800	S-N800	100,080						

額定容量 HP		補助接 點構成	開放式電磁開關		正逆電磁開關		機械連鎖		補助接點		
220V	380V		機 種	機 種	定 價	二素子	機 種	定 價	機 種	定 價	
3	3.5	1a 或 1b	MSO-N10	1,170				UN-ML11 N10-N12 用	1,190	UN-AX2 N10-N65 用上裝式	410
3.5	5	1a 或 1b	MSO-N11	1,230	MSO-2xN11	3,970					
3.5	5	1a1b/2b	MSO-N12	1,340							
5	7.5	-	MSO-N18AX	1,690				UN-ML21 N18-N65 用	1,010	UN-AX4 N10-N65 用上裝式	750
5	10	1a1b	MSO-N20	1,750							
5	10	2a2b	MSO-N21	1,810	MSO-2xN21	5,580					
7.5	15	2a2b	MSO-N25	2,360	MSO-2xN25	6,200					
10	20	2a2b	MSO-N35	3,060	MSO-2xN35	6,940					
15	25	2a2b	MSO-N50	3,820	MSO-2xN50	8,930					
20	35	2a2b	MSO-N65	4,260	MSO-2xN65	13,760		UN-ML80 N80-N125 用	1,560	UN-AX80 N80-N125 用側裝式	800
25	40	2a2b	MSO-N80	6,270	MSO-2xN80	16,120					
30	60	2a2b	MSO-N95	7,500				UN-ML150 N150 用	1,560	UN-AX150 N150-N400 用側裝式	830
40	75	2a2b	MSO-N125	9,620							
50	100	2a2b	MSO-N150	13,620							
60	125	2a2b	MSO-N180	17,230				UN-ML220 N180-N400 用	1,820	UN-AX150 N150-N400 用側裝式	830
75	150	2a2b	MSO-N220	23,040							
100	180	2a2b	MSO-N300	32,220							
150	300	2a2b	MSO-N400	38,660							

電磁繼電器 (直流用) 16A				電磁繼電器 (交流用) 16A			
線圈電壓	接點構成	機 種	定 價	線圈電壓	接點構成	機 種	定 價
DC24V	4a,3a1b,2a2b	SRD-N4□□	2,230	AC12V	2a2b,3a1b,4a	SR-N4□□	740
	5a,4a1b,3a2b,2a3b	SRD-N5□□	2,350	AC24V	5a,4a1b,3a2b,2a3b	SR-N5□□	1,150
DC48V	8a,6a2b,4a4b,7a1b,5a3b	SRD-N8□□	2,600	AC48V	6a,5a1b4a2b,3a3b	SR-K6□□	800
DC110V	10a,8a2b,7a3b,6a4b,5a5b	SRD-K100□□	4,710	AC110V	8a,7a1b,6a2b,5a3b,4a4b	SR-N8□□	930
DC220V	4a,3a1b,2a2b	SRLD-N4□□	4,340	AC220V	2a2b	SRL-N4□□	3,720
	5a4b,4a5b,6a3b 7a2b,8a1b,9a	SRLD-K100□□	6,820	AC380V AC440V	5a4b,9a	SRL-K100□□	6,200

訂購請洽普萊格 Tel:(02)2226-8250 分機#

Fax:(02)2226-8245

普萊格企業(有)公司 編製