

**美國奇異(歐規)無熔線斷路器 . 漏電斷路器 (注意折數較高) 奇異 2009 年版**

型式	啟斷容量 KA 對稱值(非對稱值)					機 種	極 數	AF	電 流 容 量	定 價			
	230/400V IEC898	240V IEC947	415V IEC947	220/240V NEMA	DC60V(1P) 125V(2P)				AT ( 跳 脫 電 流 )				
歐 規 軌 道 式 微 型 斷 路 器	6	10	3	20	20	<b>G60</b> C TYPE	1	63	0.5,1,2,3,4,6 10,16,20,25,32 40,50,63	<b>325</b> <b>220</b> <b>315</b>			
	6	20	10	20	25		2	63	0.5,1,2,3,4,6 10,16,20,25,32 40,50,63	<b>500</b> <b>515</b> <b>710</b>			
	6	20	10	20			3	63	0.5,1,2,3,4,6 10,16,20,25,32 40,50,63	<b>925</b> <b>715</b> <b>1,110</b>			
	10	25	4	30	25	<b>G100</b> C TYPE	1	63	0.5,1,2,3,4 6,10,16,20,32 40,50,63	<b>330</b> <b>340</b> <b>610</b>			
	10	30	15	30	30		2	63	0.5,1,2,3,4 6,10,16,20,32 40,50,63	<b>695</b> <b>715</b> <b>1,360</b>			
	10	30	15	30			3	63	0.5,1,2,3,4 6,10,16,20,32 40,50,63	<b>1,055</b> <b>1,110</b> <b>1,965</b>			
	微 型 斷 路 器	25 20 15				25	<b>GT25</b> C TYPE	1	63	16,20,32	<b>445</b>		
										40,50	<b>630</b>		
										63	<b>755</b>		
		50 40 30 50 40 30	25 20 15			30			2	63	16,20,32	<b>785</b>	
											40,50	<b>1,360</b>	
											63	<b>1,490</b>	
			10 4.5			10			3	63	16,20,32	<b>1,170</b>	
											40,50	<b>1,965</b>	
	63										<b>1,965</b>		
		15 10			15		<b>Hti</b> C TYPE	1	125	80 100 125	<b>1,340</b> <b>1,500</b> <b>2,140</b>		
										2	125	80 100 125	<b>2,480</b> <b>2,730</b> <b>4,140</b>
												3	125
附 屬 裝 置	軌道式 MCB G TYPE 用	1ab(1c)	<b>CA-H</b>	補助接點	<b>335</b>								
		1ab(1c)	<b>CA-S/H</b>	警報接點	<b>425</b>								
		1ab+1ab(1c+1c)	<b>CB-SH/HH-L</b>	補助接點+警報接點	<b>455</b>								
		AC24~60V/DC24~48V	<b>TELE L1</b>	分路跳脫	<b>1,105</b>								
		AC110~415V/DC125V	<b>TELE L2</b>	分路跳脫	<b>1,105</b>								
		AC/DC24V	<b>TELE U-24</b>	不足電壓	<b>1,450</b>								
		AC/DC48V	<b>TELE U-48</b>	不足電壓	<b>1,450</b>								
		AC230V	<b>TELE U-230</b>	不足電壓	<b>1,450</b>								
		1P+N 20A30mA	<b>DM100C20/030</b>	漏電斷路器	<b>1,690</b>								
		1P+N 32A30mA	<b>DM100C32/030</b>	漏電斷路器	<b>1,690</b>								
		2P 32A 以下 30mA	<b>DOC232/030</b>	漏電裝置(側裝)	<b>2,585</b>								
		2P40~ 63A30mA	<b>DOC263/030</b>	漏電裝置(側裝)	<b>3,550</b>								
		3P 32A 以下 30mA	<b>DOC332/030</b>	漏電裝置(側裝)	<b>4,195</b>								
3P40~ 63A30mA	<b>DOC363/030</b>	漏電裝置(側裝)	<b>4,235</b>										
軌道式 MCB Hti 用	1ab(1c)	<b>Hti-H</b>	補助接點	<b>360</b>									
	1ab(1c)	<b>Hti-H/S</b>	警報接點	<b>425</b>									
	1ab+1ab(1c+1c)	<b>Hti-HH/HS</b>	補助接點+警報接點	<b>580</b>									
	AC24~60V/DC24~48V	<b>TELE L24</b>	分路跳脫	<b>1,105</b>									
	AC110~415V/DC125V	<b>TELE L110</b>	分路跳脫	<b>705</b>									

訂購請洽普萊格 Tel:(02)2226-8250 Fax:(02)2226-8245

普萊格企業(有)公司 98'編製

## 美國奇異(歐規) 無熔線斷路器

(注意折數較高)奇異 2009 年版

型式	啟斷容量 KA 對稱值(非對稱)					機 種	極 數	AF	電 流 容 量	定 價
	230/240V	400/415V	480V NEMA	500V	DC500V(3P) DC250V(1P)				AT ( 跳 脫 電 流 )	
歐規工業用型	50(60)	36(40)	25(30)	18(20)	25(30)	<b>FDS</b>	3	63/160	16,20,32,40,50,63,80,100 125,160	<b>4,830</b> <b>8,160</b>
	65(75)	36(40)	36(40)	18(20)	25(30)	<b>FEV</b>	3	250	125,160,200,250	<b>11,010</b>
	85(100)	50(60)	36(40)	22(25)	40(45)	<b>FDN</b>	3	63/160	16,20,32,40,50,63,80,100 125,160	<b>5,305</b> <b>9,515</b>
	85(100)	50(60)	50(60)	30(35)	50(60)	<b>FEN</b>	3	250	125,160,200,250	<b>12,235</b>
	85(100)	50(60)	50(60)	30(35)		<b>FGN</b>	3	400	400(0.625~1.0In)電子式	<b>22,360</b>
								630	630(0.625~1.0In)電子式	<b>32,985</b>
85(100)	50(60)	42(50)	36(40)	36(40)	<b>FKN</b>	3	800	800(0.4~1.0In)電子式	<b>59,495</b>	
							1000	1000(0.4~1.0In)電子式	<b>82,375</b>	
							1250	1250(0.4~1.0In)電子式	<b>105,260</b>	
歐規高遮斷型	50(60)				50(60)	<b>FDH</b>	1	160	16,20,32,40,50,63,80,100 125,160	<b>2,975</b> <b>4,040</b>
	100(125)	80(95)	50(60)	36(40)	65(75)	<b>FDH</b>	3	63/160	16,20,32,40,50,63,80,100 125,160	<b>7,275</b> <b>10,810</b>
	100(125)	80(95)	65(75)	50(60)	85(100)	<b>FEH</b>	3	160	25,32,40,50,63,80,100 125,160	<b>8,000</b> <b>11,890</b>
	100(125)	80(95)	65(75)	50(60)	85(100)	<b>FEH</b>	3	250	125,160,200,250	<b>13,460</b>
	100(125)	80(95)	65(75)	50(60)		<b>FGH</b>	3	400	400(0.625~1.0In)電子式	<b>25,955</b>
								630	630(0.625~1.0In)電子式	<b>37,330</b>
100(125)	80(95)		42(50)	50(60)	<b>FKH</b>	3	800	800(0.4~1.0In)電子式	<b>66,815</b>	
							1000	1000(0.4~1.0In)電子式	<b>91,530</b>	
							1250	1250(0.4~1.0In)電子式	<b>114,410</b>	
歐規限流型	200(250)	150(175)		50(60)	100(125)	<b>FDL</b>	3	63/160	25,32,40,50,63,80,100 125,160	<b>20,510</b> <b>24,045</b>
	200(250)	150(175)	130(150)	100(125)	100(125)	<b>FEL</b>	3	250	125,160,200,250	<b>29,560</b>
	200(250)	150(175)	130(150)	100(125)		<b>FGL</b>	3	400	400(0.625~1.0In)電子式	<b>63,830</b>
								630	630(0.625~1.0In)電子式	<b>90,275</b>
170(200)	100(125)		50(60)	60(70)	<b>FKL</b>	3	800	800(0.4~1.0In)電子式	<b>115,060</b>	
							1000	1000(0.4~1.0In)電子式	<b>164,180</b>	
							1250	1250(0.4~1.0In)電子式	<b>177,110</b>	
附屬裝置	適用機種/FDS,FDN,FDH,FDL					<b>FDNRC(FDFH)</b>			操作把手	<b>2,245</b>
	適用機種/FEV,FEN,FEH,FEL					<b>FENRC(FDFH)</b>			操作把手	<b>2,270</b>
	適用機種/FGN,FGH,FGL					<b>FGNRC(FGFH)</b>			操作把手	<b>3,425</b>
	適用機種/FKN,FKH,FKL					<b>FNNRC(FNFH)</b>			操作把手	<b>6,125</b>
	適用機種/FD,FE,FG					<b>FAS10R</b>			補助接點 1a	<b>990</b>
	適用機種/FD,FE,FG					<b>FAS01L</b>			補助接點 1b	<b>990</b>
	適用機種/FK					<b>FNS11R</b>			補助接點 1a1b	<b>1,210</b>
	適用機種/FD					<b>FDBAM11</b>			警報開關 1a1b	<b>990</b>
	適用機種/FE,FG					<b>FABAM10</b>			警報開關 1a	<b>990</b>
	適用機種/FD,FE,FG					<b>FABAT01</b>			警報開關 1b	<b>990</b>
	適用機種/FK					<b>FNBA11R</b>			警報開關 1a1b	<b>1,420</b>
	適用機種/FD,FE,FG					<b>FASHTJ</b>			分路跳脫 AC/DC110/130V	<b>4,175</b>
	適用機種/FD,FE,FG					<b>FASHTN</b>			分路跳脫 AC220VDC250V	<b>4,175</b>
	適用機種/FK					<b>FNSHTJ</b>			分路跳脫 AC/DC110/130V	<b>7,880</b>
	適用機種/FK					<b>FNSHTN</b>			分路跳脫 AC220VDC250V	<b>7,880</b>
	適用機種/ FD,FE,FG					<b>FAUVRJ</b>			不足電壓 AC/DC110/130V	<b>5,305</b>
	適用機種/ FD,FE,FG					<b>FAUVRN</b>			不足電壓 AC220VDC250V	<b>5,305</b>
	適用機種/ FK					<b>FNUVR5</b>			不足電壓 AC230V	<b>8,755</b>
	適用機種/ FD 下裝瞬時~600mSEC 可調 3P160A					<b>FDQDB3M(220~440V)</b>			漏電裝置 30mA 10A 可調	<b>15,615</b>
適用機種/ FE 下裝瞬時~600mSEC 可調 3P250A					<b>FEQDB3MK(220~440V)</b>			漏電裝置 30mA 10A 可調	<b>23,325</b>	
適用機種/ FG 下裝瞬時~600mSEC 可調 3P400/630A					<b>FGQDB3M(220~440V)</b>			漏電裝置 30mA 10A 可調	<b>28,395</b>	

訂購請洽普萊格 Tel:(02)2226-8250 Fax:(02)2226-8245

普萊格企業(有)公司 98'編製

# 美國奇異 無熔線斷路器 . 漏電斷路器

奇異 2007 年版

型式	啟斷容量 KA 對稱值(非對稱值)					機 種	極 數	AF	電 流 容 量		定 價
	120V	120/240V	240V	240/415V	415V				AT ( 跳 脫 電 流 )		
軌道式			15 IEC947-2	10 IEC898		<b>G2000</b> (售完為止)	1	63	0.5,2,4,6	<b>365</b>	
									10,16,20,25,32	<b>245</b>	
									40,50,63	<b>355</b>	
			30 IEC947-2	10 IEC898	15 IEC947-2			2	63	0.5,2	<b>560</b>
										16,20,25,32	<b>580</b>
										40,50,63	<b>800</b>
			30 IEC947-2	10 IEC898	15 IEC947-2			3	63	0.5,1,2,4,6	<b>1,050</b>
										10,32	<b>810</b>
										40,50,63	<b>1,250</b>
經濟用分電盤型	10		5			<b>TQC</b> (售完為止)	1	70	15,50,60	<b>280</b>	
		10		5					70	<b>530</b>	
		10		5			2	100	15,20,30, 40,50,60	<b>560</b>	
									70,,80,90,100	<b>910</b>	
		10		5			3	100	15,20,30,40,50,60	<b>1,300</b>	
									70,,80,90,100	<b>1,800</b>	
	22 (25)		9				1	70	15,20,30,40,50,60	<b>520</b>	
									70	<b>740</b>	
		22 (25)		9					2	100	15,20,30
					40,50,60	<b>1,000</b>					
	22 (25)		9		3	100	70,80,90,100	<b>1,350</b>			
							15,20,30,40,50,60	<b>1,400</b>			
								70,80,90,100	<b>1,900</b>		
插入式無熔線斷路器	10		5			<b>TQL</b> (售完為止)	1	70	15,20,30	<b>205</b>	
									40,50,60	<b>210</b>	
									70	<b>370</b>	
		10		5			2	100	15,20,30	<b>445</b>	
									40,50,60	<b>485</b>	
									70	<b>740</b>	
		10		5			3	100	80,90,100	<b>990</b>	
									15,20,30	<b>980</b>	
									40,50,60	<b>990</b>	
									70	<b>1,450</b>	
									80,90,100	<b>1,750</b>	
	22 (25)		9				1	70	15,20,30	<b>445</b>	
									40,50,60	<b>570</b>	
									70	<b>730</b>	
			22 (25)	9			2	100	15,20,30	<b>700</b>	
					40,50,60	<b>750</b>					
					70	<b>850</b>					
							80,90,100	<b>1,100</b>			
	22 (25)		9		3	100	15,20,30	<b>1,200</b>			
							40,50,60	<b>1,300</b>			
							70	<b>1,550</b>			
							80,90,100	<b>1,900</b>			
漏電斷路器	10				插入式 (售完為止)	<b>THQL-GF</b>	1	30	15,20,30	<b>2,100</b>	
			10				2	30	15,20,30	<b>4,000</b>	
				3		<b>TQL-GF</b>	1	30	15,20,30	<b>2,650</b>	
	10				卡式 (售完為止)	<b>THQC-GF</b>	1	30	15,20,30	<b>3,000</b>	
			10				2	30	15,20,30	<b>5,800</b>	
	10				後出線 (售完為止)	<b>THQB-GF</b>	1	30	15,20,30	<b>2,450</b>	
		10		2			30	15,20,30	<b>3,850</b>		

# 美國奇異 無熔線斷路器

奇異 2005 年版

型式	啟斷容量 KA 對稱值(非對稱)				機種	極數	AF	電 流 容 量		定 價	附 屬 裝 製	
	120/240V	240/415V	480V	600V				AT ( 跳 脫 電 流 )			操作把手	定 價
工業 型 系 列 無 熔 線 斷 路 器 ( 配 電 線 用)	10				TEB (售完為止)	1	100	15,20,30,40,50,60	2,000	TEFR1B TEB/D/ED 用	3,550	
	10	10				2		70,80,90,100	2,900			
						3		15,20,30,40,50,60	2,700			
									70,80,90,100	3,100	TFKR1B TFJ/THFK 用	4,100
									15,20,30,40,50,60	3,500		
									70,80,90,100	3,750		
	AC227V 14			10	TED (售完為止)	1	100	15,20,30,40,50,60	2,250	TJR1B TJD/J/K 用	4,800	
	18(20)	16(17)	14 (15)			2		70,80,90,100	3,000			
						3		15,20,30,40,50,60	3,300			
									70,80,90,100	4,000	TKMR1B TKMA 用	7,000
									15,20,30,40,50,60	4,500		
									70,80,90,100	4,650		
	18(20)	16(17)	14 (15)	14 (15)	TED (售完為止)	3	150	15,20,30,40,50,60	5,300	手 柄	定 價	
								70,80,90,100	5,900			
	277V65/75				THED	1	30	15,20,30	4,350	SEFR1 SE150 用	3,550	
	65(75)	26(31)	25 (30)	18 (28)		2	100	15,20,30,40,50,60	5,400			
												70,80,90,100
	42(50)							15,20,30,40,50,60	6,900	SEFR1 SF250 用	4,100	
								70,80,90,100	7,800			
	14(15)	10			TCB (售完為止)	2	100	15,20,30,40,50	2,400	SKR1 SK1200 用	7,000	
3						60,75,100		2,450				
								15,20,30,40,50	3,300	補助接點	定 價	
								60,75,100	3,500			
								70,80,90,100	4,650			
25(30)	14(15)			TCD (售完為止)	2	100		15,20,30,40,50	3,050	SAUXPAB1 AC240/DC125V 1ab	4,200	
					3		60,75,100	3,100				
							15,20,30,40,50	3,650	SE/SF/SG/SK 用			
							60,75,100	3,850				
10	10			TQD (售完為止)	2	225	125,150,175,200,225	3,450	SAUXPAB2 AC240/DC125V 2ab	8,300		
					3			6,700				
22(25)	22(25)			THQD (售完為止)	2	225	125,150,175,200,225	5,700	SE/SF/SG/SK 用			
					3			8,400				
25(30)	25(30)	22 (25)	18(20)	TFJ (售完為止)	2	225	125,150,175,200,225	11,000	分路跳脫	定 價		
					3			12,000				
65(75)	28(33)	25 (30)	18 (20)	THFK	2	225	125,150,175,200,225	23,500	SAST1 AC120/DC125V SE/SF/SG/SK 用	10,500		
					3			24,000				
22(25)	22(25)			TJD (售完為止)	2	400	250,300,350,400	16,000	SAST2 AC240/DC250V SE/SF/SG/SK 用	10,500		
					3			18,000				
42(50)	34(38)	30 (35)	22 (25)	TJJ (售完為止)	2	400	125,150,175,200,225	22,000				
					3		250,300,350,400	22,000				
42(50)	34(38)	30(35)	22(25)	TJK	3	600	500,600(售完為止)	38,000	警報開關	定 價		
								25,000				
65(75)	36(41)	35 (40)	25 (30)	THJK	2	400	250,300,350,400	30,000				
					3			52,000				
								64,000	SABAP1 AC240/DC125V SE/SF/SG/SK 用	4,350		
								105,000				
42(50)	36(41)	30 (35)	22 (25)	TKMA (售完為止)	3	800	700,800,	68,000	低電壓跳脫	定 價		
							1000	120,000				
							1200	140,000				
100		65	25	SELA	3	150	15,20,30,40,50,60	20,000	SAUV1 AC120/DC125V SE/SF/SG/SK 用	10,500		
							70,80,90,100	23,500				
							110,,125,150	38,000				
200		100	25	SEPA	3	150	15,20,30,40,50,60	24,500	SAUV2 AC240/DC250V SE/SF/SG/SK 用	10,500		
							70,80,90,100	30,000				
							110,125,150	66,000				
100		65	25	SFLA	3	250	125,150,175,200,225,250	42,000	插入式電子額定電流座			
200		100	25	SFPA	3	250	125,150,175,200,225,250	55,000				
100		65	65	SGLA	3	400	250,300,350,400	56,000	SRPE* SE150 用	4,500		
							500,600	67,000				
200		100	65	SGPA	3	400	250,300,350,400	73,000	SRPF* SF250 用	4,700		
							500,600	86,000				
100		65	42	SKLA	3	800	700,800	87,000	SRPG* SG600 用	5,000		
							1200	145,000				
200		100	65	SKPA	3	800	700,800	135,000	SRPK* SK1200 用	5,400		
							1200	180,000				

AC1	AC3 (A)	補助 接點	適用馬力 HP		電磁接觸器		3 素子熱動過負載電驛		
			220V	380V	型 式	定 價	型 式	規 格 可 調 整 範 圍 (A)	定 價
20	6	1a	2	3	MC0A310AT	2,600	MT03□	0.11~0.17,0.17~0.26,0.26~0.43,0.43~0.65, 0.65~1,0.85~1.3,1.1~1.6,1.35~2,1.7~2.4,2.2~3.2 2.5~4,3~4.7,4~6.3,5.5~8,7.5~10.5,10~14	2,850
20	9	1a	4	5.5	MC1A310AT	2,700			
25	9	1a	3	5.5	CL00A310T	2,900	RT1□	B/0.16~0.26,C/0.25~0.41,D/0.4~0.65,F/0.65~1.1 G/1~1.5,H/1.3~1.9,J/1.8~2.7,K/2.5~4,L/4~6.3 M/5.5~8.5,N/8~12,P/10~16 S/14.5~18,T/17.5~22,U/21~26,V/25~32 W/30~40	3,500
25	12	1a	4	7.5	CL01A310T	3,450			
32	18	1a	5.5	10	CL02A310T	4,300			
45	25	1a	10	15	CL25A310T	5,700			
45	25	1a	10	16	CL03A310M	6,000			
60	32	1a	12	22	CL04A310M	8,300			
60	40	1a1b	15	25	CL45A311M	10,500			
90	50	1a1b	20	30	CL06A311M	12,500			
110	65	1a1b	25	40	CL07A311M	18,000	RT2□	A/11.5~15,B/14.5~19,C/18.5~25 D/24~32,E/30~43 G/42~55,H/54~65 J/64~82 L/78~97,M/90~117	13,000
110	80	1a1b	30	50	CL08A311M	22,500			
140	95	1a1b	34	60	CL09A311M	26,000			
140	105	1a1b	40	75	CL10A311M	31,000			
250	150	1a1b	60	100	CK75CA311	42,500	RT3□	B/55~80,C/63~90,D/90~120 E/110~140,F/140~190	21,000
250	185	1a1b	75	125	CK08CA311	49,500			
315	205	1a1b	88	150	CK85BA311	67,000	RT4□	N/120~190 P/175~280 R/200~310	25,500
315	250	1a1b	100	180	CK09BE311	84,000			
450	309	1a1b	125	220	CK95BE311	96,000	RT5□	A/120~190,B/175~280,C/250~400 D/315~500 E/430~700	32,500
600	420	1a1b	170	300	CK10CE311	120,000			
700	550	1a1b	220	380	CK11CE311	170,000			
1000	700	1a1b	300	510	CK12BE311	230,000	RT6A	500~800	33,000
1250	825	1a1b	340	610	CK13BA311	380,000			

補助電驛及補助接點&機械連鎖					接觸器用補助接點				
品名	型 式	補助接點	安 裝	定 價	安 裝	型 式□□:a,b	補 助 接 點 構 成	可 安 裝 之 補 助 接 點 數	定 價
補助電驛	MCRA0□□AT a b	4a,3a1b, 2a2b,1a3b,4b	16A 頂裝	2,600	頂裝式	MACN211AT	1a1b	MC 系列	580
						MACN202AT	2b		580
						MACN4□□AT	3a1b,2a2b 1a3b		1,100
補助接點	MARN2□□AT	2a,1a1b,2b	頂裝	580	側裝式	MACL110AT	1a	頂裝×4 + 側裝×3	460
	MARN4□□AT	4a,3a1b,2a2b, 1a3b,4b	頂裝	1,200		MACL101AT	1b		460
						MARL110ATS	1a		460
	MARL101ATS	1b	460						
機械連鎖組	MARL1□□AT	1a,1b	側裝	460	頂裝式	BCLF10	1a	CL 系列	450
	MMHO	MC 系列接觸器 及補助電驛用	345	BCLF01		1b	CL00~CL02 頂裝×4		450
				BCLL20		2a	CL03~CL45 頂裝×4 + 側裝×1	1,300	
	BELA	CL00 ~ CL45 用	1,050	側裝式		BCLL11	1a1b	CL05~CL10 頂裝×6×側裝×1	1,250
	BEL	CL06 ~ CL10 用	1,600			BRLL20	2a	CK 系列	1,300
BEKH	CK75 ~ CK12 用	4,700	BRLL11		1a1b	(左)側裝×2+(右)側裝×2	1,250		