

台製 林石牌 無熔線斷路器

林石 2007 年版

型式	啟斷容量 KA 非對稱值 / 對稱值					機 種		極數	AF	電 流 容 量 AT ( 跳脫電流 )	定 價					
	110V	110/220V	220V	380V	440V	一般型	插入式									
B H 系列 (分電盤用品)	5	5	-	-	-	BH	BH	1	50	10,15,20,30,40,50	110					
	-		5					-	-	-	2	100	10,15,20,30,40,50 60,75,100	218 392		
								-			3	100	10,15,20,30,40,50 60,75,100	375 770		
	10	10	-	-	-			BHQ	BHQ	1	50	10,15,20,30,40,50	132			
	-		10							-	-	-	2	100	10,15,20,30,40,50 60,75,100	280 530
										-			3	100	10,15,20,30,40,50 60,75,100	530 800
	15	15	-	-	-	BQL	-			1	100	10,15,20,30,40,50	189			
	-		15							-	10	7.5	2	100	10,15,20,30,40,50 60,75,100	390 870
										-			3	100	10,15,20,30,40,50 60,75,100	870 990

台製 林石牌 漏電斷路器

林石 2007 年版

型式	啟斷容量 KA 非對稱 / 對稱值			額定感應電流 ( mA )	機 種	極數	AF	電 流 容 量 AT ( 跳脫電流 )	定 價
	110V	110/220V	380/440V						
純漏電斷路器	2.5	2.5	-	30mA	E-32	2	50	15,20,30	430
	2.5	2.5	-	100mA				40	500
				200mA				50	560
	-	-	1.5	300mA	E-33	3	50	15,20,30	650
				40,50				850	
				15,20,30 40,50				900 1,000	
BH 型漏電兼過載保護	5	5	-	30mA	EB-51	1	50	15,20,30,40,50	620
	5	5	-	100mA	EB-52	2	50	15,20,30,40,50	870
	-	-	2.5	200mA	EB-53	3	50	15,20,30,40,50	1,100
	5	5	-	300mA				15,20,30,40,50	1,150
	-	-	2.5	(分卡式及插入式) (1P型) 0.1 秒	EQ-51	1	50	15,20,30,40,50	1,350
	10	10	-		EQ-52	2	50	15,20,30,40,50	800
	10	10	-		EQ-53	3	50	15,20,30,40,50	1,000
	-	-	5					15,20,30,40,50	1,200
	10	10	-					15,20,30,40,50	1,700
	-	-	5					15,20,30,40,50	1,900
工業型漏電兼過載短路保護型	10	10	5	30/100/300mA  可切換式 0.1 秒	EG-103B	3	100	10,15,20,30,40,50	2,500
	30/25	30/25	20/18			4		60,75,100	2,800
					100/85	100/85	60/50	3	10,15,20,30,40,50
	4	60,75,100	5,000						
	30/25	30/25	20/18		EG-103R	3	100	10,15,20,30,40,50	3,400
						4		60,75,100	5,600
	100/85	100/85	60/50	EG-103H	3	100	10,15,20,30,40,50	6,000	
					4		60,75,100	7,500	
	30/25	30/25	20/18	EG-203R	3	225	125,150,175,200,225	7,700	
					4		125,150,175,200,225	11,000	
	100/85	100/85	60/50	EG-203H	3	225	125,150,175,200,225	10,000	
					4		125,150,175,200,225	12,000	
100/85	100/85	60/50	EG-403H	3	400	250,300,350,400	14,500		
				4		250,300,350,400	24,000		

- 林石牌 P.1 -

型式	啟斷容量 KA 非對稱值 / 對稱值				機種	極數	AF	電流容量		定價
	220V	380V	440V	600V				AT (跳脫電流)		
N F 型  無 熔 線 斷 路 器 — 配 電 · 配 線 用	16/15	10	7.5	5	NF103B	2	100	10,15,20,30,40,50	782	
								60,75,100	998	
	30/25	20/18	12/10	6/5	NF103S	1	100	10,15,20,30,40,50	825	
								60,75,100	910	
								10,15,20,30,40,50	955	
						2	100	60,75,100	1,110	
								10,15,20,30,40,50	1,100	
								60,75,100	1,235	
	60/50	35/30	25/22	12/10	NF103R	1	100	10,15,20,30,40,50,60,75,100	1,130	
								10,15,20,30,40,50,60,75,100	1,395	
								10,15,20,30,40,50,60,75,100	1,610	
								10,15,20,30,40,50,60,75,100	3,130	
	30/25	20/18	16/15	7.5	NF203G	2	225	125,150,175,200,225	1,740	
								125,150,175,200,225	1,960	
								125,150,175,200,225	2,300	
	60/50	35/30	25/22	12/10	NF203R	1	225	125,150,175,200,225	2,550	
								125,150,175,200,225	2,950	
								125,150,175,200,225	3,050	
								125,150,175,200,225	5,300	
	60/50	35/30	25/22	20/18	NF403G	2	400	250,300,350,400	5,250	
								250,300,350,400	5,600	
	50/42	35/30	35/30	25/22	NF603S	3	600	500,600	13,000	
	50/42	35/30	35/30	25/22	NF803S	3	800	700,800	17,500	
	100/85	60/50	60/50	35/30	NF103H	1	100	10,15,20,30,40,50,60,75,100	1,750	
10,15,20,30,40,50,60,75,100								1,900		
10,15,20,30,40,50,60,75,100								2,100		
10,15,20,30,40,50,60,75,100								3,750		
2		225	125,150,175,200,225	4,000						
			125,150,175,200,225	4,400						
			125,150,175,200,225	6,100						
			250,300,350,400	6,100						
3		400	250,300,350,400	7,000						
			250,300,350,400	10,500						
			500,600	15,000						
			700,800	18,300						
4	800	500,600	19,200							
		700,800	22,700							
3	1200	1000	36,700							
		1200	42,000							
4	1200	1000	54,000							
		1200	68,000							
125/100	75/65	60/50	40/35	NF103L	3	100	10,15,20,30,40,50,60,75,100	3,300		
				NF203L			225	5,600		
				NF403L			400	9,100		
				NF803L			800	18,300		
				NF1203L			1200	42,000		
						1200	49,000			
附 屬 裝 置	附屬裝置適用機種		操作把手	電壓跳脫	低電壓跳脫	補助開關	警報開關	補助+警報開關		
	NF-103B		850	(SHT)	(UVT)	(AUX)	(AL)	(AUX+AL)		
	NF-103S/R/H/L		960	790	2,130	550	665	1,030		
	EG-103B/R/H		960	-	-	550	665	1,030		
	NF-203G/R/H/L		1,200	940	2,400	670	800	1,200		
	EG-203R/H		1,200	-	-	670	800	1,200		
	NF-403G/H/L		2,150	1,340	3,200	1,080	1,200	1,600		
	EG-403H		2,150	-	-	1,080	1,200	1,600		
	NF603S,803S/H,1203H		2,540	1,340	3,200	1,080	1,200	1,600		
NF803L		2,540	-	-	-	-	-			