

台製 林石牌 無熔線斷路器

林石 104/07 版

型式	啟斷容量 KA 非對稱值 / 對稱值					機種		極	AF	電流容量 AT (跳脫電流)	定價
	110V	110/220V	220V	380V	440V	一般型	插入式				
BH 系列 (分電盤用品)	5	5	-	-	-	BH	BH	1	50	10,15,20,30,40,50	110
	-		2					100	10,15,20,30,40,50 60,75,100	218 392	
	-	-	5	-	-	-	-	3	100	10,15,20,30,40,50 60,75,100	375 770
	10	10	-	-	-	BHQ	BHQ	1	50	10,15,20,30,40,50	132
	-		2					100	10,15,20,30,40,50 60,75,100	280 530	
	-	-	10	-	-	-	-	3	100	10,15,20,30,40,50 60,75,100	530 800
	15	15	-	-	-	BQL	-	1	100	10,15,20,30,40,50	189
	-		2					100	10,15,20,30,40,50 60,75,100	390 870	
	-	-	15	10	7.5	-	-	3	100	10,15,20,30,40,50 60,75,100	870 990

台製 林石牌 漏電斷路器

林石 104/07 版

型式	啟斷容量 KA 非對稱 / 對稱			額定感應電流 (mA)	機種	極數	AF	電流容量 AT (跳脫電流)		定價	
	110V	110/220V	380/440V					AT (跳脫電流)	固定式	可調式	
純漏電斷路器	2.5	2.5	-	30mA 100mA 200mA 300mA	E-32	2	50	15,20,30		430	
								40		500	
								50		560	
	2.5	2.5	-	30mA 固定 100/200/300mA 可調 (分卡式及插入式) (1P 型) 0.1 秒	E-33	3	50	15,20,30		650	
			40,50						850		
	-	-	1.5					15,20,30		900	
								40,50		1,000	
BH 型漏電兼過載保護	5	5	-	30mA 固定 100/200/300mA 可調 (分卡式及插入式) (1P 型) 0.1 秒	EB-51	1	50	15,20,30,40,50		620	670
	5	5	-					EB-52	2	50	15,20,30,40,50
	-	-	2.5		EB-53	3	50	15,20,30,40,50		1,100	1,150
	5	5	-		EQ-51	1	50	15,20,30,40,50		1,150	1,200
	-	-	2.5		EQ-52	2	50	15,20,30,40,50		1,350	1,400
	10	10	-		EQ-53	3	50	15,20,30,40,50		1,000	1,050
	10	10	-		EG-103B	2	50	15,20,30,40,50		1,200	1,250
	-	-	5		EG-53	3	50	15,20,30,40,50		1,700	1,750
								15,20,30,40,50		1,900	1,950
工業型漏電兼過載短路保護型	10	10	5	30/100/300mA 可切換式 0.1 秒	EG-103B	3	100	10,15,20,30,40,50		2,500	
								60,75,100		2,800	
					10,15,20,30,40,50		5,000				
					60,75,100		5,500				
	30/25	30/25	20/18		EG-103R	3	100	10,15,20,30,40,50		3,100	
						4	100	60,75,100		3,400	
								10,15,20,30,40,50		5,600	
								60,75,100		6,000	
	100/85	100/85	60/50		EG-103H	3	100	10,15,20,30,40,50		4,000	
						4	100	60,75,100		4,500	
								10,15,20,30,40,50		6,600	
								60,75,100		7,500	
30/25	30/25	20/18	EG-203R	3	225	125,150,175,200,225		7,700			
				4	225	125,150,175,200,225		11,000			
100/85	100/85	60/50	EG-203H	3	225	125,150,175,200,225		10,000			
				4	225	125,150,175,200,225		12,000			
100/85	100/85	60/50	EG-403H	3	400	250,300,350,400		14,500			
				4	400	250,300,350,400		24,000			

台製 林石牌 無熔線斷路器

林石 104/07 版

型式	啟斷容量 KA 非對稱值 / 對稱值				機種	極數	AF	電流量		定價
	220V	380V	440V	600V				AT (跳脫電流)		
N F 型 無 熔 線 斷 路 器 — 配 電 · 配 線 用	16/15	10	7.5	5	NF103B	2	100	10,15,20,30,40,50	782	
								60,75,100	998	
	30/25	20/18	12/10	6/5	NF103S	1	100	10,15,20,30,40,50	825	
								60,75,100	910	
						2	100	10,15,20,30,40,50	955	
								60,75,100	1,110	
						3	100	10,15,20,30,40,50	1,100	
								60,75,100	1,235	
	60/50	35/30	25/22	12/10	NF103R	3	100	10,15,20,30,40,50,60,75,100	1,130	
								10,15,20,30,40,50,60,75,100	1,395	
								10,15,20,30,40,50,60,75,100	1,610	
								10,15,20,30,40,50,60,75,100	3,130	
	30/25	20/18	16/15	7.5	NF203G	2	225	125,150,175,200,225	1,740	
								125,150,175,200,225	1,960	
								125,150,175,200,225	2,300	
	60/50	35/30	25/22	12/10	NF203R	3	225	125,150,175,200,225	2,550	
								125,150,175,200,225	2,950	
								125,150,175,200,225	3,050	
								125,150,175,200,225	5,300	
	60/50	35/30	25/22	20/18	NF403G	2	400	250,300,350,400	5,250	
250,300,350,400								5,600		
50/42	35/30	35/30	25/22	NF603S	3	600	500,600	13,000		
50/42	35/30	35/30	25/22	NF803S	3	800	700,800	17,500		
100/85	60/50	60/50	35/30	NF103H	1	100	10,15,20,30,40,50,60,75,100	1,750		
							10,15,20,30,40,50,60,75,100	1,900		
							10,15,20,30,40,50,60,75,100	2,100		
							10,15,20,30,40,50,60,75,100	3,750		
				NF203H	2	225	125,150,175,200,225	4,000		
							125,150,175,200,225	4,400		
							125,150,175,200,225	6,100		
							250,300,350,400	6,100		
				NF403H	3	400	250,300,350,400	7,000		
							250,300,350,400	10,500		
							500,600	15,000		
							700,800	18,300		
NF803H	4	800	500,600	19,200						
			700,800	22,700						
100/85	60/50	60/50	35/30	NF1203H	3	1200	1000	36,700		
							1200	42,000		
4	1200	1000	54,000							
		1200	68,000							
125/100	75/65	60/50	40/35	NF103L	3	100	10,15,20,30,40,50,60,75,100	3,300		
							NF203L	225	5,600	
							NF403L	400	9,100	
							NF803L	800	18,300	
							NF1203L	1200	42,000	
							1200	49,000		
附 屬 裝 置	附屬裝置適用機種		操作把手	電壓跳脫	低電壓跳脫	補助開關	警報開關	補助+警報開關		
	NF-103B		850	(SHT)	(UVT)	(AUX)	(AL)	(AUX+AL)		
	NF-103S/R/H/L		960	790	2,130	550	665	1,030		
	EG-103B/R/H		960	-	-	550	665	1,030		
	NF-203G/R/H/L		1,200	940	2,400	670	800	1,200		
	EG-203R/H		1,200	-	-	670	800	1,200		
	NF-403G/H/L		2,150	1,340	3,200	1,080	1,200	1,600		
	EG-403H		2,150	-	-	1,080	1,200	1,600		
NF603S,803S,H,1203H		2,540	1,340	3,200	1,080	1,200	1,600			
NF803L		2,540	-	-	-	-	-			